


- · Cavity Filters & Pager Interference
- The Australian Traveller's Net
- · Willis Island Story



THE WIA RADIO AMATEUR'S JOURNAL



TS-4058 and TS-6005 for toops, dependable performance. Products of workfamous Kennerod engineering, flees we versible. Fire rancoviers and designed for SSB, CW, AM, FM and FSK modes of operation or all Annative bands, including the VARIO-flows. To further endince capabilities, considerable optional DSP-100 Gight Signal Processor. The AT-450 Automatic Antonian Policy Conference on the Conference of the Conference of the Conference of the TS-6005. Alony with authorization postages and the highest besties of quality and partiremance, both modes of the yell another advantages: ultra-compact dimensions belled Policydistions and modes. Enjoy all the advantages of these superior features: Biopenier seeling dynamic range of 1086B # Kenwood asculative AP (Advanced Intercept Point) systems # Cameral coverage incolure AP (Advanced Intercept Point) systems # Cameral coverage incolure option (TS-4005 to); # Ultra-compact design # Excellent split frequency operation # CW pitch and CW reverse mode selection 10 folgial for merica and multi-function LCD display ## 18 first circuit trushing # 100 memory channels # 100 wates output on all HF banks # 250 wates output on 50 to 54 MHz is known by April 100 memory channels # 100 memory channels # 100 wates output on all HF banks # 250 wates output on 50 to 54 MHz is known by April 2000 conty)

HF TRANSCEIVER TS-450S/TS-690S HF TRANSCEIVER

KENWOOD ELECTRONICS AUSTRALIA PTY. LTD.

8 Figtree Drive, Australia Centre, Homebush, N.S.W. 2140 Phone (02) 746 1519, (02) 746 1888, Fax (02) 746 1509 Call now for further information and the name of your pagest authorised Kenwood dealer.

ı	Kenwood	Electronics	Australia F	by Ltd	only	warrants products	
١	ourchases	from their	authorised	Austri	ăan.	dealers.	

Please phone, mail or fax for in	formation
Name	
Address	
***************************************	Postcode
Publication	Issue
Model	

ALO

RSOTE

BOASC

Post Office before contacting the registered office of

the WIA.

• Wireless Institute of Australia 1992



THE WIA RADIO AMATEUR'S JOURNAL

ISSN 0002-6859

July 1992

Amateur Radio is published by the Wireless Institute of Australia, ACN 004 920 745 as its Official Journal, on the last Friday of each month.		04 920 745 as its	CONTENTS Technical				
EDITORIAL GROUP Publisher		OUP	Measurements on Balanced Lines Using the Noise Bridge & SWR Meter8 Lloyd Butler VK5BR				
Bill Roper VK3ARZ Editor Bill Rice VK3ABP			Pager Interference Part I				
	Managing Ed ham Thornton	itor	Telecom Pagers Cause Much Anguish for 2m Operators				
Pe	or Technical iter Gibson Vi	C3AZI.	2m Cavity Preamplifier Mai Le Maistre VK3KSA	16			
Ev	rechnical Edi van Jarman Vh Gil Sones VK3 Bob Talt VK3E	(3ANI IAUI	A Support for the Rotary Beam JA Gazard 55				
	Marketing		General				
	om Eyres VK uce Kendall V		14,116 The Australian Traveller's Net	19			
C	ontributing E	ditor	Fred Greening VK2DZL				
	on Fisher VK			23			
	TE TECHNIC id Brownsey \		Stephen Pall VK2PS				
	on Graham VI		The Story of Stephen Frith Part 4				
	hil Steen VK4		H Karl Saville VK5AHK				
	oy Watkins VI		The Horrors of CW				
	ROOF READ		Sale Kerkwer VK2137				
Jim Payne VK3AZT			Operating				
J	ORAFTING			36			
Vi	icki Griffin VK		Contests				
	ADVERTISI		1992 Remembrance Day Contest Rul	es			
Brei	rda Edmonds June Fox	VK3KT	16th WA 3.5MHz Contest Rules	38			
	CIRCULATIO	ON					
01	Margaret Alli ris Russell VK						
	utions and co		Columns				
concerning	the content of	Amateur Radio	Advertisers' Index56				
sho	Amateur Rac		ALARA45	Over to You - Members' Opinions 50			
	PO Box 30		AMSAT43	Pounding Brass42			
Cau	Ifield South V		Club Corner47	QSLs from the WIA Collection47			
REGISTERED			Divisional Notes	Repeater Link46			
3/105 Hawthorn Road Caulfield North Vic 3161			VK2 Notes, VK3 Notes, 5/8 Wave . 48	Silent Keys - Obituaries49			
Telephone:	(03) 528 59	62	VK6 Notes49	Spotlight on SWLing45			
Fax:	(03) 523 81		Editor's Comment2				
Business hou	rs: 9.30am to	3pm weekdays	Education Notes44	VHF/UHF an Expanding World40			
Deadlines	Editorial	Hamads	FTAC Notes44 Hamads 54	WIA Directory			
August September	13/7/92 10/8/92	15/7/92	Intruder Watch	WIA QSL Bureaux56			
October	10/8/92 7/9/92	12/8/92 9/9/92	Morseword No 6451	THIN GOL DUIEBUX			
the 15th of the m	onth of Issue, a	is not received by nd you are a ase check with the	Cover				

Stephen Pall VK2PS on P23.

Willis Island - A tiny speck in the Pacific Ocean, See Willis Island - VK9 by

Amateur Radio Service

A radiocommunication service for the purpose of self-training, intercommunication and technical investigation carried out by amaleurs, that is, by duly authorised persons interested in radio technique solely with a personal aim and without pecuniary interest.

Wireless Institute of Australia

The world's first and oldest National Radio Society
Founded 1910

Representing the Australian Amateur Radio Service — Member of the International Amateur Radio Union

Registered Federal Office of the WIA: 3/105 Hawthorn Road, Caulfield North, Vic 3161

All mail to:
PO Box 300, Cauffield South, Vic 3162.
Telephone: (03) 528 5962
Fax: (03) 523 8191

Business Hours: 9.30am to 3.00pm on weekdays

Ron Henderson

George Brzostowski VK1GB

Kevin Olds

Neil Panfold

Ash Nallawalla

Roger Harrison

David Wardlaw

John Ingham

Leigh Baker

Gordon Loveday

Rob Apathy

WHIDE

VK1KRA

VK10K

VK3CIT

VK4KAI

VK6NE

VK2ZTB

VK3ADW

VK5KG

VX3TP

General Manager and Secretary: Bill Roper VK3ARZ

VK2 Federal Councillor:	lerry Hyeland	VK2UX
VK3 Federal Councilior:	Peter Maciellan	VK3BWD
VK4 Federal Councillor:	Murray Kelly	VK4AOK
VK5 Federal Councillor:	Bill Wardrop	VK5AWN
VK6 Federal Councillor:	Neil Penfold	VK6NE
VK7 Federal Councillor:	Jim Forsyth	VK7FJ
	CO-ORDINATORS	
AMSAT:	Graham Ratcliff	VK5AGR
Awards:	John Kelleher	VK3DP
Contest Manager:	Neil Penfold	VK6NE
Education:	Brenda Edmonda	VK3KT
EMC:	Hans Ruckert	VK2AOU
Federal Tapes:	Ron Fisher	VK3OM
FTAC:	John Martin	VK3ZJC
Historian:	John Edmonds	VK3AFU

Editor's Comment

Bill Rice VK3ABP

Big Country, Small World

R ON FISHER VK3OM and I are now well into the sun-chasing safari which began on Friday 22 May. Late that night my XYL Margaret and I Joined Ron and Lynette in one of Albury's caravan parks, and next day continued in convoy.

Our first tourist destination was the Japanese memorial garden at Cowns, but the night before, at dinner in the Services Club, we noticed at the next table a gentleman wearing a WTA windcheater Who should it be but Tom Dowling VK4OD and XYL Nancy on their way home from the 50th anniversary RAAF Radar Reunion, You will read all about this celebration in a near-future issue of AR.

After visiting the gardens (a truly magnificent little piece of japan transplanced to Australia) we also looked at the nearby war cemeers, and then set out for Parkes (some 130km away) where we visited the CSIRO radio telescope with its 64m disk. later, arriving at Dubbo for two nights, we were spotted by Ro VKNIND, also in the same cara-

van park en-route to Bendigo. We spent most of Monday 25 May at the very impressive Western Plains Zoo, then went on to Coonabarabran and the Warrumbungles National Park on Tuesday. This proved to be quite an amateur get-together! Gordon VK3GRI was also spending a few days there, while another Gordon, VK2TGC at Gilgandra, gave us useful information about the local roads. We visited the Siding Spring Anglo-Australian Astronomical Telescope on 27 May. With a mirror diameter of 3.9 metres. this is the largest such telescope in the southern hemisphere, and the building which houses it is 50 metres high. Twenty-seven astronomers are currently working there, and the scheduling of time on the instrument must be a major feat of administration!

In the car park, as we prepared for our Traveller's Net check-in, we met WK4AO. An nephew of the famous aviator of some 60 years ago, Bert Hinkler, his name is also Bert Hinkler. Aprospective amateur couple near us in the Warrumbungles were old friends and colleagues of our general manager, Bill VK3ARZ. Later, at Bourke (another was the property of the company of the Warrumbungles were old friends and colleagues of our general manager, Bill VK3ARZ. Later, at Bourke (another was stept framilly in the town was stept framilly in that town

The coincidences eased a little after that. The next four nights were at Cunnamulla, Charleville, Blackall and Longreach. Who should be among the first people we saw at Longreach, but friends from our own subult of Melboome? They live 'jast around the corner' from ust I am writing this on 3 June at Longreach, home of Eddie

'just around the corner' from us! I am writing this on 3 June at Longreach, home of Eddie VK4KAA, who makes a very tasty nut-loaf! 'As the crow flies' it is just 1000 miles or 1600km from Melbourne. We have covered 2600km of roads to get here. By the time we arrive home, in mid-July, we will have travelled about 10.000km through all states but WA and Tasmania. Yet every day we will have 'kept in touch' via the 20m Travellers' Net: and nearly every day Ron will have made contact on 20m with friends in the UK (notably G4INH. GW4DIW). Australia is truly a 'big country', but amateur radio

makes the whole globe a 'small

world'.

President:

VK1 Federal Councillor:

Honorary Legal Counsel

QSL Manager (VK9, VK0)

Int'l Travel Host Exch:

Intruder Watch:

WARC & CCIR

Standards:

WICEN:

LARU

WIA News

From the WIA Federal Office

Role of the

Annateur adio magazine, we quoted from the Calendar of the IARU on improper use of the annateur bands. It was not saired at the time that the material had been prepared by Michael Owen VSSR, who is now the vice-president of the IARU. It is perhaps worth quoting Michael's first two paragraphs.

1. The ITU is not a police

force.

Note: All times are local. All fracuencies MHz.

The histernational Tolecommunications thinos resixe by strine of an agreement between nations to coopensise on ielecommunications matters. This agreement has been entered into freely by most of the sovereign nations of the world. However, by agreeting to respect the regulations and to use the mechanisms of the III, then entitions have ngt relinquished their sovereigns. Each country reserves.

the right to do what is necessary

to protect its own vital national

interests, and to determine for itself what those interests are.

Thus the ITU bas no enforcement authority. ITU officials and staff may educate an administration that is responsible for stations causing barnel for stations causing barnel ministration to take corrective action. But they may not force an administration to act.

 Our mission as radio amateurs is to persuade administrations to protect our interests.

When radio amateurs suffer barmful interference from stations operating in violation of ITU Radio Regulations, it is the national telecommunications administrations, and not but ITU, that have the power to provide relief. Each LARU membervide relief. Each LARU member-

society is obligated to promote the objectives of the IARU: the protection promotion and advancement of the Amateur and Amateur-Satellite Services within the framework of regulations established by the ITU. Part of this obligation is to seek the assistance of your own national telecommunications administration in resolving interference problems caused by improper use of Amateur Radio allocations. (In some countries. there may be only limited obportunities to seek such assistance. In particular, it should be remembered that no member-society is ever required to act in a manner that is contrary to the laws of its country.)

The IARU Resolution 91-1 which followed from the discussions details procedures to

WIA DIVISIONS

The WIA consists of seven autonomous State Divisions. Each member of the WIA is a member of a Division, usually their residential State or Territory, and each Division books after amateur radio affairs within their State.

Division	Address	Officers			Weekly News Broadcests 1992 F		
VK1	ACT Division	President	Christopher Davi	www	3.570MHz		\$70.00
	GPO Box 600	Secretary	Jan Burni	VKIBA	2m ch 6950 Flebroadcast Mondays Spm	(C) (S)	
	Carbana ACT 2601	Transurer	Ken Ray	VKIKEN	70cm oh 8525 2000 hrs Sun	(00)	\$42.00
	Phone (06) 247 7006	I PUMBLISH.	Non Poly	WHATH			
	Prione (06) 247 7006				From VK2WI at 1045 and 1915 on Sunday on the following		\$66.75
,9418960	NAME OF STREET		DEMINION OF THE RESERVE	No.	frequencies and modes: (*1045 only) 1.845 AM; 3.595 AM	(G) (S)	
V/C2	NSW Division	President	Roger Hanley	VK2210	morning and SSB evenings; 7.146 AM*; 10.125 SSB; 24.910 SSB;		\$38.75
	109 Wigram St	Secretary	Bob Lloyd-Jones		28.320 SSB; 52.120 SSB; 52.525 FM; 144.120 SSB; 147.000 FM;		
	Partametta NSW	Transurer	Bob Taylor	WC2ACE	438,525 FM: 1281,750 FM: On reley on behalf of VK2WI on		
	(PO B ox 1066)	(Office hours	Mon-Fri 1100-14	00	18.120 SSB; 584.750 ATV Sound, Ch 35, Sydney region.		
	Perremette 2124)		Wed 1900-2100)		Plus automatic releva to 2m receaters surrounding Sydney and		
	Phone (02) 669 2417				ingruelly to many country repeaters. News headlines by phone		
	Fax (02) 633 1525				(02) 552 \$188; General Divisional Information (02) 651 1489.		
VK3	Victorian Division	President	Jim Linton	WOPC	1,840MHz AM, 3,615 SSB, 7,085 SSB, 147,250 FM/R) Mt Macridon,	(F)	\$72.00
	40G Victory Bouleward	Socretary	Barry Wilton	AXCEXA	147.225 FMFD Mt Baur Baur	(G) (S)	\$59.00
	Ashburton Vic 3147	Treasurer	Rob Halley	VICINIZ	148 JCC FMFO Michael 146 700 FM (Ft) MT. Denderson		\$44.00
	Phone (03) 885 9261	Office hours 0	830-1530 Tue & Th	4	436.075 FM(R) Mt St Leonard 1000 hrs on Sunday	44	
VK4	Queenstand Division	President	John Aarsee	VK4QA	1.805, 3.605, 7.118, 10.136, 14.362, 18.132, 21.175, 24.970, 28.400.	(F)	670.00
	GPO Box 638	Secretary	Kon Ayers	AKNED		(G) (S)	
	Brisbane Old 4001	Transurer	David Travis	VK4ATR	52 525 majoral 2m recenture and 1296, 100 0900 hvs Sunday		\$42.00
	Phone (07) 284 9075				Repealed on 3.606 & 147.150MHz, 1930 Monday	(~)	
VK5	South Australian Division	President	Rowland Bruce	WKSOU	1820kHz 3.550kHz, 7.005, 14.175, 28.470, 53.100, 145.000.	Œ	\$70.00
	34 West Thebarton Rd	Secretary	John McKeller	VKSBJM	147.000 FM(R) Administr. 146.700 FM(R) Mid North. 146.900 FM(R)		\$56.00
	Thebarton SA 5031	Transume	Bill Wardroo	VICSAWW	South East, ATV Ch 34 579,000 Adelaids, ATV 444,250 Mid North		\$42.00
	(GPO Box 1234				Barness Valley 148.825. 438.425	14	
	Adminide SA 5001)				INT) 3.565M 146,500, 0900 hrs Sunday		
	Phone (08) 352 3428				(N1) 3.500M 146.500, 0600 NF SURGRY		
			Cearging Thin		146,700 FM(R) Perth, at 0930 hrs Sunday, relayed on 3,580, 7,075,		\$60.75
VKII	West Australian Division	President	Cliff Bastin	VXXLZ	14.115, 14.175, 21.185, 28.345, 50.150, 438,525MHz, Country relays	(G) (S)	\$48.60
	PO Box 10	Secretary	John Fernan	VICIAFA	3582, 147,350(R) Busselton 146,900(R) Mt William (Burbury)	(X)	832.75
	West Perth WA 6005	Treasurer	Bruce Hedland-		147.225(R) 147.250(R) Mt Seddlebeck 146.725(R) Albany		
	Phone (09) 388 3888		Thomas	VK800	146.825(R) Mt Barker Broadcast repeated on 146.700 at 1900 hrs		
VX7	Tasmonian Division	President	Tom Allen	WOL	146 700MHz FM (VK7RHT) at 0830 hrs Sunday relayed on 147,000	(F)	\$67.00
	148 Derwert Ave	Secretary	Ted Beard	WK7EB	(WCFBAA), 146,750 (WCFFWW), 3,570, 7,090, 14,130, 52,100,	(G) (S)	\$53.65
	Undistame Tas 7015	Treasurer	Peter King	VK7ZPK	144.100 (Hohart) Repeated Tues 3.590 at 1930 hrs		\$38.00
VKB	(Northern Territory) is gart	of the VICE Divin	on and relies hose		Membership Grades Three-veer members	hip avai	aldell

be followed in notifying improper band use to the Monitoring Service, and action that will be taken by the IARU.

You QSL?

The Federal Awards Manager recently advised he has received many complaints from overseas about the low rate of QSLing by Australian smateurs. (A letter from an English SWL on this subject was published in the April 1992 issue of Amateur Radio magazine).

Historically it was traditional that all first contacts were confirmed by the exchange of OSL cards, but this custom seems to be declining. This should not be due to the costs of postage when the OSI, Bureaux are functioning, but it may be because of the current high costs of getting cards printed. Members should be aware that, for confirmation for award purposes, a received card can be endorsed "Confirmed", signed and returned through the Bureau for practically no cost. Members who do not intend to OSL should advise their contacts of this at the time rather than simply not replying to cards received

Chain

Lottors
Information reached the Pederal Office recently from a member that a chain letter, labelled "for Hams only", is in circulation. It appears to be using callsigns picked at random, and requires the recipient to send money to the other names on the list. Be warned that this type of operation does not find favour with health with the pedical properties of the pedical properti

Looking for that Article?

The WIA "20 year" index is nowa 24 year index. It includes all articles published in Amateur Radio magazine since 1968, listed in over 25 categories. Members who wish to tracearticles without having to go through annual indices for several years may obtain copies of the index either on IBM format computer disk (in ASCII or DBP), or as a hard copy print-out. Disks cost \$10.00 teach, the printout \$5.00, including possage.

News from the IARU

As a result of a recent poll of member societies, the IARU has announced that the Lithuanian Amateur Radio society has been admitted to membership, making a total of 129 member-societies.

At the Region 3. October 1991 meeting in Bandung, it was recommended that the Secretary of the IARU write to the Burma Amateur Radio Transmitting Society, at its last known address, stating that it is no longer seen as representing the interests of its radio amateurs, and that its rights as an IARU member-society are suspended. As the Secretary's letter has been returned as undeliverable, the IARU Calendar of 15th May 1992 gives notice that this suspension has been carried out.

The Eleventh International Wroclaw Symposium and Exhibition on Electromagnetic Compatibility will be held in Wroclaw, Poland on 2 - 4 September 1992. Included in the program is a session on "EMCin Amateur Radio Service". The organiser is Henryk Cichon, SPZDZ, Converor of the IARU Region 1 EMC Working Group

Radio Frequency Band Plans

The DoTC Newsletter for May 1922 announces changes to the band plans for the VHF Mid Band (70 - 87.5 MHz) and VHF High Band (148 - 174 Mhz). The introduction of a two-frequency operation with narrower 12.5

kHz channelling over much of the bands is expected to help make spectrum space available for mobile services in areas of high demand.

1992 VK Novice Contest

This is a reminder that logs forthe popular VK Novice Contest, which took place over the weekend of 20th and 21st June, must reach the Contest Manager by 26th July 1992.

Remembrance Day Contest

Talking of contests, have you started your preparations yet for the big contest of the year, the 1992 RD Contest? This year's contest will be held on 15 - 16th August, and the rules appear in this issue of Amateur Radio magazine. Make sure you know where to find them when the Contest date arrives.

WIA Membership

Analysis of WIA membership figures over the past couple of years reveals that, although the number of licensed amateurs in Australia is still increasing, the percentage of the amateur population that maintains its WIA membership is slowly decreasing.

As at 31st December 1991. DoTC figures show a total of 17569 individual amateur radio stations. At that time, the WIA membership stood at 6758, ie. about 38.5 %. This figure approaches more nearly to 50 % when inactive operators and multiple callsigns are taken into account, but it still adds up to the fact that less than half the licensed amateurs in Australia are carrying all the costs of WIA activities such as WARCs, international representation, DoTC liaison, and bandplanning which benefit all Australian amateurs Also of concern is the data

Also of concern is the data Members are reminded that that shows the non-renewal of responses to the draft

WIA membership is highest among the newer members, that is those of only one or two years membership standing. It may be that this group is more apt than members of long standing to feel the effects of the current economic situation but this seems unlikely. Apparently the strength of the WIA is in the members who have been amundforSvearsormore After that time, members seem to drop out only in response to severe financial pressure, a loss of interest in amateur radio as a leisure time activity, or strong dissatisfaction with some aspect of the W/IA

What does the WIA have to do to hold the new members for 5 years? The WIA would be interested to hear members' ideas on either the reasons for the membership losses, or ways of providing improved services which may help to reduce the loss.

Incidentally, it is worth noting that the membership analyiss shows the most effective membership recruiting, and presumably retention, is that carried out on a personal basis by committed members. When was the last time YOU signed up a new WIA member?

Advertisers in Amateur Radio

Amateur radio magazine is always happy to print advertisements from members, whether or not they relate to radio equipment. Rates for advertisements for any size from business card to full page are available from the Federal Office. Members are requested, also, to inform dealers who advertise with the magazine that their advertisements are noticuted. Leads for new advertisers supplied by members will be promptly followed up.

Deregulation of Licence Conditions

Conditions

Members are reminded that

deregulated licence conditions published in the June edition of Amateur Radio magazine, should reach the DoTC by 17th July. Please remember to also send a copy of any comments you forward to the DoTC to the WIA Federal Office so that we

are aware of members' views. Thank you to those eagle eyed members who pointed out the apparent curtailing of the hands for Unrestricted licensees. No, this was not a result of secret deals between the WIA and the DoTC to limit the activities of unrestricted licensees. It was an error in the deletion of some duplications that had occurred at the typesetting stage, and there was NO ulterior motive.

The "missing" bands were clearly shown in the adjacent listings of frequencies for Limited and Combined licensees.

It is suggested that the small handful of vocal WIA knockers do their best to recover from the excess of adrenalin brought on by this typesetting error, and cast around for something else to complain about.

Intruder Watch

One of the matters raised with the DoTC representatives at the May WIA Federal convention was the action taken on Intruder Watch reports. Although DoTC takes action on many of the confirmed reports, the priorities of other countries may differ from ours, so there is no guarantee that any other administration will take action.

In addition to the WIA, the DoTC also finds it unsatisfactory when no response is received from other administrations in answer to approaches made on the basis of reports from WIA Intruder Watchers. However, the DoTC has agreed to provide the WIA with as much information as possible on the results of action taken.

If you wish to provide a valuable service to amateur radio. why not join the Intruder Watch team. You can do that by contacting the Federal Intruder Watch Co-ordinator, Gordon Loveday VK4KAL, OTHR.

RF Pollution

One of the working parties set up at the WIA Federal Convention identified RF Pollution. as a matter of high priority for the WIA's consideration. With the rapidly increasing usage of RF in commerce as well as communications, it was seen as appropriate for the WIA to place a high priority on lobbying for standards and controls on such devices and their use.

SEANET '92

In the lune 1992 edition of Amateur Radio we advised the address for information for contacts for SEANET '92. Please note that Jim Jones, the Secretary, can be reached at PO Box 37317, Winnellie, not 37173 as given.

Next Shuttle Flight

STS-50, the next SAREX Shut-

tle Flight, was scheduled for launch on 22nd June 1992. The Shuttle Amateur Radio Experiment is a secondary payload to the shuttle's main mission, a microgravity laboratory.

On board will be Commander Richard Richards **KBSSTW** and Mission Specialist Ellen Baker KBSSIX, On packet the call sign used will be W5RRR-1: SSTV will use WSRRR/S.

Heath Company Alivo.

Despite contrary reports, the Heath company is alive and well, according to a recent ARRL News Letter. The company's President has recently announced that the company is changing its focus from "the rapidly shrinking electronics kit business to the burgeoning electronics education market." We reported some time ago that the production of Heathkit products was ceasing.

The President feels that the age of the kit is now past because the prices of assembled electronic products are now so

Interference Handbook

The ARRL has recently published a new edition of "Radio Frequency Interference*. Members wishing to obtain this valuable reference should contact their WIA Divisional Bookshops. Arrangements have been made for a review to be published in an early issue of Amateur Radio magazine.

Callsign Number Plates

In the January 1990 issue of Amateur Radio magazine, I announced that Victorian amateurs could now obtain car licence plates featuring amateur callsigns. At that stage orders were being accepted for "custom" plates, in various colours. at a once-only cost of \$280.00. A few enquiries have recently

been received about these callsign number plates from amateurs who were refused a plate, being told by the RTA that a personalised number plate could not have a number except as the last digit.

This may be true for "nor-

Position Vacant Consequent on Graham Thornton's resignation, there has been some re-organisa-

tion of the Federal Office staff, and there is a vacancy as follows:

POSITION-Part Time clerical at assistant manager level LOCATION WIA Federal Office in Caulfield

HOURS: Three days a week average - hours negotiable

REMUNERATION: Above award rates plus superannuation

OUALIFICATIONS: Essential Superior English skills

Keyboarding experience Desirable

Knowledge of amateur radio and the WIA In addition, the appointee for this challenging and exciting position will be a

dedicated, hard working team member with a sense of humour. ENOUIRIES: (03) 528 5962 between 9.30 am and 3.00 pm on

weekdays

APPLICATIONS: In writing, with CV, to:

MIM PO Box 300

Caulfield South VIC 3162.

mal" personalised number plates, but an exemption from this rule was obtained for "radio callsign" plates, and many amateurs' cars in Victoria are sporting callsign number plates, including VKSARZ.

Members are directed to any Road Transport Authority office, and should firmly insist that the "radio callsign" provision has been in place for some time.

The Federal Office is not aware of the provisions for such a service in other States, and would be interested to hear about what is available.

Managing Editor Resigns

It is with sincere regret the WIA announces that, after three years of dedicated, strenuous effort in outting together Amateur Radio magazine every month, Graham Thornton VK3IY has decided to resign from the position of Managing Editor in order to devote more time to a commercial project. Graham stepped in to assist when the magazine was recovering from a change in the previous nublishing arrangements. and immediately made his expertise and experience felt.

Graham also made his presence felt as part of the staffing of the Federal Office, and as overseer of the team which proofreads each issue of the WIA journal.

The WIA thanks Graham for his hard work and continual efforts to improve the magazine, and wishes him success in his new venture. We have been promised that there will still be contributions to "Knutshell Knowledge" from Graham.

Contributors Please Help

The July issue of Amateur Radio magazine will be Graham's last production. Until a new appointment is made, the magazine will be put together by the Publisher, Bill Roper, the Editor, Bill Rice, and Federal Office staff. It will make the load considerably lighter if regular columnists can arrange to submit their copy earlier than usual to allow extra time for processing.

WICEN Divisional News

Recent developments in the National WICLEN Telephone Bulletin Board Network have been reported by Leigh Baker, the Federal WICEN Coordinator. Leigh's report will be published in fall in the August issue of the magazine, but it is worthnoting that the WICEN Divisions, despite their varying status and disparate charters, are managing to reach agreement on procedures, training and administration.

Co-operation between several states has produced an almost complete national BBs which can be accessed by anyone with the available equipment. For details about access to these phone BBs, see Leigh's report next month.

DoTC Guidelines for Pager Services

ported in WIANEWS that the WIA had commented, at fairly short notice, on a draft DOTC Spectrum Planning Document containing guidelines for the pager service.

Earlier this year DoTC issued Spectrum Planning Document No. SP 5/91, Policy Guidelines for Assignment of Frequencies to the Paging Services. It was examined in detail by John Martin VK3ZIC, Chairman of FTAC, as well as by the two amateurs who had commented on the draft paper. Rob Milliken VK1KRM and Paul Bell VK1BX From their comments a response was prepared and sent to DOTC expressing the WIA's concerns with some aspects of the pager service. Before detailing those concerns however it is worth going over some of the background.

Fromthe beginning amateurs need to acknowledge a couple of points, firstly, the pager service is not operating on amateur frequencies for it is just above 148 Mhr.; secondly, the equipment is designed to good commercial standards. Indeed, the Whis of the opinion the Policy Guidelines mentioned above are generally a good set of technical specifications.

How does no servicent ferrore.

How does pager interference happen? Principally in three possible ways; firstly through an inopportune combination of frequencies, that is by intermodulation product interference. Secondly through cross modulation, that is by information from a strong unwanted signal being imposed on a weaker wanted signal. Thirdly through adjacent channel interference, that is lack of adjacent transmitter selectivity in the receiver or excessive sideband noise from the transmitter where the transmitter can be either the pager transmitter or a dirty local oscillator.

The first potential cause is not new, having been discussed in the property of the potential property of the potential property of the potential property of the property of t

The second and third potential causes became more apparent around the time pager ourput powers were doubled late last year. Pager transmitters and sensitive, but wide band, amateur transcelvers are not compatible. The selectivity of modennanteut VHE and UHF transcelvers is not good. Indeed many boast very wide receivingranges, which leads to minimal input tuning. The WIA Response

The WIA's response observed the three potential sources of interference identified earlier. It commented that the amateur service was canable, with some assistance from DoTC, of conducting site intermodulation evaluations. It pointed out some repeater groups had changed the frequencies of their repeaters to avoid third and fifth order intermodulation problems even though the amateurs were established on the sites considerably earlier than the pager service. The WIA believed this was the negotiation between parties called for in the DoTC Document

The WIA observed pager transmitter side band noise emissions were a different issue, which amateurs faced due to the pager frequencies being so close to 148 Mhz. DoTC's attention was drawn to the earlier WIA letter of last September, which identified this problem and proposed an approach using filters on pager transmitter outputs, to increase compatibility between the two services. The WIA further observed DoTC had not seen fit to include that technical approach but rather had made an implied but unfortunately a technically incorrect reference to it in their Guideline Document The WIA explained once

The WiA explained once again that once a pager transmitter has radiated a (spurious or unwanted) sideband noise signal in the upper end of the amateur band, it was highly likely it would interfere with amateur PM receives tuned to repeaters operating just below 450 Met. No amount of literawould assist, for the interference was on the amateur working frequency. Filtering, to be effective, must be at the name.

transmitter output.

The WIA pointed out that, unfortunately, the unwanted pager radiation sanitises the upper portion of the amateur.

band for many other possible uses; a problem which DOTC had acknowledged in their Document as also applying to the land mobile service and which was to be overcome by grouping transmitters just above the pager frequencies.

The WIA also expressed reservations about the onisistion of pager receiver performance parameters from the Guidelines, noting the DoTC belief that market forces were expected to regulate the industry. The WIA wished to be assured this would not lead to transmitter power creep to achieve the total system performance specification of a service area of 40 km radius of the main transmitter.

In concluding the comments on the final Document the WIA made several requests:

- a. we wished to know when the Guidelines become effective and asked were all existing pager systems subject to its provisions?
- b. we sought correction of the erroneous statement on filtering at the amateur receiver; c. we sought assurance that DoTC, through its Radio Inspector service, would assist
 - DoTC, through its Radio Inspector service, would assist in the identification of cases of pager transmitter sideband noise interference. That assistance to be principally through the conduct of con-

trolled tests using the Radio Inspector's filters on pager transmitter outputs; and

d. we sought re-assurance the solution of compatibility problems would be on an equitable basis, with due allowance for the earlier operation of amateur equipment from a site, when that was so.

The WIA's final observation was that the difference between devolution of a function and abrogation of a responsibility appeared rather temous in the Document. We believed the public must surely expect a reduction of licence fees or taxes as the EMC/RFI service rendered reduces and the public is forced togo desewhere for that service.

What Can Amateurs Do? With increasing co-siting the planning of amateur services has become a lot more complicated. This is a challenge repeater groups and Divisional Technical Advisory Committees or TACs have to meet. The Federal Technical Advisory Committee or FTAC can help. as can DoTC to some extent. Amateurs will also need to pay more attention to design and engineering of their repeaters. Federal Council recognised this back in 1989 and recommended all repeaters and beacons be constructed to good commercial practices and standards in order to retain claim to prime

sites.

There are several methods available to control pager inter-

ference. They include:

Altering the amateur band plan to avoid the problem frequencies at the top of the 2 metre band. This has already been done on some sites. In some circumstances inverting the repeater frequencies has transferred the interference problem to mobile users of that reneater.

In the case of adjacent channel interference caused by the sidebands or sideband noise of an adjacent transmitter, inserting a notch filter on the amateur frequency in the pager transmitter path is the only solution.

If the pager interference occurs further down the 2 metre band adding filters on the wanted frequencies to improve the front end selectivity and attenuate signals in the top end of the band

Taking a lesson from commercial operators and add subaudible tone squelch to amateur transceivers so that only signals carrying the squelch tone will open the mute.

What can the WIA Do?
As you can see from this news
item, the WIA has commented
twice on the DoTC Guidelines

and will press to have its points accepted.

The WIA needs to inform amateurs on how susceptible their amateur transceivers are to interfering signals. This should be included in all future

equipment reviews.

The WIA could also usefully advise the manufacturers representatives of the problems with their products. These problems may be unique to Australian national band planning circumstances.

Publicity needs to be given to the causes of pager interference through the columns of Amateur Radio magazine; two articles have already been supplied and a third, by an amateur who overcame pager interference, has been promised.

Simple, yet proven effective, remedies contributed by members will be published in Amateur Radio magazine.

It is also obvious the two metre band plan, now twenty years old, is badly in need of review.

Thanks

That's all the WIANEWS we have room for this month. My thanks to the President, Ron Henderson VK1RH, and to Brenda Edmonds VK3KT for their help with WIANEWS.

Bill Roper VK3ARZ

A HISTORY OF RADIO IN SOUTH AUSTRALIA, 1897-1977.

John Ross. ISBN 959 5852 0 6. Published by J F Ross, Adelaide, 1978.

Subject: History of amateur and commercial radio in SA.

John Ross has done an excellent job of writing the history of radio in South Australia, including biographies of early \$6 a natientures, and his book must serve as a model for other VM. historians. In many cases, the biographies are supported by photos of the early amatture stations. It is all tile ad to realise it is no louger possible to do interview with early amatterus such as John did in 1977-78, simply because there are now so few of the old timens left. In addition to a strong amatture and VM. history, John present setteraive research into connercial broadcasting both in \$6 and in context with the rest of Australia. He even provides information on the electronics activities of the Weapons Research. Establishment and the Cedum Satellite earth station, and cowers the \$5 ATV stations too.

which also retailed it.

It is a substantial hard-cover publication of 272 pages, larger than A5 size. I am unsure of the

It is a substantial hard-cover publication of 272 pages, larger than A5 size. I am unsure of the original cost, but it now sells for perhaps \$10-\$20, if you can find a copy.

Reviewed by Colin MacKingon VKZDYM ar

A History of Radio in South Australia 1897–1977

Amateur Radio, July 1992

Measurements on Balanced Lines Using the Noise Bridge & SWR Meter

Lloyd Butler VK5BR 18 Ottawa Ave Panorama 5041

Introduction

T HAVE OFTEN BEEN ASKED how test instruments common to the radio shack could be used to measure the performance of balanced transmission lines. This is a good question considering that instruments such as the noise bridge and the SWR meter, in their usual form, are made for unhalanced lines with a ground common. Furthermore, the usual SWR meter is made for a balance at 50 ohms, and sometimes 75 ohms whereas balanced lines such as TV ribbon and open wire pairs, have a higher characteristic impedance such as 300 ohms. There seems to be little in the amateur radio handbooks addressing this problem so I decided to experiment with a few ideas aimed at using these instruments on balanced lines operating in the HF region.

Initial discussion follows around the use of special balancing circuits which connect to the usual amateur radio noise bridge. The discussion leads no the SWR meter. In the process of experiment, I constructed a special SWR meter for balanced lines and this instrument will be described. To lead up to this subject, the operation of a typical SWR meter for unbalanced lines is discussed. Whilst there is plenty of available construction information on these instru-

ments, basic theory is often just assumed.

Most radio amateurs use these instruments,
but I often wonder how many understand
the significance of what they measure.

Measurements Through Balun Transformers

Measurements into balanced lines can be made through a 1-18 transformed be made through a 1-18 transformed by the primary and secondary tightly coupled. This is easily achieved with the primary and secondary twisted together and wound on one secondary twisted together and wound on one secondary twisted together and wound on the secondary twisted together and wound on ingure the method of connection shown in figure to the method of connection shown in figure posses because there is a capacitance unbalance and the secondary for the secondary that the should be secondary that the should be secondary the should be secondary the should be shou

A more satisfactory connection is shown in figure 1B in which each leg of the line is feld through one of the two windings. For the balanced load, the current 1b in each winding is equal but opposite in phase to each other, and the magnetic field is balanced out, resulting in zero inductance. For any common mode signal, the currents 1d and 1c2 through the two windings are in

phase, hence the device acts as an inductive choke. Pathermore, if there is an unbalance in the load currents Ib1 and Ib2. Intrough the windings due to an unbalance of impedance in the load to ground, the device acts as a choke to the differential value of the current (Ib1-Ib2) or (Ib2-Ib1). In In effect, the transformer acts as an inductive choke to all but the balanced load current.

The Noise Bridge

The noise bridge is inherently a device for measuring the reactance and resistance of an PE load with one side arounded. The notor of its tuning canacitor is grounded and the output to the receiver has one side grounded. I did consider the possibility of a new circuit with the whole bridge floating above ground, but this would have presented some real design problems. However. I found that quite reasonable results could be achieved by connecting the halanced load under test via the choke circuit of figure 1R and as shown in figure 2. For frequencies below 10MHz. I used 12 bifilar turns on an Amidon FTS0-72 torolds I ferrite core. The method of winding does introduce some shunt canacitance across the circuit and five tuens were found to be more suitable above 10MHz to reduce error caused by this canacitance

One problem with the common form of noise bridge is that maximum resistance



Figure 1. Two forms of 1:1 unbalanced to balanced circuit transformer.

measurable is limited to 250 ohms or less. The characteristic impedance of ribbon cable and open wire line is usually much higher than this. In my own home-constructed noise bridge I can switch in extra fixed resistance to allow measurement up to 800 ohms.

An alternative method of measurement is to connect the balanced line via a candelabrum connected balun as shown in figure 3. Two separate transformers, each similar to that of figure 1B are used and an impedance transformation of 4 to 1 is achieved. The circuit is an extension of the figure 1R 1-1 ratio circuit with the inputs of the two transformers in parallel and the outputs in caries Peristance and reactance measure. ments are indicated on the bridge as a quarter of the real value. For example, 300 ohms resistance would be read as 75 ohms.

I found the two methods of measurement to be satisfactory on a transmission line provided the line was well balanced such as when terminated in a centre-fed antenna. If some degree of unbalance exists, such as when the line is matched into the end of an antenna, the measured results are in question. In this case, reversing the connecting leads to the line gives a different impedance reading. I suspect the true impedance in the balanced mode is some form of mathematical mean between the two readings, but I am not sure about this.

I found that the out-of-balance component could be essentially eliminated by using the candelabrum divide by four circuit, but further isolating its input via another balun choke of figure 1B. The complete system is shown in figure 4. Using this system, the transmission line leads could be reversed without change of reading, even if the line was a little out of balance. I recommend this as the preferred measurement system.

Concerning the toroidal transformer design, the inductive reactance of a winding should be sufficient to act as a choke at the impedance being measures (say 10 times the impedance). On the other hand, as few turns as possible should be used to minimise capacitance between the windings.

To achieve high inductance with few turns. a high permeability ferrite core is desirable. The Amidon FTS0-72 cores which I used have a nermeability of 2000

Before making any measurement on an actual transmission line, the circuit can be checked out using a resistor of value equal to the characteristic impedance of the line.



This will give an indication of the accuracy of the system and whether any appreciable reactance is introduced by the balancing network. This is most important towards 30MHz where the result can be most affected by a small amount of shunt canacity and lead inductance.

The BWE Maller

Before introducing SWR measurement on balanced lines. I thought it would be helpful to first discuss the operating principle of the Standing Wave Radio (SWR) bridge. Most radio amateurs could explain that the instrument somehow measures forward wave power and reflected wave power, and that it derives a ratio between maximum and minimum of standing wave voltage or current on the transmission line. Let us examine the operation of the instrument in a little more denth.

The instrument operates by comparing two voltages. One voltage is derived from the voltage across the line and is proportional to and in phase with that voltage. The other is derived from the current through the line and is proportional to and in phase with that current. One type of instrument uses a loop run along in parallel with a length of the line to inductively couple the current component. The voltage component is canacity counled into the loop. Most SWR meters are also calibrated in power. and this particular instrument, more often used at VHF/UHF, gives a power reading which varies with frequency. Hence it requires a power versus frequency calibration chart

An SWR meter, which is often assembled by the home constructor, makes use of a toroidal current transformer to derive the current sourced voltage component and a resistive voltage divider for the voltage component. A typical circuit taken from Amateur Radio. Nov 1969 (ref 1) os shown in figure 5. Because of the methods used to couple each component, the developed voltages are constant with frequency and a calibration chart is not required. For this narticular circuit, operation to 70MHz is claimed. For further explanation of the SWR meter we will make use of this circuit

The voltage derived from current in the line is developed across either of the two 27ohm resistors marked R. The voltage VI is calculated as follows: VI = L.R/T

where I, is the line current and T is the turns on the secondary of the current transformer. (Note: the primary is, in effect, one tum).

The voltage Vv developed from that across the line is equal to the voltage divider ratio formed by VR1 in parallel with R2 and connected in series with R1. The values of T. R. R1 and R2 in parallel with RV1 are carefully selected so that VI = Vv when the load resistance is equal to the nominated line impedance (50 or 75 phms).

Two detector circuits record the summed voltage of Vv and VI. One, which we will call Forward, adds them directly. The other, which we will call Reverse, adds them, but with VI reversed in phase. We now refer to the vector diagrams figure 6. If the load is resistive and equal to line impedance, then for Forward. Vv = VI and the resultant Vr = 2Vv = 2VI (figure 6A). For Reverse, the resultant is zero (figure 6B), hence the ratio R between Reverse and Forward values of

If the load resistance is not equal to Zo, as shown in figures 6C and 6D, a finite value of resultant voltage Vr is developed for Reverse, and the ratio R between Reverse




Figure 2. The noise bridge connected to read in via balun choke.

and Forward values of Vr is finite.

A third case (figures 6E and 6F) shows a load impedance equal to Zo, but reactive, hence the load current is out of phase with the load voltage. Again, a finite value of resultant voltage Vr is developed for Reverse, and the ratio R between Reverse and forward values of Vr is finite.

It can be seen that the instrument is a bridge circuit which balances when there is a resistive load equal to Zo and records by ratio R the degree by which the load deviates in impedance from that resistive value When connected to a transmission line. ratio R also equals the ratio between the reflected wave voltage and the incident or forward wave voltage on the line. In operation, transmitted power is set (or meter sensitivity is set) so that the Forward meter reads full scale representing forward wave voltage down the line. The Reverse meter, representing reflected wave voltage, then reads the ratio R between Reverse and Forward values of Vr. hence representing the ratio between reflected and forward wave voltage. The relationship between standing wave ratio SWR and ratio R is given by the formula:

SWR = (1+R)/(1-R)

The normal practice is to calibrate the Reverse meter scale in SWR as defined by the formula. The Forward meter is calibrated in power based on E squared divided by Zo where E is the line voltage for an SWR = 1.

Most amateur radio operators of today use an SWR meter, but I venture to say they are used more to ensure that a 500hm load is presented to their transmitter than to




Figure 4. The improved soise bridge arrangement for measuring lines using a 1:1 balus choke driving the 1:4 candelabrum circuit.

check SWR on their transmission line. If some form of tuning or matching device is connected between the SWR meter and the transmission, there is no relationship between what is read on the meter and what standing waves are actually on the line.

How often do we bear on the air somece quoting his 2MW = 1.1 to includate how well his airstenna system is adjuuted when in fact he is really telling us how well his irransmeter is loaded to its conrect load unpedance? In the next breath he tellis us that he is using a 2 match or transmeture is using a 2 match or transmeture what sterver and, in reality, has no idea of what standing waive exist on his transmission line, or what power loss they might be causing.

We can use the SWR meter to check the performance of a dummy RF1 load. We often see a dummy load quoted as having a standing wave ratio of some value at a given frequency. This, of course, if an anomalous declaration. The path length through the core of the dummy load can be considered as but a fraction of a wave-length, hence there are virtually no standing waves. What they really mean is that, using an SWR bridge to check deviation in impedance from the nominal value of dummy load resistance R, a given value on the SWR scale is recorded. It means the impedance load produces a SWR reading similar to a transmission line of Zo = R and operated with that SWR.

operated with that SWR. So the SWR meter is not really some device which, by some form of magic, separately plucks out the forward wave and the reflected wave to calculate SWR. It is a bridge circuit which records impedance deviation from a given nominal resistance and is calibrated in terms of transmission line SWR.

If it is not obvious, to measure SWR on the transmission line, the meter must face the line. If the line is balanced, or is a different 20 from that for which the meter's designed, some form of transformer is required. As will be discussed in later paragraphs, this addition in itself can produce some questionable readings on the meter.

Owing to loss in the transmission line, the SWR reading will always be higher at the fair or antenna end of the line. It is good to check out the fair end, but somewhat difficult if located high out in space. If the line is balanced, a balanced SWR meter would seem to be the order of the day As you will see in the following paragraphs, I, always and earn effort to design one I must admit that, up to now, I have stayed at aground level and have not attempted to use a safet.

Concerning figure 5, I built a unit based on this type of circuit some years ago. For the record, I added a small capacitor across R2 to make the unit balance properly at the upper end of the HF band This seemed to be necessary to correct for a few picofands




Figure 5. Typical SWRPower moter for MF frequencies (from Ameliaum Radio November 1959). The sensitivity ranges given in St am d5 is har doubte the correct figure. Those in the caption are correct. Circuit of the basic Frequency-independent Directional Wattmeter, with four ranges is corresponding to full scale deflections of 0.5, 5, 50 and 500 watts in Sobas lines, when the value of 12 (including WRt, if fitted) should be 220 ohms. For coaxial cable acts as an electrostatic screen between its centre conductor and the secondary winding of the toroidal transformary the cable length is

	FORWARD	REVERSE
RESISTIVE LOAD EQUAL TO TO	V2 VV RESULTANT VA = 2V2 = 2V4	RESULTANT VR = ZERO
	Α	В
RESISTIVE LOAD NOT EQUAL TO EO	V _X = V _X + V _V − >	₩ = ₩-Vs
	c	D
LOAD IMPEDANCE EQUAL TO ZO BUT PARTLY REACTIVE	¥ - × 5	LVx VVA
	€	F

Figure 6. Vector diagrams for the SWR meter (see text).

of stray capacity in parallel with R1. This might be a useful tip for someone else building such a unit. An SWR Meter for Balanced Lines

As part of the balanced line exercise, I set out to build an SWR meter for balanced lines. It seemed a simple matter to base the design on the circuit of figure 5, but with a toroidal current transformer in each leg and a balanced voltage sensing circuit. The outer cover and braid were stripped off some coax cable leaving the centre conductor insulated by the coax dielectric. A length of this was slipped through each toroidal core to form the two legs of the metered transmission line. A short length of braid was ultimately put back over the dielectric where it went through the toroidal core to form an electrostatic shield. I found this was necessary to correct a balance error caused by capacitance coupling into the winding around the core. (Of course, the unbalanced versions such as figure 5 all used the braid shield, so this was not unexpected).

The circuit of the balanced meter is shown in figure 7. The circuit constants have been worked out for a balance with 300 ohms resistance, which suits common forms of TV ribbon and open wire line. The secondaries of the two 12-1 current transformers (T2, T3) are connected in series (They also

work quite well when connected in paralle!). The voltage divider network (R10 in series with R6/R7 and R8/R9) is coupled into the signal combining and detector/ metering circuit via transformer T4.

It all seemed straightforward, but I experienced a lot of trouble with circuit balance and common mode currents. I found it necessary to isolate the transmitter source with balun choke T1 to improve the balance at the instrument input. (I should point out that the source was already fed via a standard 4 I transmitting balun) For Ti, a 30mm diameter ferrite core was used to accommodate the transmitter power This was a high permeability Philips type which I happened to have on hand

A problem of line balance on some lines showed up as a different SWP, value when the line pair legs were reversed. (This was a similar problem to that experienced when using the noise bridge). The problem was compounded by unbalance in the source circuit and hence the reason for the input choke.

It is booking transformer T4 olavs an importance of the contract of

to a conventional transformer to plays an important part imminising the effects discussed A conventional transformer connection as in figure 1A seemed more effective for this particular circuit than the choke connection figure 1B.

I tried all sorts of balancing arrangements, butfinished with the circuit as shown. The measures taken did not completely eliminate response to out-of-balance signal, but the level of this response was reduced enough to be tolerated.

Other Impedances

The balanced SWR meter a designed for a balance at Zo = \$00 ohns, but other impedances could be used by changing the value of resistor RIO. The value of RIO is inversely proportional to Zo. For example, for Zo = 600 ohns, halve the value of RIO is lavent tried any other Impedances, but that is how it can be worked out. For correct power calibration, the meter resistors must also be changed. These are changed in inverse proportion to the square root of larged and impedance change. For Zo = 600 ohms,




Figure 7. VKSRR SWRipower meter for 300-ohm balanced lines. T1 - 6 biffliar turns on Philips TDK2699 30mm diameter toroidal core μ = 800, T2, T3 - 10 turns on Amidon FTSO-72 toroidal core μ = 2000, T4 - 10 biffliar turns on Amidon FTSO-72 toroidal core.

divide the meter resistors by root 2. Checking the Balance

High power 3000 htm non-inductive loads are not easily obtained, but the balance is easily checked by using low transmitter power and loading the SWR meter with a few one or two wats resistors to make you of the power and the power and the lowest power select meet possion gives full-scale forward reading, and this is applied for just long enough to estimate the best power to be a supplied to power the selected for reverse or reflected power, the 3000 hin load should give a low meter reading (near 1:1 SWR) at all HF frequencies.

Motor Calibration

The following can be used to calibrate the meter scale:

mA	Power	mA
0	0	0
10	2	10
17	5	16
25	10	22
33	20	32
38	30	39
46	50	50
50		
	0 10 17 25 33 38 46	0 0 10 2 17 5 25 10 33 20 38 30 46 50

75 Ohm SWR Meter with Candelabrum Balun

Although 50 ohms is the most common operating impedance for SWR meters, many have a switch to select either 50 or 75 ohms. The type of meter which uses resistive voltage division (as in figure 5) can also be easily converted to 75 ohms by shunting the lower resistance arm of the voltage divider.

Another method I used for checking SWR on a 300chm line was to couple a 75chm SWR meter into the line via a 4:1 candela-birm balun pair as shown in figure 8. The toroldal cores of the balun pair needed to be large enough to handle the full IRF power which passes through their windings I used Amidon F500 PT114 fermic cores which are 29mm in diameter. The windings were billiar wound with 19turns on each, whech gave a calculated inductance of 29 merchanner. This seemed to be a good over most of the HF band without too much conscious.

I found this measuring system worked like a charm. None of the problems I experienced with my balanced SWR meter (figure 7) was apparent, and the transmission line legs could be transposed at will. This seemed to be the best system of measurement, its only limitation being it could be used only at the transmitter end of the line.


For measurements at the load or antenna end, the balanced meter would have to be used.

I did try adding a further 1:1 balun choke at the candelabrum input as I had found to be necessary with the noise bridge. However, this did not enhance the performance in any way and, in fact, tended to modify the impedance reflected at the highest frequencies.

One might well ask how the normally used 4: impechanceratio balan connection (figure 9) performs as compared with the candelabrum circuit. This connection is a type of auto transformer and probably does hitle to reject common mode signals. Anyway, when using this type of transformer, I again experienced the problems of a different problems of a different problems.

with the noise bridge). Using the 75ohm SWR meter, the SWR at 21 and 28MHz was 1.2:1, but increased to 1.8:1 at 7MHz, and 2.8:1 at 35MHz. This compared poorly with my candelabrum circuit, which gave a reading with 1.1: over the whole range of 3.5-28MHz.

Now this is an interesting result. Suppose you see this typical broadband balun at, say, 3.5MHz to couple to a transmission line and then adjust your matching at the antenna end by stub or whatever You adjust for a 1.1 SWP on the meter, but a chally achieve a mismatch and standing waves on the line. Of course, the core needs more turns for the lower frequencies. Some time ago! did some tests with this core using the 11 ratio warding connection and a 50 him.



gure 8. Measurement of SWR on a 300ohm balanced line with a 75ohm WR meter and candelabrum circuit. T1, T2 - 19 bifilar turns on Amidon 1500 Elliman ferrite core, µ = 125




Figure 9. The usual 1:4 balus circul

ent answer when the line leg pairs were reversed.

The balun transformer used for figure 9 type balun was the one that can be bought as a 1kW kit with a Amidon T200 iron powder core. Fourteen bifliar turns were placed on the core When terminated in a 3000hm resistance, this balun reflected a considerable reactive component at the lower HF frequencies. (This was verified

load. I came to the conclusion that, for better performance, the number of turns should be increased to around 20 for frequencies below 5MHz and reduced to around six turns for frequencies above 10MHz Anyway, there is a message here, Do not take your balun transformer for granted. Check it out at the frequency of operation using the SWR meter and with its secondary terminated in a dummy resistance equal to working load impedance Fortunately, even if mismatched, line losses at the lower HF frequencies are small, hence we are usually able to tolerate the effect I have discussed without recourse to rewinding the transformer.

Summary

Based on much of my own experimentation, Have described how common instruments in the radio shack can be used to make impediance and SWR measurements on balanced transmission lines. Measurement methods involve the use of particular types of balancing circuits which work in SWR meter. A specific SWR meter for 3000-him balanced lines is also described. Included in the discussion is a description of how an SWR meter works, and some comments on how it is generally used in the radio shack

I think there is material in this article to invite further discussion on the measurement of balanced lines and the use of the two instruments put to use. Perhaps some of our-rades have some other-discas which I hope they can test out before going to primit it is one thing to put up a theory in the one think particular project (simple as It may seem) was one with plenty of those holden little difficulties.

1 P G Martin G3PDM - Frequency Independent Directional Wattmeter and SWR Meter - Amateur Radio, November 1969.

2 Lloyd Butler VKSBR - The Merits of Open Wire Lines - Amaieur Radio, Sept 1991 3 Lloyd Butler VKSBR - Transmission Lines -

3 Lloyd Butler VK5BR - Transmission Lines -Measurements of their Characteristics - Amateur Radio, October 1989

ELECTRONIC WORLD DISPOSALS

NOW OPEN

For that hard to get or unusual item, give us a call. Big range of goods and components in stock.

We are interested in purchasing surplus and disposal components.

27 The Mall, cnr Eastfield and Bayswater Rds South Croydon Vic 3136

Ph: (03) 723 2699

Remember to leave a three-second break between overs when using a repeater

Pager Interference

Lately, a number of amateurs have been suffering

Part I

Ron Henderson VK1RH 171 Kingsford Smith Dr Males EATH

pager interference, that is the presence of short burst like data signals in their 2m transceivers. For those who live near pager transmitters in busy cities, the bursts are almost continuous and most annoying as they break the mute.

HAT IS CAUSING THIS interference, you might ask. What is the WIA doing about it and, even more importantly, what can the individual do to reduce its effects.

Pagen are a system of relatively high power transmitters, operating on 25th, channel spacings from 148.0125MHz utpervarfs. Yes, they expla above the amile pocket are varied by a subscriber client. In all pocket size receiver carried by a subscriber client, usually to give them a message. The pager system has a service area of 40km radius from the main transmiter and may supplementary transmiters on the same frequency for gap-litting purposes.

Throm the beginning we should establish a couple of points, firstly, the service is not operating on amateur frequencies, secondly, the epupment is designed to good commercial standards. Pagers are regulated by the recently issued DoTC. Policy Goldennes of the points of Presignes of the Paging Services, Spectrum Planning Dozument No SFS-911. The WIA commented on the first dart of that document and has sent influence on the recent issue.

How does pager interference happen? Principally in three ways, through an inopportune combination of frequencies (intermodulation product interference), crossmodulation (information from a strong unwanted signal imposed on a weaker wanted signal orthrough addicent channel

interference (lack of adjacent transmitter selectivity in the receiver or excessive sideband noise from the transmitter (this transmitter can be either the pager transmitter or a dirty local oscillator))

This article will look at the first cause, with later articles examining the second and third and providing a case study by an amateur operator who has controlled his pager interference and resumed weak signal operating.

Intermodulation occurs when two signals are present in a non-linear device. Figure 1 shows diagrammatically the basis of intermodulation, RF signals at a site and not its vicinity out to several hundred metres may intermodulate or mix due to any nonlinearity at the site. We have all heard about "nary bolt," but there are wideband masthead preamps, class C output devices and numerous other potential mixers, these inchade the preamplifier of your amateur transceiver, a slightly dirty amenta joint or a fainthy dry joint in the receive path in the receiver.

An illustrative, but real-life, case study occurred at Mt Ginnin in VK1 The amateur repeater VK1RG1 is input 146 550MHz/out-put 146 950MHz and local packet enthussasts wanted to put a 147 575MHz digipeater on the same site

When calculating intermodulations there are two principal ones that need evaluating these are:

ing, these are: third order, that is if 2 X f1 ± f2 = f3 there are problems

and fifth order, if 3 Xf1 ± 2 Xf2 = f3 there are problems

These are two station intermodulation products, three station intermodulation products are not at all uncommon. Bear in mind that the third 'station' could well be a spurious emission from your local oscilla-

For Mt Ginini the two station third order solution is 2 X 146 950 - 147.575 = 146.325

but f3 is 146.350, so allowing for FM signal deviation which, incidentally is doubled, brings the intermodulation product into the receiver input. Consequently it was not possible to use that packet fre-

quency, and the one selected was 144 800MHz I will leave you to do the sums to show it was acceptable

In calculating the intermodulation products it is necessary to try each site frequency in each position in the equation as f1, f2 and On a busy site this is a mammoth task. but solvable by computer provided you know all the frequencies in use in the vicinity At Mt Gray, near Goulburn, the number of transmitters on the site produced a 36page print-out with 70 lines per page of the potential intermodulation products applicable to the siting of the 2m repeater at that location. Of all the repeater frequencies available only one would work on the site. In view of our earlier comments regarding

the cleanliness of our own local oscillator Okay, you say, that is nothing new; we have all observed birdies in our receivers. Indeed, years ago, when VHF conveners were the go, birdies were used for calibra-

this has real impact.



Figure 1

tion and checking sensitivity. So what has changed? Only the density of signals through increased utilisation of the spectrum.

After all, we amateurs frequently use the statement 'amateur frequencies, use them or lose them', and now other people are using them more intensely too.

Incidentally, a consequence of site intermodulations is we amateurs need to check carefully before setting up any new service. The approach of inverting the repeater inputs and outputs is not a universal solution, by any means, indeed, it may just be the wrong thing to do in some cases

Bottom line. With increasing co-siting. the planning of amateur services has become a lot more complicated. This is a challenge Divisional Technical Advisory Committees or TACs have to meet. The Federal Technical Advisory Committee or FTAC can help, but FTAC is essentially one man, its chairman John Martin, working with support from specialists and TACs, so much of the groundwork must be done in the states. Can DoTC help? Yes, to some extent. But again the government's 'user pays' policy impinges. Therefore, amateurs need to pay more attention to the design and engineering of their repeaters. The intermodulation theory shown above also applies in our own transceivers. Consider a receiver fed with a strong pager signal. The first amplifier could be forced to operate in a non-linear manner, that is the strong pager signal at the aerial becomes the local oscillator (LO) for a wanted weak signa). Then, if that LO has spurious components - and few signals are spectrally pure - noise or unwanted products will be passed to the IF stages and detected Balanced mixers can

help reduce this problem to some extent Next article, transmitter sideband noise emissions. What are they and what can we do about them?

JENLEX FILTERS

Get Rid of Pager Interference

The range of JENLEX 50 Ohm helical filters is designed to reduce or eliminate pager interference on the 2m band. They are compact weatherproof filters suitable for indoor or outdoor use.

All prices are ex-works, including sales tax, and subject to change without notice. Packaging and post are \$10 on all units

. HNF1: is a 2-stage filter rated at 100 watts, with a notch depth of better than -40dB at 148.6MHz and an insertion loss of 1.7dB at 147.600MHz Price: \$175

at 50 watts, with a with notch depth of better than -40d at 148.6MHz. Maximum width depth of notch is - 80dB with a narrow band width. Price: \$175

width.

. HNF2: as a 4-stage filter rated . HNF3: is a 3-stage filter rated at 50 watts. Maximum depth of notch is -55dB with narrow band Price: \$165 . HNF4. is a 2-stage filter rated at 10 watts with an attenuation better than 30dB at 148 600 Mhz and an insertion loss better than -2dB at 147.600MHz BNC connectors are standard for this model, small enough to be used on a hand held. Price: \$150

Notch frequency and depth can be adjusted at the factory at the time or order to suit the user's local needs. Send for an illustrated leaflet and detailed performance curves.

122 Wanda Street, Mulgrave, Victoria 3170 Phone: (03) 548 2594. Fax: (03) 547 8545

Telecom Pagers Cause Much Anguish for 2m Operators

Rodnoy Champness VK3UC 17 Holms Cri Becalls 397

In town and suburban areas there would be few amateur operators on the 2mband, mostly towards the 147-148MHz end of the band, who have not experienced some trouble from the operation of Telecom and other pager transmitters in the 148-150MHz band. The ones up towards the top end near 150MHz do not cause as much in the way of problems as do the Telecom pagers just above 148MHz.


OW WE ALL KNOW THE fault is with the pager transmitters, don't we? Do you remember the TV viewers who knocked on your door and accused you of causing interference to their TV sets? Many blamed your transmissions. even though you knew your transmissions were clean. And so with the pagers: their transmission is clean too, except when a fault develops, which is relatively rare. What did you tell the TV viewer to do about his TV signals? You probably told them they needed to overcome the inadequacies of their TV system. In other words, fit a filter etc. And so it is in this case. Your amateur 2m receiver is unable to discriminate between the powerful pager transmitter nearby and the weaker signal you are trying to receive

Erroneously, many amateurs believe their black box transceiver receiver is the best receiver made since sliced bread. Sorry to tell you, but amateur-grade equipment is not in the same league as professional equipment. It may be quite sensitive and hear quie weak signals when no other signals of any gerat strength are around, but in this real world there are many relatively high-power transmitters in the near neighbour-hood. Most amateur receivers suffer from intermodulation, de-sensistission, spurious responses, image response and a variety of other inadequiexes. This does not mean your beaut piece of equipment is a heap than a although some come close! - but that and the price we are prepared to pay. We have to be established with the amateur-grade equipment and look at ways of overcoming its inadequacies.

The pagers are not causing interference, they are not being discriminated against by our equipment. The pagers do put out quite a high ERP, usually 500 watts effective itotopic radiated power, usually up at about 30 metres or so with very good take-off They usually use a 100W transmitter feeding four half-wave folded dipoles. Is this power as much as many manters use? I have run up to 1500W ERP, and some use much more. The high ERP is achieved by running as much power as allowed, plus the multiplying factor of the antenna gain.

In general, the problem caused by highpower pagers can be overcome by using notch filters to reduce the level of the pager signals at the receiver input whilst attenuating the wanted signal only slightly.

I had the opportunity of testing a filter that does reduce the level of page transmitter signals to the front end of Zm receivant ber signals to the front end of Zm receivant weeks its four-pole helical resonator filter. There are many pagers in the frequency range 189-150MHz, so there is no point in having individual notch filters for each frequency, it is not practical, too lossy and too



expensive. I re-tuned the filter with a spectum analyser and tracking generator and, with careful alignment, obtained 35dB attenuation at 148MHz, rasing to 50dB at 1484MHz, with a pastband insertion loss of 2dB at 147MHz and 1dB at 146MHz. These are very credible figures. Lext Paterson tells me he can achieve 62dB or better depth with his four-tage filter.

live about 1,84m from a Telecompager that transmiss on 148,025 and 148,0375Mfrz, and the signal is so strong that I notice de-sensing on all the PM repeaters, I do not have other troubles that some may have. Pitting the filters in the antenna line to the transceiver produced extremely pleasing results. No de-sensing of my receiver and manimal attenuation of the wanted signals. I have tried there receivers, and the results with the filter have been most pleasing. None of the receivers that we used has shown great distress even without the filter, but does not become desensed at all with the filter.

Yes, you could make one of these devices yourself, but the experience of the manufacturer and his use of a spectrum analyser to align the device make it unasttractive to do so. The filter is made by [ENLEX (are Paterson) of 122 Wands St, Mulgrave, Victoria 3170. The filter sells for \$175 and, at that price, is good whee. Lex also offers a service where he will align the filter for the purchaser f particular needs at the time of purchase. Lex has supplied a range of filters that can be obtained, on loan, from the Victorian Division to assist anateus with interference problems.

Coastwatchers Reunion

Fiftleth anniversary national reunion of 'M' special units, Allied Intelligence Bursau will be held at Gosford on 14, 15, 16 August. Intending participants should contact Mrs Jo Foster, 38 Fitzroy St, Umina 2257. Phone (043) 41 9205 for event booking Hshalls.

2m Cavity Preamplifier

I Thomton Crt Woornelliary 3138

Over the years I have seen a few pre-amplifier designs published in AR from a variety of sources. However, many amateurs have the wrong idea of what a pre-amplifier is for.

THE FIRST STAGE IN A receiver normally sest the noise level which is added to the ambient noise level that is amplified along with the wanted signal. The ideal would be to build an amplifier that contributes no noise at all and only amplifiers the incoming signals - linary. Unfortunately, this sort of performance is well beyond the average amateur are not only and the service over about 4MHz and can have relatively poor front-end selectivity, resulting in non-individual services.

linearity and cross-modulation between nearby high power signals such as TV or paging transmitters.

After many experiments with both homebrew and commercial pre-amplifiers using FETs and GaAsFETs, I found that most amplified everything and were generally more of a hindrance than a help Reading CQ and VEF Communication magazines about cavities versus noise, both wide and narrow band, I started to experiment

63.5mm (21/2") in diameter


105mm (4½,") in height
0.8mm (½,;") brass wall
Tap 'A' 12mm ('1½;") to Base
Tap 'B' 36.5mm (1½;") to base

4.8mm (γ_{es}) brass tube 1.6mm (γ_{es}) brass rod

Ficial in top for adjustment 1/8" Golden of FET 1/8" Solidar of FE

Drill 3.2mm (1/8") hole at 'C' to

guare 1



.01µF monolith

C8 1-7pF trimmer C9 33µF tantaium

82 ohm 1/4watt 68 ohms 1/4 watt ms 1/4 watt 100k ohms 1/4 wat 39 ohms 1/2 walt

Q1 any suitable dual gate MOSFET 'F8' means F8-ferrita bead)

L1 4-3/4 turns 16 B&S silver coated wire tapped 3/4 of first turn from cold end. ID 11mm (7/16") length 19mm (3/4") inch.

Figure 2 Cavity with pre-amplifier circuit




Figure 3 This VOX circuit applies if 12 volts is placed on the RF line og Icom pre switches inbuilt in the transcelvers.

with various cavities and helical resonators. and they worked! However, they were much too big, being 21inches/53cm long. After numerous experiments with various configurations. I found a smaller cavity could do the same job, being just some 4-1/8 inches long and 2-1/2 inches in diameter (105mm H/63 5mm D) The inductor in the centre was also critical in relation to the frequency and Q. By altering the inductor it was possible to change the bandwidth and/ or alter the side lobe performance. The insertion loss was less than 1dB and the rejection of off frequency interfering signals was about 40dB (goodbye to pagers at least to a more tolerable level) By placing a preamp immediately after the cavity. the insertion loss was more than compensated for. This unit, combined with a suitable VOX circuit, has proved to be a very valuable experiment which sits proudly amongst my other homebrew equipment

Construction

The cavity is a cylindrical brass tube, 2.5 inches (63.5mm) in diameter and 4 125 inches (105mm) high The cylinder is soldered to double sided PCB material, along with the 3/16mch tube and the 1/16mch brass rod. These are soldered 1/8inch apart to the PCB, in the centre of the cylinder. A removable top is made, with an adjustment hold for the trimmer. For the dedicated,

Figure 4
VOX circuit for 12v external. When
RF is applied, the relay des. S, is for power and S, 'hang time' (ie delay) for



witching of relay contacts in figure 4. Double pole relay can be used.

silver plating of the internal surfaces is great, for the hobbyist, leave it. Figure 1 shows the general construction of the cav-

Designing the Cavity

After many ideas and experiments of forming the actual cavity I found the most practical way was to select a piece of brass sheet and ways pie around an adumnium drink can, holding into place by wrapping fixe wire around the newly formed brass, thus holding its present position whilst solering the overlap finage. A good idea is not to use brass, which is too thick. I suggest to the total cavity of the control of the contro

When the cylinder has cooled, remove the can and the fuse wire, place the brass cylinder on a piece of double-sided PCB (138 x 70mm) at one end, and draw a pencil mark around the cylinder on the PCB. Remove the cylinder, exposing the circle and define its centre with a small indentation. Place the cylinder back within the marked circumference on the PCB, then solder the outer edge or perimeter that contacts the PCB all the way around. Measure and mark a point some 26mm from the PCB up the wall of the cylinder, on the LHS, that is to say, at the end close to the edge of the PCB. For argument's sake we will call this point 'A' (shown at dimension 'A' figure 1).

Now, on the opposite side of the cylinder, mark the wall at some 46mm from the PCB. That is, point 'B' (shown at dimension 'b' figure 1). At point A mount a BNC lowcost female panel mount connection, and at point B drill a hole 4mm in diameter.



The apparatus fully assembled.

Obtain a piece of brass tube 3/16* (4.8mm) x 3 7/8*(98mm) in length, and solder it to the centre of the cylinder on the PCB (where you indented the PCB). Select a piece of 1/ 16" brass rod the same length of 3 7/8" (98mm) and place it 1/8° (3mm) beside the centre rod, opposite the BNC connector. Solder it home to the PCB. Now bridge the BNC to the thinner tube. Solder a piece of 1mm silver-plated wire to the centre tube opposite hole 'B', allowing the wire to extend through 'B' for 4mm. Make sure it doesn't touch the sides of the cylinder. This works as a feed-through. Lastly, place a 5-55 picofarad variable capacitor from the outer wall to the top of both tubes.

ter wall to the top of both tubes.

To finish off the cavity, a top cover can be

made. Remember to have a hole in it to adjust the cap. Do not allow the cover to short out the capacitor, or tubes to the wall of the cavity. Point 'B' goes to the preamplifier gate 1 of the FET employed.

Figure 2 shows the circuit of the preamplifier.

It is a good idea to mount all the components in the preamp in the air, each supporting the other. This results in less loss and helps impedance-wise,

The additional circuits are typical VOX circuits that can be used to switch the cavity and preamp out of circuit on transmit. If you have any problems and require help, please call me QTHR.

Agent for Ucando
ELECTRONICS
TRAINING VIDEOS
Agent required to sell UCANDO

Efectronics and Training Videos as sold by Everyday Electronics magazine Electronics Assembly Co PO Box 21191 CHRISTCHURCH (4/54 Rolleston Ave) NEW ZEALAND

Phone/Fax 3-795-570



internal view of the cavity and pre-amp

14.116 The Australian Travellers' Net

A Diode- and Formula-Free aspect of Amateur Radio

> Compiled from many peoples' memories by VK2DZL Fred Greening, 51 Marry Street St Marry 2760

Itwas in 1969 when VK6KC Keith Williams was employed at the Japanese Cultured Pearl Farm at Kuri Bay, that a lonely seed was sown in this most unlikely spot. Fortunately it germinated and took root and has grown to what we now call The Australian Travellers' Net*.

THIS TIME KEITH WAS THE resident radio officer, weather observer, first-aid officer, company clerk, film projectionist and did any other job that nobody else could handle. I think that this type of employment is nowadays referred to as 'multi-skilling' but no one told Keith about this back in 1969.

Then as now, Kuri Bay was a very isolated place, being 350 km north-east of length gas to the more and 360km westor Wyndham, and the was well off the (then) little-used 'tourist is track' As the only European on the site, Keith was isolated both culturally and geographically from his peers. He then, as one many other amateurs have done in similar and circumstances, turned to his radio for interest and information and also to maintain some social contact with the outside world. His sear at this time was a Geloso AMTX.

His gear at this time was a Geloso AMTX and a National HRO RX but this RX was later superseded by a matching Geloso RX.

Initially DX was the main interest, for conditions were particularly favourable at this time but later, as they deteriorated, he found that he was working more and more amateurs marine mobile and a few land mobile. He made contacts with the few land mobiles who were about, came to know them, and they started to meet on a regular basis.

Keith selected the frequency of 14.106s a meeting place for no other reason than at this time of day it was generally pretty quiet. The time of 900 OAFT, as it was then, was selected as travellers, depending on what and of the continent they were on, would most likely then be stopped for either morning tear of runds. It also swited thin, for arthlist time of day he was usually preny free to play amateur radio.

This arrangement brought together a small band of people of like interest, giving Keith the social contact he sought as well as adding another interest to those amateurs who were on the move, by working this amateur in such an unusual place.

These new contacts were soon picked up and monitored by more and more 'stuck at home 'pairs of ears which, in effect, were experiencing something of the nature of outback Australia and the magic of faraway places ... and so came into being the nudeus of today's net.

With the passage of time base stations became involved with the sessions, and relayed back and forth between Keith and any weakly heard stations, and from this it was not 100 long before Ketth had these stations assisting as control statuous to call and pick up stations that Ketth could not read himself. The net could now legumately call itself a net, so Doug VK5VK agwe it the name "The VK6KC Travellers Net". Later VK6ART Arthur became very much in developing a base format for running the sessions. These early procedures became the blueprint from which the curperationary and the procedures were developed.

In the fullness of time Keith left his employers and retired to Perth and it was only then he realised just how busy one can become in retirement. It was not long after this that he asked Arthur VK6ART if he would assume control of the net, as Arthur had much superior gear and an antenna system ideally suited for handling widely separated stations. Arthur accepted the post and handled it with distinction for the best part of 10 years. We all owe Keith a debt of gratitude for his initiative in starting the net, and also to all those other stations who helped in the early days and whose names are now lost in the mists of time. A big 'thank you' to all concerned.

When Arthur assumed control of the net he quickly found solid support from Reg VK6YE and later Roy VK6BO. The somewhat informal procedures soon had to be streamlined to meet the rapidly increasing demands being placed on the net by the growing band of amateurs taking part in the sessions, some at home and many more on the road. The net was now a respected voluntary service to all who travelled by land and by sea. It now provided an almost professional service in respect to safety and communications to travellers and has since been a major player in many rescue operations by alerting the proper authorities to the dangers and emergencies facing travellers far from conventional means of communication

On the lighter side, the net also acts as a contact point for fineds and relatives who are not licensed amateurs to leave messages for passing to the travellers when they check in each day. All travelling amateurs are urged to leave the phone numbers of control stations with family and friends to ensure contact is not lost, particularly when off-roading in remote areas. The types of messages handled range from the invariable 'clean' and cleaser' ones on the light and the state of the light of the light of the light of the light of the state of the light o

will you tell VK8ABC that I will catch him on 7070 at the usual time trought. Apart from this kind of traffic from home there are always base stations at home walking to take travellers off frequency just to ragchew. It is, by and large, a very versatile platform for all sorts of contacts.

As the volume of traffic increased, so did the number of base stations from almost all over Australia, to ensure no traveller's call would go unbrard or unanswered. Some of these stations helped a little: some helped a lot: and some are still part of the net. A brief roll call of those stations would include VK6KC VK6ART VK6BO VK6YE VK6HH. VK6TB, VK6RJ, VK6ZZ, VK5ARM, VK5RI, VKSAAX VKSYK VKSPN VKSIJX VKSKE. VK2HI, VK2FDM, VK2ALH, VK2IV, VK4YG, VK4AF, VK2CID, VK3BMS, VK4ACU, but this list would be far from complete, as many other people also did their share. I know that all those who presently run the net would wish me to say on their behalf "thank you all who have helped, and we hope that you still listen sometimes and enjoy the net and think to yourself "I helped to get that net started" and then feel a little sense of pride in having helped do something worthwhile, VK3UX, VK6ZZ and VK2HI are all silent keys now I am told, but their help is still remembered.

With the passing of time, Arthur's involvement in the net became more and more time consuming and, in some respects, almost a full-time job, especially when he was involved in emergency situations such as marine disasters. At these times Arthur could be found in his shack day and night doing what needed doing until relieved by the proper authorities or the situation was satisfactorily recobed. I understand that after the "White Waves" incident, Arthur's XVI. Eilen did suggest that perhaps they could meet socially once a week at the supermarket to discuss the world outside amateur radio and perhaps buy affilicient of the necessities of life over them through until the following week. I believe that shortly after this discussion, Arthur decided to take Thursdays off and leave Ree to not the set in his alternal.

By now record keeping too had become state-of-the-art, as both Arthur and Roy had computers and had jointly developed a format for their use. Now after a station called in it was positively known who it was, where it was, how it was and where it was going to be that night ... all handy knowledge if they were needed or went missing. Another firmly established procedure is the call 10 minutes before the advertised starting time 'any emergency or priority traffic'. This announcement is initiated by net control in Perth and is repeated by the VK5 relay station. If there is no VK5 relay station available then another relay station, either in the centre or in the east, is invited to broadcast this announcement. This gives anyone with problems a clear frequency on which to contact the net. There are those who know just how important this nause in proceedings can be

Ultimately Arthur felt that he had contributed as much as he could to the net and, in view of the close working relationship he had with Rov VK6B0, asked him if he would assume the control position for the net.

Roy agreed to accept this position and he, in turn, asked Peter VK6/HH to fill the position he had just vacated so he too could have one day a week off to go to the supermarket. These XYIs wield formidable nower, don't they?

In 1988 the name of the net was extended to identify it better by changing to 'The Australian Travellers' Net' and the frequency moved up the hand to 14 116 to escape the overwhelming clamour of the recedyl arrived packet radio stations that were whiping out those trying to contact the net on the long used and well recognised frequency, Not only was this a quieter frequency, but was more in line with the new band plan. Now, not only is there a new name, but also a new frequency.

Now the net is recognised internationally as a valuable and reliable net comparing favourably with SEANET and markine
mest of similar standing. As previously mentioned, the net is widely used by assistant
markine mobile, but is also used by vasting
amateurs who have obtained a reciprocal
licence for used uting their stay in Australia.
It is also known as a contact point for
anyone in distress, and can be used freely
by anyone for the duration of their emergency, licensed amateur or not. In essence,
this net can and does do a lot for all kinds of
peopole.

From 1987 until now, at the peak of the season about 70 callers per day, made up of mobiles and contact stations have checked into the net. One can only surmise that these numbers will increase when the present economic crisis is past and people hit the road and take longer talk breaks at lunch time. Some incidents come to mind where the net has been able to render valuable assistance in times of distress. In 1987, a boy in a party visiting the Purnie Bore, which is on the edge of the Simpson Desert, broke through the hard crust of the mud surrounding the bore and plunged feet first into the boiling mud below, scalding his legs terribly.

Getting the picture, Arthur constacted the Royal Flying Dorot Service and acquainted it of the situation, and was advised of the inst-aid to be given. He relayed this information to the accident site, and kept in touch with the truck carrying the mussing siter and medical supplies from Ordinadata through the RFDS base at Alice Springs, whose operation was alleensed matteur, so keeping both parties up to date on the state of affairs.

On another occasion, the net picked up



Keith Williams VK6KC who started the Net.

an outpost station with a weak signal trying to contact the RFDS at Alice Springs, but which, because othe weakness of its signal, could not trigger the auto emergency alarm. Contact was made with the base at Alice Springs by phone, and they came up on air and took over the problem

In 1984, an amateur came upon a man unconscious beside the road north of Sandfire Flats. He contacted the net which alerted the SES, which then handled the problem.

The writer is deeply indebted to VK4ANN, who contacted the net when Urgent or Priority Traffic was called for on behalf of our daughter in Brisbane. Our grandson had been rushed to hospital and found to have what proved to be an inoperable brain tumour and was given only hours to live. Pull praise must be given to the police at Yunta in SA, who sorted things out for us and organised us on to a plane for Brisbane. The boy died just as we landed, but we were at least with our daughter when she needed us most. Our thanks and full praise to the amateur fraternity which made this possible.

A note just to hand advises me of an incident of recent times when a family travelling the Pine Creek to Jabiru road were involved in a serious motor accident where four people required ambulance transport to hospital. Fortunately an amateur happened upon the scene and put out a very early call to the net which was picked up by Roy VK6BO who was readying things for the day's operation. After obtaining all the relevant information he contacted the WA Police Communications Network and it arranged for the people to be transported to Katherine Hospital in a matter of hours. One of the injured had later to be flown to Darwin for treatment that was not available in Katherine.

Not long after this the net was approached to see if it could locate an amateur holding a limited call, and so not on the net. They announced the details on the next session and an amateur located the car in the blow holes area north of Camarvon. This resulted in a very urgent message regarding family welfare being passed in a matter of only a few hours.

All this is but a sample of the work done by the net. Some of the messages bring sadness to the recipient, others joy and others laughter for all concerned. How many of us relate to the message to Dad from his son that says he is forwarding the new water pump for the Gemini to Banka Banka Station and it should be there by a week from tomorrow.

From what I hear the Australian Travellers' Net has now become big brother to a new net designed to watch yachties across the Indian Ocean ... logically called "The Indian Ocean Maritime Net". It too grew from a casual contact which revealed a 'hole' in the maritime network's coverage of this part of the world.

Some time back the net had a M/M (OK4KOR) with three on board crossing the Indian Ocean to South Africa and using but five watts of power on the transmitter Contact was maintained with the net until propagation made contact impossible, and when the yacht reached Madagascar, Beda OK4KOB changed to the Durban net. This experience showed that nobody was providing a service for boats crossing the Indian Ocean. This contact led to others, and now we have an 'Indian Ocean Net' running at 11.15 Zulu each night, with a calling frequency of 14.316 and then moving to an operating frequency usually somewhere between 14.322 and 14.337, depending on ORM, Presently the working frequency continues to be announced for 10 minutes after

it is determined, so latecomers will know where to find it

For those interested in the 'mechanics' of the net. and how it is run. I am. indebted to Peter VK6HH for the following information. The concept of one man controlling the net, with a second man as a relief one day a week, has gradually changed to what could almost be called a control team based in Perth Roy

VK6BO is acknowledged



ur Oliver VK6ART who ran the let for many years. (Photo courtesy lell Penfold VKSNE).

as being the net controller, with Peter VK6HH being his 2IC, who takes over alone one day a week, or more often as required when Roy has to attend to other commitments. Generally these two men work as a team and they would be very unusual circumstances indeed, if ever the net was left without a controller in Perth To further increase the efficiency of the control, a 2m link is maintained throughout the sessions on 144 625. This is a handy way to report 'doubling' or to confirm information reonived from faintly heard mobile stations. and this is doubly handy when one control station is experiencing local QRM caused by rain static or the like.

- 1. Both stations use the FT107M as their main transceivers
- 2. Both have standby gear. Roy has a TS430S and Peter an IC735
- 3. Roy has an NEC computer, and Peteran Amiga. Both computers contain the same information.
- 4. Roy uses a tower-mounted Yagı, and Peter a two-element Quad atop a mast, and a 107' dipole with tuned feeders through a Z-match as a back-up antenna 5. Both shacks have Telecom phones
- 6. Roy has a back-up generator for use should mains power fail during the session

Control Station Telephone Numbers These phone numbers are available to all to use to enquire about the net itself or to leave and receive messages for or from travellers. When ringing these numbers, please remember to take into account the time differences across Australia and give the callsign the message is for



Roy Chamberlain VK6BO who took over from Arth VK6ART.

VK6BO (09) 331 1825 Peter VK6HH Rob VKSRI

(08) 93 4001 Alex VK3RWS (03) 579 0006

There has been a spin-off for amateur radio arising from the use of this net. Some XYLs who previously had little or no interest in amateur radio have become avid sked-time watchers, later progressing to obtaining an amateur licence for themselves. as have some of the passengers who have been afield in vehicles operated by touring amateurs. Thus amateur radio has become a comfortable way of keeping in touch with those either at home or touring about

I think this just about covers the story of the Net. It is a very brief and generalised coverage, but to tell it properly and mention all the people one would really have to write a book. Already I think I can hear numblings from those electronically oriented readers who are objecting to this bloke taking up valuable space in the technical journal of the society with a rag-chew article about travel tales, so let me say now there are many facets to our hobby as there are many colours in a rainbow, and don't we all get a thrill at seeing that wonderful bow across the sky, especially when our own favourite colour shows through clear and bright?





SOME THINGS HAVE NO COMPARISON

radio

The magazine for the serious radio operator

AT YOUR NEWSAGENT EVERY MONTH

Willis Island VK9

Stephen Pall VK2P1 PO Box S

It was in late 1989. As I was tuning across the band, I hearda "CQ DX" call. "This is VK9TR on Willis Island," said the Australian voice. Suddenly the band was alive and, within minutes, the transmitting frequency of the Willis station became a "dogpile". Willis Island was on the air and continued to be so until the middle of 1990.

INCE TREVOR'S RETURN TO Adeladid, I have exchanged several lettern with him. Tevor, who thoseed up, gues his callsign as VKSPG, supplied me with facintaring information about life and activity, past and present on one of the emotest islands on the Australian coasiline. But before I proceed to quote from Trevor's letters, let's took at the history of this Island. Willis Island is part of an Island group lying inthe Coral Sea, and consists of North Cay, Mid Islet and Willis isself They are 267 naultical miles north-east of Townsville at latmide 16-17 South, and longuide 149-58 east.

The islets were discovered in 1853 by Captain Pearson of the ship Cashmere-he named them after the owner of his vessel. The island remained unnoticed and uninhabited, except for a survey done by Captain H M Denham of HMS Herald in 1860, until the end of the First World War.

The north-eastern part of Australia is visited quite often by cyclones. In September 1921, the political pressure to establish a cyclone warning station on an island in the Coral Sea prompted the then Minister of Territories, the Hon A Poyton, to ask the Commonwealth Director of Navigation. Captain John King Davis, to submit a report about the feasibility of establishing such a station, having regard to the "dangers and safety of personnel remaining on the island in the above assets."

in the cyclone season". Captain John K Davis, who was the commander of the Aurora in 1911-1914 during the Australasian Antarctic Expedition and after whom the Australian Antarctic base was named, was aware of the great value to shipping, if such a storm warning station was established. He himself led the exploring and working party to the island in October 1921 on the ship SS Innisfail, and after arriving back in April 1922 he submitted a 14-page report which the Australian Senate ordered to be printed on 3 August, a total of 902 copies at a cost of £26 which, in those days, was quite a sum of money The report reveals that the island is approximately 583 yards long (533 metres) and about 212 vards wide (194 metres), However, the usable grassed portion is only about 468 yards (427 metres) by 150 yards (137 metres). On this small area of usable land. Captain Davis. 13 other helping hands and the crew of the ship erected in the short time of three weeks: living quarters for three men, a *wireless telegraphy house", two wooden radio masts of approximately 80 feet high (26 metres), installed the radio and meteorological equipment and provisioned food and other stores to last for six months, and 1600 gal lons of drinking water in tanks and casks Captain Davis writes in his report.

"On 1 November, communication with Australia was efficied with one mast, and the following message was despatched to the Minister for Home and Territories. Work of erection of Willia Island Station proceeding assisfactority; job has proved a heavier one than anticipated. All hands are in good bealth, and its hoped, if weather continues fine, to despatch the Invisitalifrom here on Monday evening. 7 November Work then remaining can be completed by resident party - Davis."

The first meteorological report was sent from the station on B November 1921, and 70 years later in 1991 Willis Island still provides important meteorological information to the Australian Bureau of Meteorology. However, the means of communication have greatly changed since.

A letter written by Mr Eric Riethmuller in 1981 at the age of 78, and who, according to the information given to me, passed away where or four years ago, gives a very interesting insight into early life on the island. Rethmuller was on Willis Island at various times, starting in 1927 as an observer-cumradio officer. He writes to his modern-day colleague at Willis in September 1981 as follows

-The communications from 1921 when the station was established by Cantain Davis is in great contrast to what you have today (1981). Willis Island began with the callsign CGI and worked Cooktown (VIC), CGI later changed the callsign to VIO, had one 1 5kW rotary spark transmitter with two frequencies - 500kHz and about 300kHz (in old language 600 and 800 metres). The transmitter was driven by a 5HP upright single cylinder petrol engine via a 110V DC generator, and these two made such a racket that in the receive mode, the petrol engine had to be switched off (... to hear the incoming signals). The operator had to dash an and out of the engine room, swinging the crank handle with rapid enthusiasm, transmit, switch off and listen and hope that his opposite station in Cooktown did not reply too quickly - writes Riethmuller,

During the cyclone season communication was very difficult from Willis in the early years, due to the ever-present static noise. The weather reports were sent in five-letter code groups, and each group had to be receated, sometimes nine times between the two stations. Willis was manned during the 1920's and 1930's according to Rjethmuller's letter, with personnel from Amalgamated Wireless (Australasia) Ltd (AWA) marine radio department. There were two people on the island - one radio officer/observer and one handyman/cook, from the months of May to November Life was tough in those times. Riethmuller contimues

Before leaving Sydney I spent several days at the weather observatory, where a man named Nelson initiated me into the mysteries of how to read the mercury barometer and look after the anemometer, barograph and thermograph.

I sort of remember the barometer, temperature etc had to be read each day and recorded in certain books. For weeks on end the weather changed little. SE trades (wind) blew consistently, the sooty terns wailed all night, and very little rain. On arrival there about May 1928, I found the station in a run-down condition. Most things had been given over to the cockroaches, corrosion and humidity with sad results. One item completely ruined was the large medical store. For that season, as later, practically all food was tinned or bottled. Things such as flour, sugar, biscuits, dried fruit were all done up in sealed cans to defeat the weevils and ants plus humidity. We had a dozen or so hens that kept us in eggs. Hens were fed on wheat mostly, and kept in a small yard to the north of the wireless hut. Both buildings were referred to as "huts" though built of reinforced concrete. For cooking, we had a three-burner kero stove and a primus. Stove was needed for the breadmaking. We mostly were proud of the results with the bread. Yeast was the old grandma type, hops potato cork tied down in a bottle. When "H" (the offsider) missed his beer, he used to take a mug of the yeast and pour it down his throat. At the end of the first session we were short of flour Ration was half a slice of bread per meal, caused partly by the month-late arrival of the Morinda, which had run aground up New Guinea somewhere the previous trio.

Later I was there with Snape, also from the Marine (department of AWA) and sometimes we followed one another. He also was an eager beaver, and we two put the station in order Took a couple of years to do so This even impressed the high command to such an extent that old Fisk (then chairman of AWA) ordered that we be given a bonus of 30 pounds for "good work at Willis Island" Weather men came with the



The pioneers of Willis Island, around 1930s, Note string on the left to operate the camera.



November relief, plus a second radio Wallah (radio officer): I staved over the summer season. Before returning for my second trip towards the end of 1928. I spent several days in the AWA castle in York Street making a short-wave transmitter under the direction of Ioe Reed, one of the AWA engineers. When back on the island, this little toy changed our whole communication. We transmitted on 32 metres, received VIT on 600 or 700. His glorious signal came in all over the static and dynamotor noises. We still had to run the engine and the 11/, kW set to obtain the 1000 or so volts for the SW set

The AWA personnel on Willis later were replaced with the personnel from the Bureau of Meteorology. After the war, the Overseas Telecommunication Commission assumed responsibility for radio communications, but in 1966 the Australian Bureau of Meteorology took over sole control, which is still has to this day

Today the island boasts guite a range of modern communication equipment, such as 500 and 1000W CODAN HF sets (previously RACAL) a digital data transmitting system, a back-up RTTY system, telephone etc. The power is supplied by two aircooled DEUTZ diesels with 40kVA alternator sets and a water-cooled CUMMINS with 50kVA alternator set attached. At present. there is also a 3cm manual wind finding radar, type WF2, able to track targets of 500mm to a distance of 80 to 100km. The two wooden masts of yesteryear were replaced with two marine aluminium masts 24m high with stanless steel rigging, and dipole antennas with baluns. There is a sloping multiband antenna in the range of the 5 to 30MHz, and another half Delta antenna for the 2-14MHz range.

The scientific study and information gathering carried out on Australian outposts -Willis Island, Macquarie Island, the bases in



Trever VK9TR operating on Willis Island. Note the "local brewery" advertisement.

Antarctica, just to name a few - attracted radio amateurs from the early days. Amateur radio as a hobby neatly fitted with their scientific background and profession. Amateur radio in the early days was the only source of communication with the loved ones on the mainland, and even today. where there is a telephone on practically every base, amateur radio still plays an important role, not to mention the DX aspect of the hobby. Ken McLachlan VK3AH. in an earlier article about Willis Island in the September 1982 issue of Amateur Radio. describes these amateur activities in more detail. I list here their callsign and the year of operation, supplemented by my own observations, just for the record. The list is not complete, and further information about amateur radio operations on Willis is welcome

John VK4JO was there in 1963. VK4WV was there in mid-1964. John VK4HG in November 1967, Gavin VK4EV in 1968 and Kevin VK9ZC in 1973. Dave VK9ZZD wentto Willis shortly after his previous tour of duty, lasting 12 months on Macquarie Island.

Dave was followed by Mile VRSZG and Trony VRSZH in 1982, And VRSZG in Janusus 1982 and John VRSZ in Janusus 1983 and John VRSZ in Janusus 1984. Graham wentchere as VRSZW m May 1984, and Trevor VRSTR was there from November 1989 to June 1990. Harry VRZBJR speen alterium there when visiting the Island in a sailing boat, and used the call VRSZR. There is no amateur activity at present on Willia Amateuss who were active from Willia were always sought after for contacts in the DX world. Willis Island is just one of inter locations with a VR prefix, which is considered to be a separate 'DX country' according to the rules of the DX Country' according to the rules of the DX Country Cub.

One of the most successful recent DX operations was the one by Trevor VK9TR. His cheery voice, politeness and patience towards sometimes not-so-nolite DXers and his willingness to participate in several net operations, had left a very pleasant memory and gratitude in the heart of the serious DXers. Trevor, who is a radio technical officer with the Australian Bureau of Meteorology, spent eight months on Willis. He received his first taste of amateur radio at Macquarie Island in 1980-81 watching VKODB operating DX. Returning to the mainland, he obtained his full call in 1982. as VK5BTR. After the death of his father in 1987, he took over his late father's callsign VK5FG. Since returning home from Willis. Trevor had very little time for amateur radio. His technical skill is very much in demand by his employer, and he spends quite a lot of time organising the installation of automatic weather stations spread across South Australia. Trevor's letters to me describe the life on Willis as totally different from those times before him in the mid-1920s and 1930s.

Let's now sit back and enjoy the extracts from his letters. He describes his life on Willis as "working and DXing in paradies".

It is probably true to say (writes Trevor) that some of us have some grand ideas as to what paradise should look like Some no doubt would be disappointed, but I certainly was not. That place of paradise was Willis Island, that small coral island in the Coral Sea. I guess, not knowing what to expect, off I went to Willis, armed with a plastic container of "real things" (valves) and a trusty FT200, contending that I may at least to be able to make a contact or two. Well, in the end, I was a bit out by two things: I ended up with a Kenwood TS130S and 7641 contacts. The staff at Willis for the eight-months stay were the grand total of four, three weather observers and myself, with the male to female ratio of 3:1.

With this small population, the weather observers being responsible for the daily rotatine of weather observations, including upper atmosphere balloon flights and synopsic observation. There were times when working in the power house in the middle of the wet eason in my capacity as station technical officer, I thought I was neare to bell than paradise But the ever-present thought of sitting under the palm trees in the genite breeze, apipping the local brew of "Booby Bird Bitter" always won out, and added to that paradise touch.

In another letter, Trevor mentioned that brewing beer is another interest of his, but that hobby has been made considerably easier by the use of brewing kits. "It does take the funaway from it, a bit," he says, Just like amateur nadio: home-brew gear has been replaced by factory built black boxes.

Beer was also mentioned in Riethmuller's letter written in 1981:

Thinking back to the year of 1927 (he writes) my offsider "H", a man aged 45, and I, travelled to Willis on a Burns Philp island steamer named Morinda. The trip took one week, and "H" looked "deeper" into the beer bottles than was advisable.

Arriving at Willis, "H" was incapable of descending the gangway to the surf boat, so he was put over the side in the cargo sling,



The four "residents" of Willis Island. Left VKOTR.

together with the beer supplies acquired by lum on board ship. Most of the bottles broke before reaching the shore. There was, full of inexperience, a big heap of stores scattered on the beach, amongst which sat the inebriated "H" incidentally, three weeks later "H" still appeared "sick-ened" and hard to understand, so I looked in one of the storerooms where there had been sux bottles of port wine supplied as medical stores. Only two were left, so that night quietly buried them in the sand. And all that hanneed in 1927

Back to Trevor's letter He writes: One had to be a diesel mechanic. plumber, radio technical officer, cook, electrician and, at times, general father confessor, so you can see, it's a pretty interesting life if you do not weaken and succumb to savouring too much of the highly rated Booby Bird Lager, the local home brew. (Guess who was also the chief brewer?) By the way, the local brewery also sponsored the advertisement that can be seen on the photo of yours truly operating inside the equipment room. One of the pertinent facts that I took no time to discover was the fact that this paradise also had a five-star food supply and a view from almost every room. Some of the feathered residents were a little noisy at night and in the morning, but

There is a large bird population on Willis. Sooty terns, noddy terns, black and pink foot booby birds, frigate birds and migratory birds like kingfishers, falcons and egrets, to name a frw.

generally well behaved.

to name a few. Turtles also appear around November, to start laying eggs, which hatch in January, normally at night, and present a sight wisnessed by few people, as the baby turtles make for the sea in their thousands. People always ask how difficult it must be with honly four people on the island. Well, the answer is relatively simple Although with situation lends itself to a great study in human relations, surpnsingly, people were not what you call bumping into each other throughout the day, except if it was to help out with some command task. The only

real assembly of the entire population was normally at evening meal nime for the five-star reat. When asked about the scientific significance of Willis Island, I am always beaton, because, we are all aware, the season, because, we are all aware, the supply lead, but it is very difficult to correlate themonetary expenditure to collected data. All I can really say is that, weatherwise, willis Island data are of great value to the Queensland region, and possibly to the Australian east-coast network of weather forecasting.

Willis Island data or supplementations of the starting of the st

Willis is certainly a great place to operate amateur radio. I say this not only from my maybe biased viewpoint, but on behalf of the other three people who were not in any way connected with the hobby

Whist is was one of my passimes, and has been since 1982, it also gave great enterialment to the other residents, as we often sat around the 'rig' - Booby Bard Barer' in hand, listening to world wide conversations taking place live. The extra bonus was of course, the fact that the others could participate by listening. I think that this one of the great attributes of the holds hence creating the feeling that maybe the finesse of paradise is participation.

Imade 7641 contacts (writes Trevoragain, in a different letter) with the approximate breakdown of the QSOs as follows:

USA 45%
Europe 25%
Japan 15%
South America 5%
Canada 3%
NZ, Australia & USSR 7%

The difference between the percentages of USA and European contacts is due to the type of antenna used. It was a V-beam Type 4131, not rozatable, and as it pointed in a NE direction it was perfect for USA and Canada The other V antenna was pointed SW, but was a little low for Europe, but it did prove okay for South Africa

Due to the physical size of these antennas, they were difficult to load on 21MHz, and out of the question on 28MHz. (A small dipole was used for these contacts) A breakdown of contacts on the various bands was as follows:

10m 5% 15m 10%

20m 80%

80m only occasionally

At this point, and just getting under way so to speak, I found it a great help to start networking on the Family Hour net working from the Family Hour net with Gray VK-604 and the most helpful USA net controllers Bob KI4RU, Bud KC4DWI and others on that net, as well on the "222" net with Jim VK9NS and his colleagues, (of course, one has to mention the veteran of many nets, the ANZA net, with Percy VK4CPA and his helpers

Personally it was not from the 764 1 QSOs logged that I derived the enjoyment of my stay on Willia because, as all DXers know, that is only the start, but it is the fact that there are so many great people out there, some of them very lonely and handscapped, but all having the opportunaty to participate in communicating with each other. I really had no intention of becoming so involved, but found tenjoyed its omisch that I wouldn't hesitates to return to paradise if the opportunity presented itself again, but I would certainly go a little better prepared.

In closing, I have to admit that Willis Island is a fantastic place, whether it is working, washing, cooking, fishing, relaxing with a booby burd Bitter or plain DXing with a Kenwood 130S, 85W output into a V-beam: it is paradise!

Acknowledgement of material used.

*Several letters written by Trevor VK9TR
and photographs supplied by him

* Photocopy of a letter written by Eric Riethmuller, and copies of old photographs of the old wireless station, courtesy of the Australian Bureau of Meteorology

*Report by Captain John K Davis, Commonwealth Director of Navigation, Willis Island Meteorological Station, 3 August 1922.

* Australian Encyclopaedia, 1963 edition, Volume 4, page 377b and volume 9, page 315b.

* Article about Willis Island written by Ken McLachlan VK3AH, Amaieur Radio, September 1982.

ATN ANTENNAS 56 Camphoell St. Birchip Vio 3483 Accessories Ask for a free catalogue We manufacture a comprehensive range of HF, WHF and UHF antinness, balants, power

dividers etc to suit your application. Three of our log periodics provide continuous coverage from 13-30MHz, including WARC frequences, and replace outdated tir-benders. Now in use in 29 oversees countries and six continents.

- Rotators by Create, coax cables & nonconducting guy/haiyard materials.
- B&W all frequencies 1.8-30MHz and fed vee.
 All frequencies 3.5-30MHz folded dipole.
 10W, 100W, 1kW No radials required.
- Hard-drawn copper antenna wire.
 Aust/NZ distributor for Create antennas/ rotators & Phillystran (Keviar) nonconducting guying materials.
- High gain VHF & UHF amateur, scanning & TV antennas.
- Butt section triangular aluminium towers for fixed or tilt-over applications (refer March/April 1987 AR).
- Selections of power chips and TX
- tubes at friendly prices.

 VSWR/PWR meters by Diamond to 1300MHz 5 models. All in stock.
 - Ámateur Radio, July 1992

The Story of Stephen Frith

Part 4

H Karl Saville VKSANI H 1945 Worth East R TEATREE QUILT SO

In the final part of my story of Stephen, I will describe the effects of fitting a speech synthesiser to the computer. I had seen an article in an Australian electronics magazine back in February 1966 by Mark Bishop, of a speech synthesiser using the General Instruments SPO256-AL2 Speech Processor, but at the time I did not have a use for one. However, one of our TAD committee members, Richard Jackson, recently demonstrated a talking blood-pressure device which he had made up for the Blind Institute, and this rekindled my interest in speech synthesisers.

T WAS CHEAP TO MAKE, AND fairly easy to program, and while it is not the best speech synthesiser, it is adequate for our purpose, and the more time you experiment with it the better the speech sounds get. One has to learn the basics of word sounds and how they are built up and it is like going back to primary school again.

The SPO256-AL2 is a single-chip N-channel MOS LSI device that is able, using its stored program, to synthesise speech or complex sounds. With 59 discrete speech sounds-called allophones-andfive pauses, any English word or phrase can be created by addressing the appropriate combination of allophones and pauses.

This seemed to be the logical step to take with Stephen. Up to now he had been enjoying himself playing games and only occasionally using his word processor. When I fitted the speech synthesiser to his computer programs I thought it would enable him to speak to the world or, if the

volume was turned up, he could shout to the world, but it did not turn out as I had thought

thought. I may have mentioned previously that Stephen is married to Linda, and that Linda is as helpless as Stephen, but for one very important detail. She can talk, and because she has a voice she has been educated and. as a consequence, she is really a normal intelligent being. She and Stephen have grown up together and, because of their very close association, there has developed a sort of body language between them. Stephen has no trouble at all letting people know what he wants because Linda seems to know, and she will tell you. Stephen has grown to depend on Linda in this way. And, because of his lack of voice, his education was not as good as Linda's, He finds it very difficult to express himself with a word processor. Now he has his computer and can out letters on the screen, the training staff at Julia Farr are giving Stephen regular

lessons in spelling and grammar, and it is hoped he will become proficient in using his word processor in the near future

In the meantime he prefers to play games on his computer and will spend all day long trying to beat the computer

When you consider that a helptess and disabled person has about 12 hours or more each day to while away, you can realise they cannot be just putting messages upon the screen all the time. It would become very boring, as it is very slow and difficult, and also very tiring for him. It takes two to make a conversation, so he would need a friend, or someone, to be standing by his side for a onsidenable period, asy 15 minutes or more for each sentence, and it could take a long time to hold a meaningful conversation. Most of the time he and Linda are controlled to the side of the day of the side of the si

However, speech has made it possible for the computer to be more than just a machine that communicates, entertains or educates. It can become a personal thing, in fact a personality. The computer can announce the program that is to be used, it can say whose turn it is for the next move, or who won the game, and by how many points, and also congratulate the winner by name. We all like to be congratulated when we achieve something, and the disabled are no exception. The computer can have a name and announce itself to the operator. In other words, the computer responds in a friendly way and interacts with the operator. This is very importantly to a severely disabled person, as he can take command and be in control (maybe for the first time) of the situations created in the computer He feels he is not alone any more, he has a real friend, a friend who talks to him and is his constant companion - and the disabled really do need friends.

institutional Care

It is very strange, but you would think that, being in an institution, if a computer wrote out the phrase "I want a drink" and the speech synthesiser loudspeaker said "I want a drink", and if this was repeated many times, someone would come running with a drink. But, unfortunately, it does not work quite like this.

Institutions are run by the clock. Seven o'clock, and a nurse comes and prepares resident for wakey wakey. Eight o'clock, another nurse comes and takes the resident to breakfast. Nine o'clock, nurse takes resident to bath. Ten o'clock, nurse brings round the pills. And this carries on through-



AESU FT-911 23cm HANDHELD

WITH 2 YEAR WARRANTY

The incredibly compact FT-911 transceiver provides superb performance on the 23cm amateur band and is designed for quick and easy operation A multi-function backlit keypod allows fast frequency entry plus programming of the 49 tuneable memories, selfing of the programmable power saver system and a host of other convenient functions The microprocessor control system also features 2 VEOs, rotary dial luning in 4 selectable funing steps, a backlif 7 digit LCD screen with bar graph PO/S-meter, and a range of scanning features including busy channel, band, or selective memory scanning and priority channel maniforing VOX (Vaice Operated Tx) circuitry is also provided, allowing handsfree operation with the optional YH 2 headset. Comes complete with a long-life 7 2V 1000mAH NiCad battery pack, carry case, belt clip rubber duck a antenna and approved AC charges

Specifications Frequency Coverage

Channe Sleps Power Output Current Consumption Stand by (with 1 sec save) Receive

Sensitivity (12dB SINAD) Dimensions

1240 - 1300MHz 10 12 5, 20 & 25kHz 1W @ 7 2V - 12V

150mA Better thon 0 2ul x 32mm



Here's a compact 23cm FM mobile fransceiver that really packs a punch! It's ideal for both mobile and base stations and has a wide treatiency coverage (1240-13000MHz), plus 10 watts RF output. A rugged die-cast chassis logether with extensive use of surface-mount components gives excellent RF isolation and long-term revolutify. What's more, the easy to use control panel has a backlif LCD screen with auto brightness control and PO/S-meter As well, it has 4 selectable funing sleps, a total of 21 memones, inbuilt CTCSS tone squelch encode, one-touch repedier revers and a variety of scanning functions. Comes complete with a mobile mounting bracket, MH-14A8 hand in craphone

and DC power lead Cat D 3390

MEGA BONUS - SAVING OF \$70! With every FT-912R you can purchase the Diamond F-1230A 13 5dBi gair

vertical base antenna for just \$169 (Cal D 4870 usually \$239)

FT-650 6m/10m/12m



The FT-65Q is a high power all-mode mobile transceiver backed with specialist features for the seious 6m operator. There's continuous coverage reception from 24 5 to 56MHz (so you can follow the r sing M.U.F. and work the DX earlier) and 3 direct digital synthesizers (DDS) for clean transmit and receive operation. It has 6 front-end Band Pass Filters and a 2 stage law noise preamp for exceptional sensitivity (SSB typically 0 125uV) User selectable tuning steps, manual and automatic IF Notch filters, IF Shift and IF bandwidth controls give optimum performance under difficult conditions. In addition, DDS gives SS8 bandwidths of 1,8,2,0,2,2, and 2 4kHz as standard. With Yoesu MH 1 hand microphone

MEGA BONUS - VALUED AT \$1991 With every FT 650 you get a HF/6m SWR/PWR meter with accurate P E P metering at no extra cost Cot D 1360

Cot D: 3380



Ton of the line fentures reliability and value for money from the name you can trust. Yoesu. Only the compact

- 144 to 148MHz transceive poeration, with enhanced receiver
- oerformance Ultra long life 1000mAH 7 2V NiCod battery pack (supplied as standard!) 2 5 watts RF output as standard, 5
- watts with 12V DC (or optional FNB-11 NiCod) Better than 0 16uV (12dB SINAD)
- sensitivity Stand-by current consumption (1 sec
- SAVE) only 7mA Programmable power saver for extended operating periods
- . Keypad or dial frequency entry, with selectable huning rates
- 49 tuneable memories which store repeater offsets
- . Band, memory, priority or limitedband scanning
- Just 55 x 155 x 32mm
- . Carry case, belt clip, carry strap and approved AC charger
- Now with enhanced receiver sensitivity and improved strong signal bondling

Cot D 3350 \$**4**79

2 YEAR WARRANTY

FT-470 2m/70cm **HANDHEID**

Dual-band performance at its best The compact FT-470 is an easy to use bondheld transceiver that gives you areater flexibility with a sensible microprocessor control system for both 2m and 70cm operation

- 144-148MHz and 430-450MHz transceive operation
- · Single band or dual-band receive, or full duplex cross-band operation . Ultra long-file 1000mAH 7 2V NiCod
- battery (supplied as standard!) . 2.3 walls RF output (both bands) as
- standard, 5 watts with 12V DC Back-Irt dual 5 1/2 digit frequency LCD syreer
- Better than 0 16k/V (12dB SINAD) sensitivity on both bands
- CTCSS tone squelch encode decade inbuilt as standard
- Stand-by current consumption (with 1 sec save) only 8mA per band · Keypad or dial frequency entry, with
- selectable tuning/spanning rates 21 funeable memories and 2 VFO's
- oer band · Bond, memory, priority or limited
- band scanning · Complete with carry case, belt clip, carry strap and approved AC charges
- Only 55 x 180 x 32mm OH D. 3360

\$7**49** 2 YEAR WARRANTY





you get a bonus FNB-14 1000mAH NiCad battery Cat D-3351 VALUED AT \$99.95 Offer valid unit the 29th of August or while stocks lost

FT-747GX COMPACT H.F TRANSCEIVER



With every FT-411E you

get a bonus FNB-14 1000mAH NiCad

battery (Cat D-3351)

VALUED AT \$99.95

Offer valid until the

29th of August or while stocks lost

The FT-747GX is a compact SSB/CW/AM and optional FM transceiver providing 100 watts PEP autout on at 1 8-30MHz amateur bands, and general coverage reception from 100kHz to 30MHz. Convenient features include a front panel mounted speaker and an easy to read backirl digital display, dual operator selectable turning steps for each mode, dual VFO's for sol trequency operation and 20 memory channels (eighteen of which can store split Tx/Rx frequencies) Wideband 6kHz AM and narrow 500Hz CW IF filters are also a standard feature. Complete with Yoesu MH-1 hand. microphone Cal D-2930

\$1299 YAESU

Your choice of 2 Mobile One HF whips

MEGA

from our range of 80m. 40m or 20m whips WORTH OVER \$85. * Offer valid until the 29th of August or while stocks lost

2 YEAR WARRANTY



PRICE

Don't miss this best ever price on the popular Diamond X-200A dualband 2m/70cm base station arrienna. Hurry in and save \$30 on this high performance Japanese vertical antenna (white stocks lost). The X-200A uses robust FRP (flaregrass reinforced polyester) tubing construction. and a ground plane to provide excellent all-weather operation and a clean low-angle radiation pattern This sturdy antenna has stainless steel hardware throughout and solid mounting hardware for a stable connection to your mas

Specifications

Frequency - 144-148MHz, 430-450MHz 2m-6dB, 70cm-8dB

200W Max Power 2.5m

2 x 5/8 wave (2m) 4 x 5/8 wave (70cm)

Length -Cat D-4860

\$**460**

ST-7500 2m/70cm MOBILE ANTENNA

A high performance dual band antenno at a down to earth price! The ST-7500 is just 1 metre long and uses a ground independent design to provide high gain (3dB on 2m, 55dB on 70cm) with a maximum power rating of 150W Quality construction plus a hitable whip structure makes it especially idea! for the discerning mobile operator Requires \$0-239

ontenno base (D-4036 recommended) Cat D-4810

2m/70cm HIGH GAIN HANDHELD ANTENNA The Diamond RH770 is a high gain telescopic dualband antenna for use on

handheld transceivers when maximum range is required. If provides approximately 3dB gain on 2m and 5 5dB agin on 70cm. If weighs sust 85 groms and collopses from 93cm to 23cm for easy storage. Comes fitted with a standard BNC connector to attach to your

fronsceiver Cat D 4336

HUSTLER HF TRAP VERTICAL ANTENNA The tradition continues! The SBTV is yet another

HUS LER

masterpiece from the people who have been making antennas for over 33 years. This rugged 5 band HF trap vertical uses Hustler's exclusive trap design (25mm solid libragiass formers, high-folerance frap covers and low ioss windings), for accurate trap resonance with 1 kw(PEP) power handling. Wideband coverage is provided on the 10, 15, 20 and 40m bonds (SWR typically 15 I at resonance, less than 2 1 SWR at band edges), with 80kHz bandwadth typica on 80m at less then 2 1 SWR. An optional 30m resonator k.t. can also be installed without affecting operation of the other bonds

High strength aluminium tubing and a 4mm (wall Inicianess) extra heavy-duty base section provides columnin mechanical stability. What's more stainless steel clamps and hordware guarantee a longer life. At just 7 65m, the 68TV can be ground mounted (with or without radias, although radials are recommended), or it can be mounted in an elevated position with a radial system. Unlike other ontenno designs the

5BTV can be fed with any length of 50 ohm coax coble Cat D-4920

30m Resonator Kit

Adds 30m coverage and includes \$7095 all hardware Cat D-4921

VPK-4 Padial Kit Surts 5BTV (with or without 30m option) Cal D-4922 \$5,095

HUSTLER RX-2 2m 5/8 WAVE MOBILE

Here's value! A quality 2m 5/8 wave magnetic mount antenno for mobile or temporary base stat on use Comes complete with 4 5m of coox cable with a PL259 attached. It has 3dB gain with a power rating of 100W maximum and a flex ble stainles steel radiator to minimise wind loading

HUSTLER Con D-4805

DS XPRESS PHONE & MAIL ORDER SERVICE & YAESU BROCHURE HOTLINE Outside Sydney (Free call) 008 22 6610 Sydney & Enquiries (02) 888 2105 FAX (02) 805 1986 Or write to DS XPRESS, PO BOX 321 N/RYDE NSW 2113

YAESU STOCKS NOT HELD AT ALL STORES, PLEASE CONTACT YOUR LOCAL STORE FOR STOCK AVAILABILITY, OR ORDER BY PHONE 008 22 6610

* 18/07_2 18/08 * Elevition Supra 757 4484 * Unbahade ## 71 722 * Seption ### 5644 * Seption ## 71 722 * Seption ### 5644 * Seption ## 71 722 * Seption ### 5644 * Seption ## 71 722 * Seption ### 5644 * Seption ## 71 722 * Seption ### 5644 * Seption ### 564 \$399 • Bankstown Square 707 486 III 439 5311 • Gosford 25 0235 • Hon

out the day. Lunch time, pill time, drink time, dinner time, etc, etc. Nurses have a schedule to keep. With a large number of residents to look after, and many are very difficult to manage because of their desabilities, it is not surprising the nurses and other staff are generally run off their feet trying to keep up with the schedule.

And it takes a very special kind of person to be a good nurse for the disabled, and I have met many very dedicated nurses.

Generally, though, Stephen has a lot of time on his hands, and his computer becomes his mate, his friend, some days his only friend, his constant companion — a companion thay jumps at his command and does what he wants it to do—and it helps to fill in those very long hours with something interesting

Programming for the Disabled

Programming for the disabled is an ongoing occupation. New programs come to long going occupation. New programs come to mind, all programs need changing, become unidated. The operator's skill improves and time delays need shortening to keep up on with their speed of operation. More difficult games are needed, and programs of wider and wider interest are needed. Stephen to started with the Mosse code and, because of the his mability to transmit a readable Morses code signal, a combination Morse and scanning system had to be used.

As his ability at operating the switch improved, various methods of scanning and stepping were introduced to increase his acquisition of letters or words. It has been as much a learning exercise for the programmer as it has been for Stephen.

Conclusion

I attended a Caring Mothers meeting recently and was very surprised to learn of the number of brain-damaged people caused by canaccidents in South Australia We are told by the media of the number of deaths each year through car accidents, and that there have been more, or less, this time last year, but rarely do they publish the number of people who have been brain damaged because of these accidents. The hospitals operate and stitch them up and. when the wounds are healed, send them home to mother to look after them for the rest of their lives. There are 4000 of these brain-damaged people in South Australia alone

Since just before Christmas, I have been training one of these lads in the use of a computer He is a young man in his mid-20s, helpless and cannot talk. His name is Kelly The only way he can operate the computer switch is with his foot.

Then there is Sue, a lovely girl. She is 29 years of age, with cerebral palsy, and cannot talk. She operates the computer switch with the back of her head. Her parents want to get her a printer so that Sue can write her life story.

I mentioned in the first part of this story that I was a member of the Technical Aid to the Disabled.

Technical Aid to the Disabled (TAD) is a

voluntary organisation comprising a group of about 80 technical members (in South Australia) with varying skills, such as carpentry, mechanical/electrical engineering and electronics. We also have experts in the latest computer usage and programming

When called upon for assistance, our members will design, construct, install, rain and maintain any assisting device unavailable commercially, or will adapt existing asds, facilities and everyday items more specifically to meet the needs of the user Induviduals, family or friends may contact TAD directly as there is no referral necessary

We work very closely with the Juliar Farr Centre, Royal Society for the Blind, regency Park Centre for Young Disabled, Royal Adelaide Hospital, Domiciliary, Care, Intellectually Disabled Services Council and many other organisations

Our members are volunteers, and there is no charge for the time spent on a project, but the client is asked to meet the cost of materials used, and out-of-pocket expenses. In some cases a small administrative charge may be necessary

It we can help, or you know of someone with a disability who would benefit from using our services, contact us on 261 2922.

(in South Australia) of write to the Coordinator, Technical Aid to the Disabled, PO Box 112, Pastwood 5063.

ordinator, Technical Aid to the Disabled, PO Box 112, Eastwood 5063. (Corresponding information for NSW was published in January AR, page 30 Consult the telephone directory in other

states, Ed).

EARLY AMATEUR RADIO IN AUSTRALIA - A CLARIFICATION

52-54 Mtlls Rd, Clembasem 2156
In my article published in AR of Msy
1992 I stated that from 1899 to 1905 the
Royal Asstralan Navy was in charged
of wireless matters. To be strictly correct, it
was still the Australian Squardon of the
Royal Navy Prior to Federation, in 1901,
the various Australian states had their own
military forces, including an assortment of
mail armed vessels, to protect their cauge
ment took on this responsibility in 1901
but looked to the Royal Navy for half in and
financial assistance. Between 1901 and
financial assistance. Between 1901 and

the expected contributions from states.

commonwealth and the UK during which

time the navy was called the Common-

Colin MacKinnon VK2DYM

wealth Naval Forces. On 10 August 1914, this embryonic navy was placed under the control of the Royal Navy for the duration of the war, and by the conclusion of hostilities was officially the Royal Australian Navy.

The various Government Acts that I mentioned were not the inspiration of some clever Australian orlik committee, but followed very closely the UK Acts for the same purpose of controlling wireless and telegraphy. Therefore they were influenced by events in the UK, including the PMG Monopoly, stiffing of amateur experiments the arguments with the Marconi Co, and the dislike of that company in many circles. In 1923 AW Was able to exert sufficient influence on the authorities to break away from the UK regulations which dictated a broad-

broadcast entrepreneurs wanted and got the 'sealed set' system, with stiff royalty and licence payments. It falled miserably In my article I told how a Perth radio club used its equipment to discover a number of illegal stations. Recent access to official records reveals that after the outbreak of war, suspicious telegrams were being sent from Perth to remote areas to the north and then transmitted by illegal wireless stations associated with German companies or friendly to the German cause Germany had a number of colonies to our north equipped with powerful wireless stations capable of relaying the information to Germany and to ships atsea. The enemy's local & overseas colonial wireless stations were captured and destroyed early in the war

The Horrors of CW

Julio Kentwell VK2XBR/VK2KSE/VK2ISI 34 Raymond Rd

Back in 1982 I obtained a limited amateur ticket. VK2XBR. The event was not shown on national TV news broadcasts, nor did it make the front pages of sundry newspapers; in fact, it never even appeared in the sports section. Nonetheless, it was done.

HY A HUMBLE LIMITED. NOT the mighty full call? Let's say I considered CW to be a boring, unwarranted imposition; antiquated, ridiculous, irrelevant and about as applicable to amateur radio as being able to type 20wpm in order to gain your certificate for HF. As for HF. I considered it to be full of old windbags who could talk for half an hour without actually saving anything, who had most likely never learned which end of the soldering iron was which, and who used only store-bought gear.

The lure of VHF/UHF had been strong in me since my teenage years in the early to mid-1960s: up there I would go, and damn HF.

Everything proceeded smoothly for nine years. I explored ATV, built the VK2RTS Sydney ATV repeater, built much VHF/ UHF home-brew, including my famous collection of 415V three-phase-operated two metres and UHF year I still considered HF and CW to be the domain of fools

Back in early 1973 I had started learning CW I could do about 6wpm when, in unfortunate circumstances, my right arm was cut halfway through and, predictably, became purely ornamental (totally useless in fact!) for quite a long time thereafter. So much for CW!

I never regained my interest in it, and that

was that It should be mentioned that I had spent some years on 27MHz as "Batman" in the old pirate days, along with many others who are today's amateurs, and a few of these years were during a sunspot peak around 1979, so "been there, done that" applied to me in terms of world-wide DX on HF. During my years on amateur radio as VK2XBR I was never heard to say anything nice about CW: in fact, I rubbished the hell out of it.

There comes a time in one's life when some of one's pontifications rebound upon oneself with a crash. One is then in the ridiculous position of having a large black crow, complete with feathers, jammed into one's flapping mouth and being, unequivocally, told to eat it.

Yes folks, it happened to me!

In my ATV years I became friends with one Doug Chaffey VK2NBC. Doug eventually upgraded his licence to VK2G1E, subsequently VK2FC, and continued to play a leading role in the development of ATV activity. Doug had been VK2NBC since 1976, while anther chap, Ralph VK2ZRG, had been a limited for around 30 years; they made a deal. "I'll upgrade my theory if you upgrade your CW* and vice-versa. Well, it worked and they did, Ralph became VK2NR.

So far, so good,

The real problem came when, in late 1991, Doug pulled up stakes from Chester Hill and moved to Trangie Yeah, I know. where the hell's Trangie? It's on the Mitchell Highway, about as far past Narromine as Narromine is past Dubbo. Ever tried to

work Trangie from Springwood NSW on two metres? It's not on!

Now I find I have a problem I want to keep contact with Doug on the bands and Lean't. What to do?

Meanwhile, as all this was occurring, Ralph VK2NR had set up a system with Paul VK2IPL, at whose domicile resides the 2m section of the VK2RTS ATV repeater This repeater is a complicated device using one callsign from two locations, capable of independent 2m and ATV operation as two repeaters or as one giant complex, too involved to describe here Through the magic of amateur radio, not to mention some Ralph-brewed equipment, Ralph set up a system for slow-morse practice sessions (as if anyone would be idiotic enough to call 12 or 14wpm slow, although Doug does 45wpm), which sessions I, of course, ignored

Until my problem!

On 13 November 1991 I sat down for the first time to try to copy Ralph's slow morse after an 18-year layoff. At 5wpm, two sessions of five minutes each, I made five and 10 errors. Pairly obviously, learning CW is like learning to ride a bicycle- once you master the art of falling off the damn thing, you never forget how it's done Admittedly. 6wpm and above looked as though it had been mauled by a pack of wolves but, in less than one week, 6wpm was down to five errors over five minutes with just two sessions of practice. I passed my 5wpm send and receive on 1 December 1991 Enter VK2KSE, King Size Ego

The old Batman-days FT707 had some seven years worth of dust on it, but still worked. The glorious moment arrived and I had my first HF 80m OSO with Doug VK2FC on SSB This probably won't interest you very much - if at all What might interest you, though, is that the following evening I had a CW OSO with Doug This event is regarded by me as a high spot in my chequered amateur radio career

Why should this be?

Because, believe it or not. I had discovered the enjoyment, pure and simple, of goode olde steam powered CW wireless Now who would believe the man dubbed Mr Amateur Television by his peers, and a confirmed CW hater, would ever do that?

Not I, cried the little red hen! Having achieved the ability to work Doug

on 80 metres with my Terry VK2UX/Tim VK2ZTM inverted-V antenna the story

should have ended there. It doesn't My most important discovery so far is that CW is fun! No-one could have to dime this, I would have laughed aloud at the idea. I had to find out for myself

So, undaunted by the rapidly increasing "diddley dahs", I soldiered on towards 10wpm, and this is where things started going a little funny. You would expect that, as you regularly practised your CW receiving, your error score would steadily drop. That sounds fair enough, doesn't it? Except that it's not what actually happened Right from the word go, all my CW receive practice was done in a book and the number of errors made was entered in a chart. At this stage I was still doing only two nights a week and my error scores at a given CW speed varied wildly (and somewhat crazily!) from night to night. As an example, take my errors at 10wpm over a short period: 46, 22, 13, 31, 32, 27, 39, 44, 21, 29, 28. If there's any downward trend there, I can't

find it

A discussion with Terry VKZUX resulted
in his suggestion that I use the VKZSWI
more practice sessions each evening. So I
did, and the errors started to take on a
pattern Two-Chart were now kept-one-lof
Ralph VKZSWIS CW on VKZUTS Grown which
error's cores above were taken's and one
for VKZSWIS WI
WE place in from
the property of the property of the property of the
where I started using VKZSWI and, from
Ralph's Jowynn, we have errors of: 27, 25,
19, 5, 9, 12, 17, 6, 5, 2.

Now this is much more like it!

The proof of the pudding was indeed found in the consumption thereof. Terry's idea bore fruit very quickly; the secret was in a little CW practice every right.

One VKZBWT operator, Jim VKZNDI, supplied another valuable clue. He said, "When you're copying around 75 percent of the 10wpm segment, go to 12wpm and concentrate on the higher speeds." It heard him say this just one week before I went for my exam, which was my rotten luck, be-

cause it's good advice and worth knowing.

Probably one of the most important facts you'll ever her about learning. GW was mentioned to me by Cec Purvis. Cec points out that CW is assound. Hyou learnto receive good CW (and there's plenty of the other sost around) then you will know yourself whether or not your own sending is good, just by the sound off; Fairly obviously, you need not touch a key until you are well on the way in receiving.

I actually proved that My first use of a Morse key in 18 years was when I did my Swpmsending test, no errors and acclaimed as good CW, even though sent by a man with a mangled sending arm. The point is that if you learn good CW first, you will send good CW.

The great moment arrived, and on 1 March 1992 I passed 10 wyns need and receive. Know something? It was easier than I hought it would be, even though I was a nervous wreck before the event and knocked over two cans of beer to settly myself down prior to having a go. I had to widen the gap on the key to stop my shaky hand from bouncing the key around, but out flowed the good CW and all was well. I had put in the work; I respect her newards while others at the same exam failed because they just hadn't been far dinkum about putting in the effort. How senous were they about upgrading?

Which brings us to the crux of the matter I never did think that CW, any more than 1 upping or public speaking, should be a requirement for HP operation, now, having and clone it, I am still firmly of that opinion. CW does absolutely nothing for your technical expertise, therefore it is irrelevant in terms of a focuse to the still result of a force of a force of the still result of a force of the commission of a force of the still result of the commission of a force of the still result of the commission of the

My friend Barry VK2FP is learning to play guitar. It will take him many years to play it as well as I do, since I have played for 24 years and practise every day. Do you play a musical instrument? If so, how well and how often. Is it fun?

You can learn CW, with just 10 minutes a day at it, in a few months Anyone who can't spare that time is a ratbag or a liar. The big question is whether or not the time spent is worth the bother For me, it was.

No doubt about it, the day will come when CW is no longer required Until then, people will continue exercising their raph of choice in pursuing it or not, as they see fit Many of those who do their five or lowpm and pass will puthe CW key away, never to be used again Others will keep it connected and ready for use because, like me, they are proud of their achievement and genuinely like CW, for the pure enjoyment of it. That's what it's all about, those lift operators who say'! had to do CW so the control of the

My thanks to Ralph VK2NR, Jim K2NDI, Rosco VK2BRC, Michael VK2BMW and Doug VK2FC for their help in getting me where I needed to go. Thanks also to Terry VK2UX and Cec Purvis for a helping hand

May the Morse be with you!

Sunday CW Net

The number of the Sunday CW Net, held on 31 May, was 984 Many CW operators may care to note that the 1000th Net should take place around September '92. Information can no doubt be obtained from the Sunday Net controllers.

G Lanyon VK2AGL

Support the WIA in order to protect amateur radio frequencies

Intruder Watch

Gordon Loveday VK4KAL, Federal Intruder Watch Co-ordinator, "Aviemore". Rubyvale 4702

Freq	UTC	Date	Mode	Comments	x
7.002	1235dly	230392	AIA	V hrd more in winter	27
7014/16	1130+	2303	2xR7B	Possibly north of VK/ZL	21
14002	0638	030492	A3E	Foreign language B'caster	
14003	1015+	120492	NON	Nil ID during listening time	3
14006	1210	090492	A3	Nil ID, QRN'd VK6HG	
14008	1517	190492	A3E	B'cast for no ID	
14015E	1233	110492	JE3	2-way tfc Chinese	
14032	1405	090492	J3E	B/c stn Indo or Malay lang	
14044	0930+	daily	2x LSBI	+ guard freq? 3 all told???	31
14045	1300	080492	J3E/U	R Nederland re B/C via R fone	6
14045/6	1039+	0704 dly	NON	No 1D in 3 hrs	20
14058+	0815+	2304 dly	PON	+AC3 fax China??	42
14059+	0800+	210492	FIB	Unable to resolve fully	4
14060E	1108	060392	AIA	No further info	2
14070	1030+	010492	AIA	VBX coded tic out mainly	25
14075	0830+	0204 dly	A1A	VRQ cq de VRQ MSG-SGO, LAF etc	33
14078	1205	140492	A2A	CK80 calling CQ fast CW	
14080	0330/35	0604	A1A	KFB XQ de KFB as PHL etc	11
14092	0955+	110492	A1A	RGT77 coded traffic	2
14095	0200/06	0604	A1A	VPC/CQ de VPC AS RGU etc	13
14100	0930+	040492	AIA	NZB coded tfc	27
14126	1030+	0704	F1B	Cont RTTY 2.5KHz shift	10
14210	0950mni	2303mni	A3E	Harm of 7105/f severe distort	25
14211/15	0935	2303mni	2x F1B	Both 250Hz shift, 3rd regis	28
14217.5	0700	240392	F1B/A1A	UMS + NON when NIL tfc 250Hz	12
18075	1035	0304	A3E	B'cast stn, talk in English	2
18080	1208	100492	A3E	B'cast stn Chinese	10
21001	0500+	2603	NON	A1A often hrd no ID	19
21031	0500/600	260392	F1B/A1A	MINR CW tfc to UUU UMS	33
21250	1009/+	0704	NON	Some NS CW & R7B	11
21283.5	0705+	240392	A1A/F1B	UU UMS mostly 250Hz	47
21315	0500+	220492	A3E	B/c, faint music (7105 x 3)	10
21379	0500+	240492	A1A/F1B	UMS ID in A1A	2
24900	1143	2904	A3E	B'cast stn middle E, music	2
24925	1052	030492	J3E/L	Russian military stn	3
28183	2221	130492	F1B	50bd news in French	
28515	1149	200492	A3E	B'cast stn music	
Prece 204	nn 20565	20575 20505	20605 206	25, 20675, 28505 are higger one progra	2mm

Freqs 29500, 29552, 29575, 29995, 29605, 29625, 29675, 28995 are breast area programming musls and or talks - all non-amateur origin, all logged many times by VK6RO. Our winter is bringing an influx of CB stations from all Asian areas onto 28MHz band. Observers this month: VKs 4BG, 4AOX, 4BHJ, 4BTW, 4BXC, 5TL, 4BXC, 5TL, 6AJ, 6RO, 6BWJ, 7RR.

Support the advertisers who support Amateur Radio magazine

This space could be earning you money!

Advertising rates available from PO Box 300 Caulfield South, 3162

A Call to all Holders of a Novice Licence

Now you have joined the ranks of amateur radio, why not extend your activities?

The Wireless Institute of Australia (N.S.W. Division) conducts a Bridging Correspondence Course for the AOCP and LAOCP Examinations

Throughout the Course, your papers are checked and commented upon to lead you to a successful conclusion

For further details write to The Course Supervisor

WIA PO Box 1066

Parramatta NSW 2124 (109 Wigram Street, Parramatta) Phone. (02) 689 2417

11am to 2pm Monday to Friday 7 to 9pm Wednesday

PACKET RADIO PRIMER

by Dave Coomber G8UYZ and Martyn Croft G8NZU

ISBN 1 872309 09 7, first published 1991 by the Radio Society of Great Britain 140 pages. Price UK£7.00.

Reviewed by: Bruce R Kendall VK3WL

At last someone has written a book as whiten a book as we have because nearly everything I have read about this rapidly growing segment of our hobby is either written in "Packatese", or assumes the reader has some existing knowledge of computers or packet radio isself.

of computers or packet radio itself.
The preface to this easy reading book for the beginner openly states that "it is not intended it should be a standard reference manual, and some liberties have been taken with the deeper meaning of some of the more technical aspects of "packeteering".

Consisting of seven chapters and alx appendices, this book covers most of the basic information required to get on the air using the AX25 protocol Subjects such as the radio, the terminal node controller, the computer, software requirements, commands, operating procedures, mailboxes and bulletin boards are covered in a way that makes the newcomer feel comfortable. It goes on to discuss the various bulletin board software packages in use, and the basic commands one requires when logging

commands one requires when logging on to these mail boxes.

Appendix 4 is on "PC Software" and

Appendix 4 is on "PC Software" and details some of the TNC commands and features of YAPP v2.0, ProComm v2.41, and Paket v4.0

The information contained in this took is about 99 per cent applicable to our local packet radio scene. There is no our local packet radio scene. There is no however, a few instances where negulatory requirements peculiar to the UR are mentsoned, such as the quite British requirement for Monee code station identification when using packet and/or transmissions. These few points and/or transmissions. These few points asade, readers should have little faculty is getting their packet stations up and running using the Information con-

For those amateurs who have yet to experience this mode of communication, or for the frustrated packeteer who is having difficulty digesting the existing range of publications on this subject that are often not written for the raw beginner, this book is a must and I would suggest it as recommended reading.

The authors do recommend in their preface that for the more technically minded or more advanced operator, other publications such as the RSGB and ARRL handbooks be consulted in conjunction with or after reading the Packet Radio Primer.

Pootnote: Other publications such as Your Gateway Io Packer Radioby San Hornepa WAILOU, and available from divisional bookshops, make good reading but do not, in the opinion of this reviewer, handle the basics quite as well as Packer Radio Primer Both publications have their place, but the latter is recommended for those wishing to take their first steps in packet radio.

MURPHY'S CORNER

tained within

In the article by Paul Kay VK4SY 'Homemade Spectrum Analyser' on pp24-26 of the June issue, the photographs are both upside down and transposed. They are reproduced correctly below. Apologies to Paul for the mixtup.

internal view of spectrum analyser -PSU is in top lefthand corner. Mitsumi tuner is in the middle, and the Ferris HF3000 board





analyser.

On p45 of the June Issue, Dave Horsfall VK2KFU should have been described as Deputy Co-ordinator for the Sydney North region, not for the whole of NSW.

Amateur Radio, July 1992

Awards

John Kelleher VK3DP Federal Awards Manager

The A4-DX group of the Royal Omani Amateur Radio Society will activate these

DXpeditions: i Zanzibar, 15-31 July - callsign 5H0ROA ii Pemba, 21-27 July - callsign 5H0ROA/A Bands, 10-80 including WARC bands Mode, SSB/CW/Data

OSL: Via A47RS **Hervey Bay Award**

Due to the unqualified success of the special event that this club operated in August 1991, celebrating the Whale Festival, we have been requested by the city of Hervey Bay's Whale Festival Committee to organise a 'sister' award for August 1992.

Feedback from all parts of the world have led us to believe the award itself was very well received, and it is our intention to keep this standard of award - although a different presentation - to the forefront once again.

We wish to advise all members of the amateur radio fratemity worldwide that the Hervey Bay Amateur Radio Club Inc will be activating the special event callsign VI4FOW (Pestival of Whales) from 1-31 August 1992. The approximate frequencies will be: 3.794; 7.100, 14.235; 21.250; 28.495MHz, all + or -QRM, of course, and Australian novice frequencies will be activated as much as possible, as the bands permit.

The annual migration of these gentle giants, the humpback whales, into the warm, sheltered waters of Hervey Bay, enables them to rest and rear their young before continuing their southerly travels to the Antarctic regions. Visitors form many countries and all states of Australia arrive and marvel at the gentle nature of these magnificent creatures of the deep. Some lucky visitors have actually managed to 'pat' a whale from the sightseeing vessels

An award and OSL card will be available for working the special event station, VI4POW. Applications for the award may be directed to PO Box 829, Hervey Bay, Queensland 4655, Australia.

New Zealand Association of **Badio Transmitters**

This is the address for future applications for NZART awards NZART PO Box 108. Gisborne 3801 New Zealand

Air Forces Amateur Radio

Special Event Station VI4AAF

The Air Forces Amateur Radio Net is congratulating our RAAF on its 71st anniversary with an A4 sized Special Event Award. Only one contact required. Forward QSL or copy of log entry to awards manager. Len VK2LEN OTHR with \$3.00

Shortwave listeners may apply for the award by submitting an extract of log with \$3.00 to the awards manager.

You can find the Air Forces Amateur Radio Net on a Tuesday on 3.567MHz at 1000z and 3.610MHz at 1030Z, also on Tuesday. We are using the callsign on other frequencies. VI4AAF.

Contests

Presented by the relevant Contest Managers

1992 Remembrance Day Contest - Rules This contest is held to commemorate those

amateurs who died during WWII, and is designed to encourage friendly participation between all amateurs and to help in the improving of operating skills of all participants.

This contest is held annually during the weekend nearest 15 August, the date on which hostilities ceased in the south-west Pacific

The contest is preceded by a short opening address by a notable personality, which is transmitted on various WIA frequencies during the 15 minutes immediately prior to the commencement time of the contest. As part of this opening ceremony, a roll call of the names of those amateurs who paid the Supreme Sacrifice is read

A perpetual trophy is awarded annually for competition between Divisions of the Wireless Institute of Australia. It is inscribed with the names of those Australian amateurs who made the Supreme Sacrifice, and so perpetuate their memory throughout amateur radio in Australia.

The name of the winning Division each year is also inscribed on the trophy and, in addition, the winning Division will receive a sultable certificate. The winning Division also holds the trophy for the next 12 months, after it is presented at the Annual Federal Convention

Objectives Amateurs in each VK call area will endeav-

Contest Fuded

- our to contact other amateurs · in other VK call areas. P2 and ZL on bands 1.8-30MHz, except the 10, 18 and
 - 24MHz bands: in any VK call area, including their own, P2 and ZL on bands above 52MHz, and as indicated in Rule 5.

0800 UTC Saturday 15 August to 0759 UTC



Sunday 16 August 1992 All Australian amateur stations are requested, as a mark of respect, to observe 15 minutes silence prior to the commencement of the contest. It is during this period that the opening ceremony broadcast, referred to above, will take place.

- 1. There will be two contest categories: (a) High Frequency (HF) - for operation on bands below the 52MHz band
- (b) Very High Frequency (VHF) for operation on bands from 52MHz and upwards 2. In each category there will be three sec-
- (a) Transmitting phone
- (b) Transmitting CW (c) Receiving
- Modes applicable to each section are as follows:
- (a) AM; PM, SSB; TV
- (b) CW, RTTY (c) Receive (a) or (b)
- 3. All Australian amateurs (VK callsigns) may enter the contest, whether their stations are fixed, portable or mobile. Members and nonmembers of the Wireless Institute of Australia are eligible for awards
- 4. Cross Mode Operation is permitted. Cross Band Operation is not permitted except via a satellite repeater.
- 5. Scoring contacts
- (a) All contacts score one point
 - (b) On all bands a station in another call area may be contacted once on each band using each mode, le you may work the same station on each band on phone. CW, RTTY and TV. (c) On the bands 52MHz and above, the same station in any call area may be worked using any of the modes listed at intervals of not less than two hours since the previous same band/ mode contact. However, the same station may be contacted repeatedly via satellite not more than once by each mode on each orbit. (d) Acceptable logs for all entries must show a minimum of at least 10 valid contacts
 - 6 Multi-Operator Stations Are Not Permitted (except as in Rule 7), although log keepers are allowed. Only the licensed operator is allowed to make a contact under his/her own callsign Should two or more operators wish to operate any particular station, each will be considered as a contestant and must submit a log under the individual callsign which applies to that operator.
- 7. Club Stations may be operated by more than one operator, but only one operator may operate at any time, se no multi-transmission. 8. Cohers - for a contact to be valid, serial numbers must be exchanged between stations making the contact. The serial number will comprise three figures commencing 001 for the first contact, and incremented by one for each successive contact. Should the serial number 999 be reached, the serial number
- 9. Terrestrial Repeaters contacts via terrestrial repeaters are not permitted for scoring

will revert to 001

- purposes. Contacts may be arranged through a repeater. The practice of operating on repeater frequencies in simplex is not permitted.
- 10. Portable Operation Log scores of operators located outside their allocated call district will be credited to that call area in which the operator takes place, eg VK5XY/2 - this score will be added to the VK2 Division scores.
- Entries a log of all contest contacts must be kept. This should be in the format as shown in the example.
- A summary sheet for each category and section entered must be submitted to the RD Contest Co-ordinator showing the following information in this order as per the example shown:
- Category (HF or VHF), Section (phone, CW or receiving). Callsign, name, address, total
- Declaration: "I hereby certify that I have operated in accordance with the rules and sperit of the contest."
 - Signed: Date:
- Only the summary sheets for each category/section entered are to be submitted. DO NOT send contest logs.
- Sheets are to be forwarded to the RD Contest Co-ordinator, 2 Moss Crt, Kingsley, WA 6026. Envelopes are to be endorsed "Remembrance Day Contest" on the front outside.
- Entries must be forwarded in time to reach the RDCC by Friday 2 October 1992. Although they are not required by the RDCC, the contest logs should be retained by contestants in case proof of claimed score is desired by the contest co-ordinator.

Determination of Winning Division Scores by stations in VK0 are added to VK7.

- Scores by VK9 stations are added to the mainland call area which is geographically nearest.
- Scores claimed by P2 and ZL stations are not included in the scores of any VK call area.
- The formula to be applied to determine the winning WIA Division is as follows: Total Contacts per Division/Total Licences
- per Division times the Weighting Factor. The Weighting Pactor is calculated such that should each WIA Division perform equally
- as well in 1992 as in the past four years (averaged) the result would be a seven-way dead-heat.
- Consequently, the most improved Division will win the trophy, and also earn a revised and lower weighting factor for the following

Receiving Section Rules 1. This section is open to all shortwave lis-

vear.

- teners in Australia, Papua New Guinea and New Zealand. No active transmitting station may enter this section.
- 2. Contest times and logging of stations on each band are as for transmitting. Logs should be set out as per the example.
- It is not permissible to log a station calling CQ. Amateur Radio, July 1992

- The detail shown in the example must be recorded 4. Scoring will be as per Rule 5 for transmit-
- ting, with other aspects of that same rule also applying.
- 5. Club stations may enter this section. Example Transmitting Los Remembrance Day Contest 1991
- Callsign: VK1XXX Category, HF Section: (1) Transmitting phone Date Band Mode Call No Pts Time (MHz) Red
- (UTC) 9800 002 14 SSB VK200 001 6802 14 SSR VK6I1 002 00 1 SSB VK5ANW 0805 14 003 011 0807 14 SSB ZL2AGO 004 003 SSB VK4XX 007

005

Example Front Sheet Remembrance Day Contest 1991 Category: HP Section: (a) Transmitting phone

0809 14

- Callsign. VK1XXXName: Joe Brown Address: PO Box 123, Farm Orchard, ACT 2611
- Total Score Declaration: I hereby certify that I have oper-
- sted in accordance with the rules and spirit of the contest Signed: I Brown Date: 20.8.92

Example Receiving Log Remembrance Day Contest Name/SWL No: 130371 Category: HF

- Section: (c) Receiving phone Band Mode Str
- Time (MHz) Catting Called Sot Red (URC) 0800 SSB VK1XXX VI(200 001 002 1 0802 SSB VK1XXX VIOSILL 002 001 1 0805 14 SSB VICSAMW VK13000 011 003 1 0807 14 SSR 71 24GD WOOD 003 004 1
- 34 SSB VK7AL VIC2PS 007 010 1 12. Dismalification. Any station observed during the contest as constantly departing from the generally accepted codes of operat-
- 13. Awards certificates will be issued in accordance with the Guidelines for Certificate Issue Remembrance Day Contest.

ing ethics may be disqualified.

Rules of the 1992 VK-ZL-Oceania DX Contest For VK and ZI. Stations

- 1 SSB: From 1000 UTC Saturday 3 October
- to 1000 UTC Sunday 4 October. CW. From 1000 UTC Saturday 10 October
- to 1000 UTC Sunday 11 October 2.Only open contact per mode per band is
- permitted. All bands except WARC bands may he used 3.VK and ZL stations are permitted to contact each other only on 160 and 80 metres. VK to VK: ZL to ZL, and ZL to VK contacts are

permitted on these two bands.

4 Cyphers: Exchange a five or six-digit number composed of the RS(T) report, together with a three-digit number beginning at 001, and increasing by one for each QSO

5 Scoring: Different points for contacts

On Omerent Dai	ilds are as ronows.	
160 metres	20 points	
80 metres	10 points	
40 metres	5 points	
70	1 point	

2 points 10 metres 3 points Final score will be the total QSO points multiplied by the total number of prefixes worked The same prefix worked on a different band is counted. Note: K1, W1, AA1, N1 etc are all different prefixes W1AAA/6 would

count as Wh. not W1.

15 metres

6. Logs (a)Separate logs for each band, please, and

for SSB and CW. (b)Show date, time in UTC, call of station

contacted, cyphers sent and received (c)Indicate clearly each new prefix worked

(Underline, highlight or show in separate column, as in CO WPX)

(d)State OSO points claimed for each band (e) State number of prefixes claimed for each band.

Summary sheet to show ...

** Callsign, name and address

- Total points claimed on all bands
- Total prefixes claimed on all bands
- ** Total points claimed
- Declaration that the rules were observed.

SWL Section: As for transmitting section.

** VKs must hear and log ZL or other stations (No VK stations)

" ZLs must hear and log VK or other stations (No ZL stations)

Post logs to: NZART Contest Manager, John Litten ZL1AAS, 146 Sandspit Rd, Howick

1705. New Zealand, to arrive by 15 December 1992. Awards: Separate awards for SSB and CW.

(a) Special certificates to top scorers in each prefix area

(b)Special certificates to top scorers on each band

(c) Participation certificates to all entrants on request (one IRC for postage, please).

> Help stamp out stolen quipment - always include the serial number of your equipment in your hamad.

1992 J		e Field Da	y results			
Section 6 Hour 6 Hour 6 Hour	Portable Home Stn Home Stn Home Stn	Operator Multi Op Single Op Single Op	Mode Phone CW Phone	Band All band HF HF	Callsign A Minter SWL VK4EAW VK6DE	88 26
6 Hour 6 Hour	Home Stn Portable	Single Op Multi Op	Phone Open mode	VHF/UHF HF	VK3PJB VK6BWI VK2BDT VK2HZ	13 3 16 266 *
6 Hour	Portable	Multi Op	Phone	HF	VK4WIN VK4WIW	172 254 •
6 Hour 6 Hour 6 Hour 6 Hour	Portable Portable Portable Portable	Single Op Single Op Single Op Single Op	CW Open mode Phone Phone	HF All band All band VHF/UHF	VK1WI VK3EFO VK4BLE VK4OE VK2ANK VK2DXV	140 22 290 286 366
24 Hour 24 Hour	Home Stn Home Stn	Single Op Single Op	Open mode Phone	All band All band	VK6BWI VK4EV VK3DD VK4PJ	20 38 157 48
24 Hour	Home Strr	Single Op	Phone	HF	VK5PMC VK5CN VK3CAY	38 169 98
24 Hour	Portable	Multi Op	Open mode	All band	VK7FD VK4WIS VK1AGA VK6ANC	36 2558 2276 2168
					VKSARC VK2WG VK3BML VK3ATL	1700 1394 944 678
					VK5BAR VK4WIT	448 182
24 Hour 24 Hour 24 Hour	Portable Portable Portable	Multi Op Multi Op Multi Op	Open mode Open mode Phone	HF VHF/UHF All band	VK6VS VK1WI VK4IZ	138 ° 2416 4404
					VK4WIE VK2FBK VK3GH VK3ANR	4254 2178 1333 1099
24 Hour 24 Hour	Portable Portable	Single Op Single Op	CW Open mode	HF All band	VI2FFG VK5BP VK3XU VK5NW	1058 212 30 ° 646 °
24 Hour 24 Hour	Portable Portable	Single Op Single Op	Open mode Phone	HF VHF/UHF	VK4DR VK5BW	464 ° 408 °

Congratulations to the certificate winners (annotated by an asterisk). Well done. It was disappointing to note insufficient. CW entries and scores to justify awarding the President's Trophy again this year. Hopefully more competition in the single op, portable, CW section next year

The number of logs submitted does not show how the popularity of the contest has increased over the past few years. I was not able to enter myself but had the chance to listen around and there seemed a lot of activity. More loss and in particular comments will hopefully be submitted next year.

On that point next year the rules will only be changed for 50 MHz contacts. Scoring for 50 MHz will follow the VHF/UHF scores up to 499 km. For distances over 499 km. 50 MHz contacts will score as for HP contacts. A table of scores such as the following has been suggested by a few contestants with varying scores depending on distance. This table is for portable stations only. Home stations will score on a smaller scale that is yet to be designed. 8-49 km 58-99 km 100-149 km 150-199 km 200-499 km > 499 km

2

ar

50 MHz scoring was the only area of contention in all the comments received with the logs. So if you want to comment on the rules for next year, read last years rules again and drop me a line. Your input is much needed otherwise no other changes will be made

Many stations failed to log any overseas contacts. The rules for the John Moyle do not exclude any operator from entering. Those stations that did log overseas contacts were noticeably ahead on scores for the contest Lets see if we can encourage more portable single operators next year. In the future I

would like to phase out log submissions by home stations. Any comments!

Entrants are reminded that I will continue to make myself available on air on the weekend preceding the contest for any last minute enquiries.

10

90

The 16th West Australian Annual 3.5MHz CW & SSB Contests Transmitting & Receiving Rules

1. Duration:

CW Sunday 2 August.

SSB Sunday 6 September Between the hours of 1030z and 1330z time, ic three operating hours for each contest.

2.Frequencies

All contacts to be made in the 3.5/3.7MHz band using frequency allocation applicable to your licence conditions

3.Calling

Stations will call CQ WAA using the three times three technique; infringement of this rule hy the use of long CO calls may result in disqualification, as will pre-arranging of a OSO.

4.Scoring

Points for contacts are as follows:

Within Western Australia 5 points per contact

WA to all mainland eastern states 2 points per contact WA to VK7 4 points per contact WA to VKO and overseas B points per contact

Three points per contact with WA stations only S. Multipliers

A multiplier of two per WA shire worked will

apply to the final score. WA stations north of the 26th parallel only: an additional multiplier of 1.3 will apply per contact confirmed with stations south of the

26th parallel 6.Contacts

4

(

Stations may be worked twice on each night, le once between 1030z to 1300z and again between 1300z to 1330z; these contacts will count for points. Each time the contact for WA stations will take the form of an exchange of five lett

Eas RST

Shire Identification Letters

e characters comprising RST/RS and shire ters. stern states and overseas stations will send I/RS plus a running number starting at 001.	53. Gosnetis 54. Greenough	GS GR HC
7. Logs Contest logs to be set out on one side of a quas below:	uarto or foolscap sheet	with columns headed

Time	Call	RST	RST	Shire	Shire	Points
Z Claimed	Wkd	Out	In	Letters	Multiplier	
10.45	VK6-	59MV	59	PD	1	5
11.05	VK6-	56MV	56	R8	1	5
11.10	VK3—	55MV	55001	-	-	2
11.20	VK6-	59MV	59	MV	1	5
			Totale -	9	17	

Example · Final Score(south of 26th parallel) = 3 x 17 x 2 ÷ 102 points

(north of 26th parallel) = 3 x 17 x 2 x 13 = 132.6 points. Column 7 to be totalled at the foot of each page, and the running totals brought forward.

The last page to contain the following summary: Total number points scored, input power, equipment and antennas used, along with comments on the contest in general, SWL participants score as above using the outgoing TX score. All logs to be addressed to the WAA Contest Committee, 42 Kennedy Street, Melville WA

6156 and posted so as to reach us not later than 9 October for both contests. The results for all contests will be published in the December issue of AR.

58.	Kalamunda
59.	Kalgoorlie
60. 61.	Katanning Kellerberrin
62.	Kent
63.	Kojonup Kondinia
64.	Kondinin
65. 66.	Koorda Kulin
67.	Kwinana
68.	Lake Brace
69.	Lawarton
70.	Leonora
71.	Mandurah Manjimup
73.	Meekatharra
74	Metville
75. 76.	Menzies Merradin
77	Mingenew
78.	Moora
79.	Morowa
80.	Mosman Mukinbudin
81. 82.	Mullewa
83.	Mundaring
84.	Murrhitan
85. 86.	Murray Mt Moonet
87.	Mt Magnet Mt Marshall
67. 88.	Nannup
89.	Narembeen
90.	Narrogin Narrogin Town
92.	Nedlands
93.	Northam
94.	Northam Town
95.	Northampton Nungadin
97	Peppermint Grove
98.	Parenjori
99.	Perth
100.	Pingelly Plantagenet
102.	Port Hedland
	Qualrading
104. 105.	Ravensthorpe
106.	Rockingham Roebourne
107.	Sandstone
108.	Serpentine/Jarrahdale
109.	Shark Bay
111	South Perth Stirling
112.	Sublaco
	Swan
114.	Tambellup
116.	Tammin Three Springs
117	Toodyay
118.	Trayping
119. 120.	Upper Gascoyne Victoria Plains
121	Wagin
122. 123.	Wandering.
123	Wanneroo Waroona
124	Wardona Wast Arthur
125. 126.	Wastonia
127	West Pilbara
128. 129.	Wickepin
130.	Willena Williams
131	WongaryBallidu
132	Woodantilling
133.	Wyalkatchem
134. 135.	Wyndham East Kimberley West Kimberley
400	Valence

136. Yalgoo

137, Yilgam 138 York

1N

KA

KL

KG KN

KT

KP

KD KO

KII

K₩

LG

LVA MARKA MA

RM

RB SS SJ

SB SP ST

SU

TP TM TS TY TG UG VP WIN WID WID

WA WA WS WP WI WU

WL WB WG WY WE YO

YN

GM GS GR

VHF/UHF - An expanding World

Eric Jamieson VK5LP PO Box 169, Meningie 5264

All times are UTC

Six Metres in Australia

GI VK3AUI worked a few interesting stations recently, they included on 759 K73-81, KC6RR and Jas, 26/3- C21BR, 27/3-3D2AG, 30/3: XEIGE, 3D2AG, 8/4- Z13TY, 1464- POSDR, X32BB, 3D2AG, 8/4- Z13TY, 1464- POSDR, 15/4- XEIGE, 3D2AG, XEIABA, 3D2PO; 16/4-NGCW, KGSTI, WA6DPX; 20/4- XEIGE, 22/4-3D2AG, 25/4-3D2AG, XEIGE, 26/4- XEIGE, XEIGRR, 27/4- K6FV/b, V73-4Tb, 3/5-Z13TY,

The month of May has been relatively quiet JAs were rarely heard here at Meningle, and little to report between 38 and 50MHz. The same report comes from Adelaide and from VK5BC at Berri. However, there were a few contacts that should have been included last month. Jack T30IH had 108 6m contacts to VK from South Tarawa over a four-week period ending early April. The lucky recipient of the only contact to VK5 was Roper VK5NY at 2250 on 24/3 A message from Steve VK3OT says lack will visit T30 again in August and honefully those who heard him last time, but could not get through the ORM, will be more succesuful, OSL to Jack Haden, PO Box 299, Ryde, NSW 2112.

Last month I reported VK3OT as having worked 7Q7XX, but this second-hand report should have been checked by me as it is apparently not so - sorry Steve. However, 7Q7XX is QRV on six metres with 50 watts and a four-element Yagi and has been worked extensively by overseas stations.

John VK4ZJB has received his QSL from KC6RR and suggests others will receive theirs in due course, but it may take time as KC6RR was reported having made 28,000 contacts during his DXpedition!

Clarry VKS/L said he missed a few opportunities to work Europe by not noting the signs, but on 8/2 at 07/40 he heard VK8/GF working Y13/ZF, so waited and worked his first Europeans, OZ1LO at 0825, 58/FIPE at 1151 and ONKS/TA 1153 after which propagation swung back to JAs. Clarry said the gong was tough with his 20 wasts and fiveelement Yagu at 20 feet, but he enjoyed the experience.

The VK2QF Report

Neville VK2OF has sent an interesting report, and for those of you who have wondered what he has worked, the following should tell you. Neville says six metres has yielded some exciting DX during the past eight months, particularly from Europe and the South Pacific New Short Path Record. For this contact with Joel CU3/N64MG on 27/ 11/91, VR2QF now holds the Australian 50MHz: record with a distance of 19251.3km. That's really pushing out the DX finniless, and the distance will not be easy to better, as there is not a lot of global space left beyond that distance.

New countries in bold print. 13/1/92-DETET. 26/10 [Joja othesed IK. 28'z 1928A, IK.2GSO, VUSZV., IK.1EGC, VUSZV., OZZVV., OUSSA, IR.1917, O142GC, OHZT, O142GC, OHZT, OZZIBVW, ON-MANT, ON-MGG, PA3VST and many others. 11/2: TIZINA, TIZILL 12/2: YUSZV. YUSZV. 5/3: KGOK. VUSZW. 5/4: VUSZV. 5/3: KGOK. VESPER 8/3 V73AT, VSGBG, KGORR. 9/3- ADZ. CZ1BR 22/3: SDZAG, FOXDR. RGCYX, KGSTL. ZZYA. 102AG. SOVER. RGCYX, KGSTL.

1/4 WGRV/HRO- this was Jimit first QSO from HRO. 5/4 WGRV/HRO - this was Jimit first QSO from HRO. 5/4 WGRV/HRO - 3024G 7/4 ZIZTYY on early Es at 1929. 13/4 WSSPR 1, 3/4 WSSPR 1, 3/2 WSSPR 1, 3/2 WSSPR 1, 3/2 WSSPR 1, 3/2 WSSPR 1, 3/4 WSSPR 1, 3/2 WSSPR 1, 3/4 WSSPR 2, 3/4 WSSP

It seems the DX targely disappeared in early May at VLXQF as it did in most of the country, Neville said he had been looking for XSTFPV but was not very hopeful as the F2 seems to have moved that Joet, whom he worked as also mentioned that Joet, whom he worked as abon mentioned that Joet, whom he worked as abon mentioned transplant I am sure all simuteurs will join with me in withing Joel a successful operation and a speechy recovery.

ille dietres trom Aussia

A report from Yoshi JAIUT countery of Brenda VKSRT yieve Setals of the fin propgation test of 17-23 April from Khaharovik CRy, eastern Bussia, with the cellsigns of RDXC22 and UZDXCWW Bisch were club stasions and there were 15 operation with assistance from JAIUT and JHMBUC. The stations are from JAIUT and JHMBUC. The stations 50-115 using SSB and CW. They used an FT-655, TS668S, IC-551, HB9CV and a six-element Yagi.

The propagation test was promoted by the

Friendship Amateur Radio Society, Khabarovsk, and carried out with support from the Khabarovsk Umon of Friendship Society and the Radio Sport Club KAMIFUSEN Japan, with JASRMR and JAOBEE

She Metre Mews from the U.S.

Khabarovsk.

Grenada James Jangdon 137AE is active from this island: OSL to James of the Philatelic Dept, Post Office, Sauters, Grenada, Kuwait Don 9K2WR and Boh 9K2ZR shared the same rig when making their first contacts at the end of March. By 20 March they had worked more than 25 countries. Bob 9K2ZR reports VK8RH is organising a CW beacon for 9K2 - frequency 50.041.5, callsign 9K2SIX, and planned to be on 24 hours. Permit to operate is now awaited. Dominican Republic HISA was activated by Akiso Nagi IASDOH until the end of March. OSL to his home address of Box 73. Ishii Tokushima, 779-32, Japan, Eire OSL for E12EPB is John Edmundson, Drumbuoy, Lifford, Co. Donegal, Eire.

St Helena Chuck ZD7CRC is now on the island and ready to go on six metres His direct address is Chuck Chalmers ZD7CRC. Box 126. St Helena, South Atlantic Ocean, However, as there is no airstrip on the island, mail by sea can take a considerable time! DXpedition to UA2 The expedition to UA2 by Mike UL7GCC and Peter PA3EUI will operate from mid-July until sometime in August. The callsign is expected to be 41.2FM and the first grid locator probably KO04. No OSLs via bureau, but direct only to Peter vd Woude, Sparrendal 610, 3142LT Maassluis, Netherlands Turkey Fric FIRK commenced his firm operations from Turkey on 23/4 using the callsign TA/ F1JKK QSL route appears to be Antoine F6FNU

Contrary to what one might have expected, April was comparatively quest in the UK Ted Collins GHUPS reports satisfacts worked or heard included ZSGML, ZSSM, YSTMF, ZSGM, USSAM, YSTMF, ZSGM, ZSSM, ZS

being nine countries

Geoff GHICD reports the ODS Glebanop. beacon on 90 078 or an unto some problems, but these have now been restlifted. On 1244 he worked 7988R 1879 for a G [first and country number 121. Later the station was \$50 on SSR, 1574 News that TVIABE (Genin) had worked Mails and southern France 1774 1110 AZIZ at the type of the station of the station of the bear of the station of the station of the the size day on 2.05 8 MI into Europe. Geoff confirmation of the station of the station of the the size day on 2.05 8 MI into Europe. Geoff confirmation of the station of the size of the size of the station of the work of the station of the size of the station of the size of siz

In my May 1952 notes I commented that the 50 stations worked in a day from the UK/ Jersey area on 432MHz seemed an awful lot of stations, but Geoff sausers me it was no misprint - there is much activity on that band in turnope, also widespread use of 1950MHz as well. It would seem then, that no matter when they rum on the righ there will always be have tited contacts we always and the part of the contact of the contact of the part of the contact was always to the contact with a state of the part of the contact was always to the contact was always to the contact was always to provide the contact was always to the contact was always the contact was always to the contact was always the contact the con

The UK Six Metre Group

This group, of which I am now a member, is celebrating its 16th birthday. The group issues a quarterly bullent; issue 3 for April runs to 52 pages, and included are loss of snippets of information relating to 6m activity and proposed activity on a world-wide basis. The following selections should be noted by you.

At the moment 6m operation from Monaco is strictly forbidden, so any amateur claiming to be operating from there is doing so illegally. Attempts are being made to reverse this situation. Lebanon ODSSK came on at the end of January. Samir runs 10 wates to a 1/4 wave vertical but has been widely heard in the UK. It is hoped a five-element beam will be constructed soon. Switzerland Swiss stations are permitted to operate only in non-TV hours, usually 0000 to 0500 UTC. which is not very helpful. Swiss authorities will decide at the end of 1992 the fature of the 6m band Brunel Peter V85PB will be at Brunei for three years Greenland OX3CS and OX3LK are permanent residents and keen to make contacts. OX3LX is likely to be active during the northern summer, probably until 25/9, running 50 watts and a four-element beam. Tanzania 5H3RA is on six from square KI93 and will be there until spring 1993.

ANDs and will be there usual spring; 1993.

Batonia ISSNC, ESSPC and ISSCQPI appear
to be the only for stations equipped for IX
working. Gustermala Paul KAPAKI as seeking
a /TGG permit, but this may take six months.
CPPRUS GOKOM (ex ZCMMC) hopes to be
QRV as ZCMMK for a couple of weeks at the
end of August, and later to sign as 59th. In
October/November Adrian will activate VPB
CRIBIATION of ADD COUNTY OF THE ADD COUNTY OF

lalands KP2A is the only operator at present on six from there, ad is usually on daily between 1200 and 1600. John specifically requests that 6m operators call him only if they need him for a new country. Ceets SVIDH recently reported that a 6m beacon was planned for Crete and that permits may be issued for operation as SVS and SV9.

Snain it appears one-year permits could be available to stations fulfilling rather strinpent criteria, eo he a naid-un member of a local or international organisation; have had a full Class A licence for at least five years. during the past 10 years applicants must have participated in at least five international five national VHF/UHF competitions: no sanctions against the licensee in the past 10 years: the applicant must give details of places of operation, equipment used and what technical studies they wish to carry out and at the end of the year, a log with observations of their activities must be submitted to enable consideration of a further one year's extension! So there!

Poland Despite all the rumours there are still no firm indications there will be any early operating from 5P - this the latest news from SP4TKX. Trinidad Island - Natel DX Group is planning a DXpedition for eight weeks from early October 1992 and using the call of Pr0T. Finally, 7858 from Lesotho is now on six, as also is 221AFR from Zimbabwe. CIQTY and CXPDK are new stations on from Unsusuw.

Repeat Contacts

Tenzanie - Maza 5H3RA in KI93 warms stations he does not like to exchange grid squares or make repeat contacts, or be helped when a ORP station is calling him: so, bewarel I note the UK Six Metre Group magazine carries a few comments about stations who repeatedly work DX stations. ZP6CW makes a plea for no more repeat contacts from stations who have already worked him. The question is being asked in the UK why UL7GCC needs to be worked three times a week, and the same two TU stations each time they appear on the band, apparently by the same stations. KP2A does not want any repeat contacts. A number of US operators are now looking for less powerful and more distant VK stations than those regularly available from the east coast of Australia, in particular looking to Western Australia

western industries who plen is circulating to sould apply to have leavely worked a station, must you do it again and again, to possibly exclude someone who has not worked the DX station? However, I must add what should you do if a DX station is repeatedly calling CQ and not receiving replies? Operations who have already worked that station could arrely be excused for giving a quick call and stating, any. "Feet, you are still 50 here in britishmen?" as the case to be a station of the country of th

the air for a longer period. All in all, one needs to weigh the consequences of calling again, as there will be times when it can be justified it's a world-wide problem and one where there are no simple answers.

The time is drawing near when one or more

VK assions may achieve DXCC on an netrost during Cycle 22. Ker years ago this would have been considered virtually impossible due to our geographic position on the globe. Much will depend upon whether the present incorrection and the product and the produce a surprise or two. Who knows? As a matter of interest the May 1992 issue of the AARL DXCC Countries Earls hows there are the product as the product of th

DXCC now being a consideration, a degree of contents has centred on the position of New Guinea in our total of countries onlimed. As a result of enquiries to me, I contacted the ARRL DXCC desk for an opinion and, as this has now arrived, the following is the official response, with some elaboration from me to give a better understanding.

Originally. New Guines was divided into three countries: Dutch New Guinea to the west which, at the moment, is not our concem. The eastern portion was divided into two countries, the northern portion called the Territory of New guines, with its dividing line meeting the coast at a point between Dona and Cape Ward Hunt. It included such coastal towns/settlements as Lae, Madang, Wewak etc. The southern portion was called Papua or Papua Territory, and included Port Moresby. Milne Bay, Buna etc. Up until 15 September 1975, for ARRL DXCC purposes, each was considered a country in its own right. From 16 September 1975 the two countries became Papus New Guines - same land, but considered a new country with a new name.

Therefore, up until 15/97/5, if you worked someone in Lae you had one country, and another if you worked into Port Moresby. On and after 16/9/75, if you worked a station in Port Moresby or anywhere else in the amalgamated country, you scored a further country, therefore a possible total of three countries. The May 1992 ARRL DXCC list confirmed the above situation.

The above should set some readers scouing durough their QSL cards However, before I socept any claims for the Six Metre Standings List I would like to penuse the actual card or a photocopy of the card to enable me to decide if your claim can be supported geographically.

On Higher Bands

Ron VK3AFW says he continues to work Andrew VK7XR most mornings on 144 1 CW with readable signals. Andrew reported on tropo opening to VK3 in April, and on 25/4 he heard a brief opening to VK4 on two metres and copied several repeaters, but no contacts

were made.

On 9/5 from 0700, auroral activity was noted in VK3 on both six and two metres. Around midnight local time Norm WSBUT worked VK72MF and several other stations on six metres, and VK3ELV in Wangaratta and VK72MF in Hobart on two metres SSB.

VK3AZY and VK3DUQ were involved.
On 16/5, Ian VK1BG worked Phil VK3ELV at Wangaratt on 1296 at 5x4 both ways, for a distance of about 270km over the Great Divide at one of its highest points. This contact save Ian his fourth VK3 on 1296. Contacts

were also made on 144 and 432MHz. All these contacts were via aircraft enhancement. Others to use aircraft enhancement have been Eddie VK1VP to John VK3ZJC and Aric VK3AMZ. Lyle VK2BE has also worked

VK3ZJC.

Two thoughts for the month: Laughter is the sum that drives winter from the human face and With a good hand of credit cards, it's easy to go for broke - and make it. Till next time - 73 from The Voice by the Lake.

The program starts with Ross' copyright

notice with 'Press any key to continue', fol-

lowed by a blank screen with the status line at

the top giving "Last S/N: 0. Press ALT H for

help. Speed. 25°, and pressing Alt-H gives a

screen which has all the controls explained. I loaded some Punction key memories with

3 by 3CQ calls, my callsign, some serial number

formats and repeats to see how they all worked,

sn't).

Commonly used punctuation is provided, such as question mark, comma, full-stop and

- slash, with special characters of - (hyphen) sends BT,
- = (equals) sends AR
- \ (back-slash) sends BK + (plus) sends SK
- : (semi-colon) sends KN

I would have liked to have seen a few extras in the special character department such as \$ @ & %! etc, but n is difficult to find someone who knows some of those more obscure characters.

Ross has given me permission to distribute the program, so if you want a copy you can either send me your formatted disk with return post and packaging, or just \$5 and your format requirement of 360kB or 1.2mB disk and I will supply the disk, p&p etc.

I am sorry if you do not have a computer

and find all this talk of programs and such boring. I guess it is something we all need to adjust to and that is the main reason I am involved in computers - to try to stay one jump ahead of my kidds 'But also it is such a large and varied subject that I am glad I am not being left too far behind the times.

Does anyone know the official Morse characters for some of the obscure characters mentioned above?


I think it is generally agreed amongst amateurs that the exclamation mark should be --- •. (OE), but did you know the following?

colon ---- • • • (OS)
spostrophe • --- • (IN)
brackets - • (KK)
(left ---- band bracket used to be -- • ---

 (KN)) underline (UK) understood * * * - * (SN) semi- colon- · - · - · (KR) quotes (RR) multiplication sign CXD dollar sign ***- **-(SX) paragraph .- .- . . (AL)

Correspondence and argument on the above subject will be enthusiastically entered into.

73, Gil VK3CQ



Pounding Brass

Gilbert Griffith VK3CQ - 7 Church St Bright 3741

This month I would like to feature some Morse code software which was sent to me by Ross Keatinge ZLIBNV in May. Gary Bold reviewed Ross' program in April for his column in Break-In (tin New Zealand official journal) and Ross posted me the program, which I have been trying out.

You may remember the list program I tried out was YK3VR Geoff's BD Contents program. Well, this one can be used for contesting as well, but does not give the printous and cover sheet as in the BD Contest program. It is very simple to operate but still has the following features:

*A memory for each F-key (to F10)

*A repeat character

*Automatic serial number incrementing for ontesting.

*Serial number resetting and alteration with page up/down keys *Speed change while transmitting with up/

down arrow
*Status line giving last serial number and

speed
"Help screen which does not interfere with

*And the following 'hot' keys:

*And the following 'hot' keys: Alt-D toggie colour/mono display

Alt-H Help screen

Alt-N Setup IO Port Alt-P Pause on/off

Alt-S Speaker on/off

Alt-W Save messages, speed and serial to disk

Alt X Exit to DOS ESC Stop sending and clear the buffer.

ESO. Stop sensing and creat use outset. The CW for the transmitter comes out of the parallel printer port on your computer, and the interface is very simple for modern rigs with positive keying (see figure 1). The interface fits miside a DB25 connector shell and is easily assembled from one's Junk box by anyone with a soldering iron.

and found it was possible to keep pressing Fkeys until the screen is full, at which time you started to lose messages as you tried to enter them. But a full screen represents a buffer of 1800 characters, and I make that about 10 minutes of buffer to the page at 30 words per minute! I entered up to 1800 characters in one F-key memory, but found I had wiped a previously recorded F-key, so I eventually settled for recording 10 P-key memories with 400 characters each, and yet I did not find the real limit of these memories. It may be possible to record 1800 characters in each F-key memory and save them to disk without losing anything. To enter text into a F-key memory you press Alt F1 and the status line tells you that you are currently entering text to message number 1, entering text terminates when you press enter. You can enter the hash sign (#) last and the message will repeat, or enter the

Amateur Radio, July 1992

AMSAT Australia

Bill Magnusson VK3JT - Packet VK3JT @ VK3BBS

National Co-ordinator Graham Ratcliff VK5AGR

Please take note of the AMSAT information

nets: AMBAT AUSTRALIA OFF

Control station VK5AGR Check-ins commence at 0845z on Sunday

nights Bulletin commences at 0900z

Frequencies 3.685MHz or 7.064MHz. At present 7.064MHz is used.

AMSAT SW Pacific net: 2200z Saturday on 14.282MHz.

Experienced satellite users and newcomers alike are welcome on the nets. A large body of experience is on hand to answer queries. Listen to the WIA Divisional broad-

casts for regular AMSAT information. AMSAT Australia Newsletter and Compu-

ter Software: Satellite users, whether experienced or newcomers, will benefit by subscribing to the AMSAT Australia newsletter and software service. The newsletter is published monthly by

Graham VK5AGR. Subscription is \$20 payable to AMSAT Australia, addressed as follows

AMSAT Australia GPO Box 2141 Adelaide 5001

The newsletter provides up-to-date information on all current and planned satellite activity. Graham also provides a first class software service for satellite users. New soft-

ware is reviewed regularly in the newsletter. KITSAT-A

Last month I outlined some details of this new satellite. More information is coming to hand as the launch date approaches.

KTTSAT-A will transmit and receive 9600bps FSK signals using the AX.25 protocol. The downlink will also contain telemetry, experimental data, camera images and store and forward data. This will account for about 95 per cent of downlink time. The remaining five per cent will be taken up with DSPF (digital signal processing equipment). This will take the form of digital voice broadcasts and highspeed modulation experiments.

The satellite will be controlled from Korea The control station call is HLOENI. The University of Surrey team will be acting in an advisory capacity

KITSAT-A user frequencies: There will be two uplink frequencies. The primary uplink frequency will be 145 850MHz. The secondary uplink frequency will be 145.900MHz. There will be one downlink frequency. It will be 435.175MHz. These frequencies have been chosen after long deliberation to be least likely to cause interference to existing amateur radio satellites. (Unlike a couple of other recent examples).

The launch is planned for 23 July 1992. It will travel into orbit with another (commercial) micro-satellite and the main navload. which is called Topex/Poseidon, an oceanographic researcher. As I mentioned last month, the orbit will be very interesting and unique for an amateur radio satellite. It will be rather like a highly inclined version of the old Oscar-7 with long access times and slow transmit across the sky The 66-degree inclination will take it way south of VK on occasions, giving good opportunities for VKO contacts. I won-

der if anyone's geared up down there? No doubt KITSAT-A will be allocated an oscar number when it's safely in orbit and fully commissioned. Watch your local packet BBS for details as the launch date approaches.

Oscar-10 Keps

It looks like the approaches made to NASA. by Amsat-NA have been successful in reincluding Oscar-10 in the two-line keps list. The last set I downloaded, which were marked day 144, included a set for Oscar-10. Let's hone this continues as Oscar-10 is still a very workable satellite.

Oscar-13

Operating conditions for southern hemisohere stations should slowly improve over the next couple of years. The apogee is moving south at the rate of about 0.01 degree per day after a lengthy stay in the northern hemisphere. This rate will increase a bit as it comes further south. It is currently about 50 degrees north of the equator. For stations in VK6 there should already be some quite good windows into Europe, and this will gradually extend east over the next couple of years as the apagee moves further south. So it's time to dust off all that gear, reset the rotators and make the most of it. Remember, we've not only another three or four years before Oscar-13 re-enters, so we'll probably never see it back over the equator. But, during the time it has left, it should provide some good longdistance communications in the southern hemsphere.

Sall Barn to the Moon

"In 1492 Columbus sailed the ocean blue" And, to commemorate this epoch-making event, another rather amazing event is to take place in 1994. Originally proposed to start in 1992, this race has attracted participants from Europe, USA and Japan. The idea is to design and build a spacecraft using 'solar sails' for propulsion and engage in a sailing race to the moon. The craft will be launched on an Arianne rocket. They will make use of the solar energy and their sails will be made like the radiometers we are all familiar with, spinning around in the sunlight on our science classroom window-sills. Their direction will be controlled by radio command through yaw, pitch and roll control surfaces on the sails. The first craft to send back a picture of the other side of the moon will be the winner. The combined Amsat-NA and World Space Foundation spacecraft will carry a colour camera similar to the one on Webersat Oscar-18. It will carry a beacon on 145.825MHz and a microwave communication package. If it is successful in reaching the moon it will have the capacity to go on to a close encounter with Mars some time later. This is pretty exclting, and will no doubt create gulte a bit of interest as the launch time approaches.

Satel 1.	Re Activity for	January to	March 19	192			b Arnold VK3ZBB
	llowing launching	announcem	ents have be	en received.			
Intl No 1992 -	Satellite	Date	Launch Nation	Period min	Apg lom	Prg km	Inc deg
005A 005B 005C 006A	COSMOS 2177 COSMOS 2178 COSMOS 2179 11SA-78	Jan 29 Jan 29 Jan 29 Feb 10	CIS CIS CIS USA	11h16m 11h16m 11h16m	19150 19150 19150		64 5 64 5 64 5
007A 008a 009a 010a 010b 011a 012a 013a	JERS-1 COSMOS 2180 USA-79 SPRBIRD ARABSAT-1C MOLNIYA COSMOS 2181 GALAXY 5	Feb 11 Feb 17 FEB 23 FEB 26 Feb 26 Mar 04 Mar 09 Mar 14	Japan CIS USA ESA ESA CIS CIS USA	96.0 104.9 714 7 631.3 632.4 11h42m 105.0 653.9	580 1028 20318 35776 35832 38998 1027 36135	558 980 19913 222 222 629 994 1092	97 7 82.9 54 7 7 0 7 0 62.9 82.9 19 6

014a	SOYUZ TM-14	Mar 17 CIS
1963-047B	ATLAS/CENTAUR	Mar 20
1971-096A	EXPLORER 45	Jan 10
1975-033A	ARIABAT	Feb 11
1976-085B	COSMOS 851	Mar 22
1977-015A	COSMOS 895	Mar 22
1978-024A	MOLNIYA 1-39	Mar 09
1978-072A	MOLNIYA 1-41	Feb 08
1980-051A	METEOR 1-30	Mar 01
1990-038A	COSMOS 2075	Feb 20
1990-058A	GAMMA	Feb 28
1991-049A	COSMOS 2153	Mar 13
1991-051E	MICROSAT-5	Jan 24
1991-085A	COSMOS 2174	Jan 30
1992-001A	COSMOS 2175	Mar 20
1992-002A	STS-42	Jan 30
1992-004A	PROGRESS M-11	Mar 13
1992-014B	SOYUZ TM-14	Mar 19

E. Malles

1992-014A SOYUZ TM-14 carried three cosmonauts and docked with the MIR space station on 19 March 1992

Bob Arnold VK3ZBB

Education Notes

Brenda Edmonds VK3KT - WIA Federal Education Co-ordinator PO Box 445 Blackburn 3130

I have recently had the opportunity to examine a copy of the 1991 Proceedings of The ARRI National Educational Workshop. This is the third year in which amateur radio recruiters, educators and others have been asked to submit papers for publication in the hope of assisting others to increase public awareness of amateur radio, teach amateur radio classes. integrate amateur radio into the formal classroom, or encourage and support newly li-

censed amateurs. The 'booklet' runs to 254 A4 pages Almost all of the 40+ contributions are from licensed amateurs. Many of them are 'How I do/did it' type, setting out in more or less detail the reasons for the activity organised, the preparations, processes and results, some evaluation and further suggestions. They range from a sample submission for funding to complete lesson plans or dissertations on the application of amateur radio to the Earth Science classroom, the Elementary School Guidance and Counselling Program or teacher training. Each paper is published unedited, so there is a wide range of styles and formats as well as varying levels of technical detail

The most impressive part is the obvious enthusiasm and dedication of all the writers. Although admitting their own personal preferences, many of them have taken a larger view in the interests of encouraging a new generation of amateur operators, whether in primary school or among sensor citizens. While acknowledging that the success rate in any

group may not be more than five per cent overall, and that the attention span of teenagers is traditionally very limited, the programs

have all 'worked' to some extent. (This is not surprising, I suppose Would you write up one that was a miserable failure?) The authors have some to a lot of trouble to make their contributions easy to follow, with samples of publicity material. Individual class worksheets and a host of useful ideas. And it has all been produced specifically to allow others to evaluate the ideas and use them, if appropriate

This is not a book I would say should be in every amateur's library, but it would be very good value for anyone wishing to introduce amateur radio to a group of students, or looking for ideas for new approaches. Divisions and clubs would find useful publicity suggestions, and many of the bright ideas will appeal to course teachers. (Why didn't I think of some of these years ago?) There is little effort required to translate the American situation to the Australian. As well, much of it makes entertaining light reading, mostly in short articles which can be read in only a few minutes

The ARRI and the contributors are to be congratulated on this initiative

I would very much like to know what is happening to amateur radio in Australian schools. Please drop me a note if you are running a school station or classes, or if there is a chance of integrating radio into classes in your school. Perhaps some of the ARRL Workshop papers could encourage more school activity.

My inspection copy from Stewart Electronics. RRP \$24.00. This will be available from Divisional bookshops shortly.

FTAC Notes

John Martin VK3ZJC FTAC Chairman

Records

Moss Kucerans VICTIK has broken his VICT shortpath record on six metres by working PAOLSB on 8/2/92. The contact was CW and the distance is 17.053km.

John Bisgrove VK4KK (also better known to some of us at VK4ZIB) made two new VK4 6m records within the space of six minutes on 15 February. The first was a contact with Ken

Willis GSVR (16.416km), and the second was to Paul Simons G4CCS (16.515km).

Date Base

The time for the next Callbook is getting very close, so any corrections or additions to the beacon and repeater lists would be much appreciated as soon as possible!

Sign up a new WIA member today

ALARA

Jenny Adams VK3MDR -- 70 Kanoaroo Ground Rd. Wattle Glen 3096

Greetings to all once again. In May we had our annual general meeting and there have been a few changes. Firstly, a thank-you is in order to all who have retired from their positions, especially Bron VK3DYF who, after editing our newsletters for six years, takes on the job of secretary, Robyn VK3ENX has taken on the job of publicity, and I hope she enjoys the task as much as I have. Dorothy VK2DDB is our new editor. Congratulations to all those re-elected in their present positions - President Maria VK5BMT, Immediate Past President Jenny VK5ANW, Vice Presidents Christine VK5CTY and Judy VK3NYL, Treasurer/Souvenir Custodian Val VK4VR, Minute Secretary

VK3VAN, Historian/Contest Manager Marilyn VK3DMS, Librarian Kim VK3CL and Sponsorship Secretary Poppy VK6YF. Last, but not least, our State Representatives: VK1/2 Dorothy VK2DDB, VK3 Bron VK3DYF, VK4 Margaret VK4AOE, VK5/8 Meg VK5AOV, VK6 Poppy VK6YF and VK7 Helene VK7HD. In July we celebrate our 17th birthday, with

many states celebrating with a luncheon. Set aside a few hours on the fourth Saturday in July for our ALARA Birthday Activity Day, 0800 to 1200 on 3.588, 14.288, 21.188, 28.588 and 28.688. Hopefully the previous editor's rig will hear some activity this year.

Cheers for now.



Pictured on Wednesday 9 October 1991, L to R: Christine VKSCTY (alster of Maxi), Maxi DJ4YL, Irene Wilson, Beelse VKSYL and Mar VKSBMT at a coffee house in the City of Adelaide.

Spotlight on SWLing

Robin Harwood VK7RH

As I write this, the situation in the former Yugoslavian republics has worsened. The United Nations has imposed tough economic and political sanctions on Serbia and Montenegro, to try to bring the senseless slaughter and misery to an end. So far there has not been any success. Although the shortwave senders of Radio Yugoslavia from Belgrade are situated in Bosnia-Herzgovina, it does not appear to have made any appreci-

Tell the advertiser vou saw it in the WIA Amateur Radio Magazine!

able difference. Presumably they must be located in Serblan-controlled areas

Croatia has now commenced broadcasting on shortwave and has been heard quite well in Australia Listen on 9830 or on 21480kHz around 0600z for Radio Zagreb in Croatian. At approximately 0605z, there is a brief English news bulletin. Overseas DX sources report that these short English newscasts are heard at 0603, 0803, 1203, 1603 and 2103, A European monitor also stated that Radio Zagreb has an English newscast at 2220z on 6210. I have found 21480 provides the best signal, as it is on 24 hours a day, 9830 is fair, despite being a clear channel, and I suspect it is a lowpowered sender. Belgrade is still being heard at 1130z in English on 21605, preceded by a Serbian program.

The Southern Cross DX Club Inc. which is based in Adelaide, has produced a receiver guide. This non-technical guide is a review of new and second-hand receivers currently available in Australia. It has been written and compiled by Stephen Newlyn VK5VKA This nine-page pamphlet reviews most models, such as the Kenwood, Icom, Panasonic, Yaesu, Grundig and Sangean etc. It is well written. but isn't a technical review. It costs \$2.50 and is available from the Southern Cross DX Club Inc. GPO Box 1487, Adelaide, SA 5001. This month, as you are all no doubt aware,

the 1992 Olympics commences in Barcleona, Spain. There is going to be an extensive coverage on shortwave from most of the international and national stations. The Spanish Foreign Radio in Madrid has been giving extensive coverage of the trials and difficulties the Spanish authorities have been encountering in organising these Games Incidentally, the new title of the former Spanish Foreign Radio is the External Service of the Spanish National Radio. A 24-hour Spanish World Service will be operational by now. I'm hearing it best at 0600z on 7105

Well, that is all the news for this month Until next time, the very best of 73 and good listening.

Repeater Link

Will Mc Ghie 21 Waterloo Cr Lesmurdie 6076

On-Alt Audio

The four diagrams as shown are real samples of amateur audio as seen on two metres FM. The vertical scale is deviation in lefts. The dotted lines show + and - SkHz, and + and - 10kHz. The horizontal scale is time. These audio samples are input signals to a repeater. If the repeater has no audio processing, the output audio from the repeater will look and sound the same.

sound the same. Figure 1 is the right peak deviation but with too much mic gain. Figure 2 is close enough to being correct. A peak deviation of Skift with the right mic gain (compression). Figure 3 has an unknown peak deviation with too little mic gain Figure 4 has too much deviation, but the right mic gain for mich mic gain figure 4 has too much deviation, but the right mic gain.

right mic gain.

There are many combinations of the four samples as shown, but they are representable of the wide variation in ansateur and oil signals. The problem for the epicare designer is to reach under the control of the processing to one out the differences. Simple avide processing can easily restrict the post device particular control of the processing to one out the differences. Simple avide processing can easily restrict the post device a simple variation of the processing to one out the differences. Simple avide processing can easily restrict the post device and the processing can easily avide and the processing can easily avide avide to the processing the proce

To help relate the diagrams to what these samples sound like, here is a description of

Figure 1 sounds loud, with a loud audio background noise. If mobile, the vehicle's mechanical noise can be heard as loud as the operator's voice. Comments like, "You must be driving a big four-wheel-drive truck with all the windows down' best describes this signal

Figure 2 sounds comfortable, with the right mix of wanted audio and little background audio. An easy-on-the-ears signal.

Figure 3 is hard to understand. Your receive volume control is flat out, and you miss a lot of what is said. There is white noise on the audio, mixed with ignition noise if you are mobile. Chances are the next amateur signal blows you out the window.

Figure 4 is loud, but may be broken up due to the excessive deviation causing the repeater's mute, and/or your mute, to close on voice peaks. This type of audio is confusing, as is sounds strong with no noise, but breaks up.


The difference in audio level between figure 3 and figure 1 or 4, can be 20dB. Yes, 20dB. That is 100 times more audio power. It is little


wonder that some stations blow you out the window while others can't be heard.

It is important to understand that audio levels in an FM system do not relate to RF signal levels. Strong RF signals do not have loud audio simply because they are strong. The single most important adjustment in your FM transmitter for good audio is the mic gain Cornectly set for your voice and operating situation, this control will produce that easyon-the-car sound.

In a future article of 'Repeater Link' I will endeasour to describe the correct setting up of the mire gain and deviation controls. These two controls may appear to do the same thing, but they do not. Results from adjusting them can easily lead you into believing the correct outcome has been achieved, but an understanding of their functions is needed to set up an PM transmitter's audio.

Most FM transceivers produce good audio and never need adjusting, but this is not always the situation. If you receive consistently poor reports of your signal, don't only look at the RF side of things, or blame it on the repeater, it may be your transmitted audio.








FIGURE 2

FIGURE 4

Club Corner

Summerland ARC - Minifest

Sunday 2 August is the date for the Summerland Amateur Radio Club's annual Minifest

Bring and Buy stalls: heaps of treasures awalting discovery; disposals; packet demo; trade display

Maybe a foxhunt or two.

Refreshments available (BBO, tea, coffee drinks etc.

The venue is our clubrooms at Richmond

Hill, via Lismore, commencing at 9.30am. Directions on VK2RIC. VK2RBB or VY2AGH

More information from John (066) 21 933, Ken (066) 24 4771, or Graeme (066) 85 1336. Packet news on VK2EA-2, VK2AGH-

2, or VK2YDN-2, all via VK2RPL-1, 668900. Make a note in your diary now - Sunday 2 August 1992, Minifest

Graeme VK2G1 **Publicity Officer** by this time. On top of the card we read "Besucht das schoene Danzig" (Visit beautiful Danzig), one of the few tourist promotions that were just becoming popular, and which on many of today's OSL cards have given rise to many attractive pictorial renditions. The name of the very omate building does not appear on the card. However, a search of Polish tourist literature led the writer to identify it as the Artus Mansion situated in what is called the Long Market in the middle of Gdansk In late mediaeval times the building was the meeting place of rich merchants, and became a kind of closed club and stock exchange. The internal fittings were completely destroyed by bombing, but the interior has been fully restored by expert craftsmen just to the right of the picture can be seen a fountain. This is called the Neptune fountain and is the most famous one in Poland, Neptune signifying the dependence of the city upon the sea for its prosperity

Bullions's Mode

Much of the history of amateur radio can be gained by the study of the QSL cards of yesteryear. This column is only possible by reference to such cards in the WIA QSL Collection. We think it's worth preserving and for this reason appeal to all amateur radio operators and short wave listeners to give generously to the Collection. (It should be realised, however, that all OSLs are gratefully received whether they be pre-war or post-war). If you would like to help, please contact the writer of this series of articles. All contributions are acknowledged both in AR and by personal letter by the writer, who is the honorary curator of the Collection.

Theolie

The WIA (Vic Div) would like to express its thanks to the following who have kindly donated OSLs to the Collection (Supplementary

Percy VK4CPA Bill ex VK6WY Mike VK6HD Ron VK3OP Stan VK3BSR (ex VK3ASB) Frank VK2OL Owen VK1CC Reg ex VK1RF. Also to the family and friends of the follow-

ing "Silent Keys" (Supplementary list). Russell Edwards VK3CZ Fenton Sanderson VK6TS

> Have you advised the WIA Executive Office of your new callsign? Use the form on the reverse of the Amateur Radio address flysheet

QSLs from the WIA Collection Ken Matchett VK3TI Hon Curator WIA QSI Collection

4 Sunrise Hill Road, Montrose 3765, Ph: (03) 728 5350

Danzig - and what's on that old QSL card? Part II VM4AI This is a slightly older OSL than that of

YM4ZO, and dates from October 1935 The TWR (Tone, strength, readability) code is still being used, although some operators at this time had already started to use the RST system. The operator has crossed out his callsign of YM4AF, thus turning his QSL into a SWL report, his licensed receiving call being DE2796Y When transmitting, the operator, Max

Brandstaedter (who was then living in Hitler Street) used the popular Hartley transmitter in which the anode and grid are connected to opposite ends of a parallel tuned circuit.

Input power was only 30 watts. Note the Nazi symbol of the swastika on Max's card. This became quite a common symbol on German OSL cards from about the mid-1930s, the Nazi Party having won the elections held in Danzig in 1933. The operator is using GMT rather than local time standard, as GMT was becoming increasingly used on the Continent





Xmtr Hartley - unu 30 wts Rovr SG - P Aerial 52 . DX 5 Cant ... 40 Countr. Text - Pse qui 73 fb DX

Qn: Max Brandtstädter Danzig-Oliva, Ad. Hitlerstr. 484 DE - OSO M ATA

Divisional Notes

VK2 Notes

Tim Mills VK2ZTM AGM

Perhaps on the second time. The re-sched uled NSW Division was advised in last month's notes for Sunday 28 hone. It should be over by now. A report in later notes and in VK2WI weekly news.

July Trash & Treasure

This is set down for Sunday afternoon 26 July in the car park at Parramatta. Sellers from 1pm and buyers from 2pm. Good weather was on hand for the May event and saw a very good crowd, perhaps still waiting from the cancelled March event due to doubtful weather Perhaps the next problem is going to be overcrowding, for there was a record number of both sellers and buyers in May. As always, keep an ear on the Divisional broadcasts for details

August Exams

The next exams conducted by the NSW Division will be Sunday afternoon 30 August. Closing date for applications is 13 August. Venue is the library at the Parramatta office. Check page 3 in this AR for means of contact-

ing the Divisional office. AK SMI Late in October this year, the morning VK2WI broadcast will move to a slightly earlier time slot of 10am. There will be no change to the present evening slot from 7.15pm. More details in later notes. A request last month for a replacement base station for 52.525 has been filled. Thank you. A solid state unit is now being crystalled up. The planned 6m repeater for VK2RWI is getting closer now that a transceiver and cavities have been sourced. The transmission on 12 metres will move soon from 24.91 to 24.95MHz. An alternative test may be conducted on 15 metres about 21,17MHz. These secondary transmissions are made when equipment is spare via a standby unit when not required for 80, 40 or 30 metres. The Great Lakes Amateur Radio Club has recently set up its 2m repeater VK2RGL on 7375 to automatically relay both the morning and evening broadcast from VK2WI. This is the 14th repeater used in broadcast presentation. Additional relays are still required in major regions. Club committees should soon receive a newsletter detailing various changes and upgrades scheduled for VK2WI, which may affect aspects of their relay involvement. It is time for the roster for announcers and engineers for the next quarter at VK2WI to be drawn up. Advise the office of unsuitable dates/times from the current crew, or if anybody wishes to join the roster, also contact the office by the usual means.

COL Bureau

Please note recent changes to card handling. Check your club OSL officer for details. collect a sheet from the office, or listen to the neriodic announcements on the broadcasts. Have you registered your card-handling methods with the Bureau, via the office? See card and report in AGM booklet.

VK3 Notes

Barry Wilton VK3XV At last, some good news regarding our reneater sites!

Following the publication of our letter to DC&E in the May edition of this magazine, the Victorian Division Council produced another comprehensive submission which was forwarded to the assistant director. National Parks

and Public Lands Division The final outcome of this matter is most favourable, and the following is an excerpt

from an official letter received from DC&E-"The nature of an organisation and the purpose for which a site is used dictate the policy adopted by the Department in establishing rent. A market rental applies to those tenants who are involved in operational or commercial activities or have exclusive use of a site. However, organisations primarily set up to provide a social, recreational or cultural service to the community, and which have limited means to generate revenue, are charged a nominal rental only.

Given that the Institute is a non-profit organisation established to provide facilities for radio amateurs and generates revenue primarily through members' subscriptions, it is considered that the Institute fits into this latter category and should, therefore, be regarded to be a community tenant for the purpose of rental determination. A copy of the Department's policy relating to community tenants is attached for your information.

The nominal rent charged for community tenants is currently set at \$104 per annum, an amount covering Departmental costs. This amount will be payable for each tenure held. Regional staff have been advised to adjust accounts accordingly

Please note that, where there are any situations where the Institute has entered into a commercial arrangement to sub-let its own facility to another organisation, a market rent would be payable in respect of that site." It would certainly appear that success has must closely monitor the situation as it develons regarding the privatisation of the reneater network utilised by Victorian Government

It is too early to predict the long-term offects of this privatisation policy; however, we will keep you well informed.

WR Wave

Jennifer Warrington VKSANW Council Update

Peter Maddem VKSPRM

Here, as promised, are the rest of the council portfolios and their holders

Bob Allan VKSRIA President DoTC Lisison & SATAC Co-ord John Highman VKSPTH Secretary

Bill Wardrop VK5AWM Treasurer Federal Councillor & Journal Editor

Building Supervisor & Auctioneer Ian Watson VK5KIA Alternate PC, WICEN Director and Publica-

tions Officer

Mark Spooner VK5ACO

Program Organiser & ESC member Rowland Bruce VK5OII

Past President, 5/8 Wave Columnist (and possibly Minutes Secretary) Rob Gunnourie VK5FI

Clubs & Country Members' Representative Chuck Waite VK5CO

Membership Secretary (and possibly Examinations & Education Officer)

Alan Roocroft VK5ZN

OSL BURO Manager

One or two positions were still subject to negotiation at the last meeting when these were announced

And yes, you did read that right, next month's column will be my last. I decided at was time to hand it on to someone else. preferably someone who is still on Council and pearer to the 'heart' of the Division. I am delighted that Rowland has agreed to take it on and keep it going. He proved last year that he is equal to the job. It was pure coincidence. but next month will be exactly 10 years since I started doing it.

Diary Dates

July 28General meeting, 7.45pm at the BGB. As promised last month, here are the Examinations Information Sheets for Remote Area and Special Conditions Examinations. courtesy of Christine Taylor VK5CTY.

Information for Applicants for Amateur Exams Special Conditions Examinations

From January 1992 the amateur examinations will all be conducted under the authority of the WIA Evon Service

In each state there will be a list of official examiners which will be available from DoTC. These examiners will conduct exams at sched-

uled times and places (available from the examiner or the local Division of the WIA) been achieved on this front; however, we All examinations must have two official examiners present at all times.

If, because of religious or work commitments, a candidate cannot attend a scheduled examination they may apply for an examination to be held on a day or at a time that is

Payment for the examination(s) will be at the time of application

The examiner will apply for only the papers required and will arrange the time and place with the candidate when the papers

On the day of the examination the candidate will be able to obtain a provisional mark at the conclusion of the examination. The official mark and any appropriate forms will be forwarded to the candidate from the WIA Evam Service

These results, along with any previously obtained qualifications, must be presented to the Department of Transport and Communication when applying for certificates or station licences Good lucki

Prepared by Christine Taylor VK5CTY.

Remote Areas

From January 1992 the amateur examinations will all be conducted under the authority of the WIA Exam Service

In each state there will be a list of official examiners which will be available from DoTC. These examiners will conduct exams at scheduled times and places (available from the examiner or the local Division of the WIA). Candidates from country areas who attend any of these scheduled examinations may apply for a private examination in their own area

Many of the professional people in the local towns can be authorised to conduct an individual examination. A list of these people is also available from the Divisional Office.

These people may become 'once only' ex-

aminera When the candidates are ready to sit for any of the amateur examinations they should approach one of the people on the list, with this information to explain their request, and ask

for assistance The examiners' applications, along with a covering letter from the candidate listing the examination(s) to be attempted should be sent to the

WIA Exam Service PO Box 300 CAULFIELD 3162

This service will send back all the appropriate information to suide examiners and exатипесь.

Good luck!

Prepared by Christine Taylor VK5CTY.

VK6 Notes

Harry Atkinson VK6WZ

Two well-known VK6 operators are leaving - one to live in VK3, the other to spend about two years travelling Australia. Alan VK6AR will be a resident of Geelong some time this month. He and XYL Shirley will henceforth live close to family in Victoria, perhaps to the chaprin of Telecom! John VK6GII and XYL Hone are off to warmer climes initially, by taking the clockwise route around VK. Plans? To go places and renew friendships and to take at least two years doing it. Good luck to both parties.

Nick VK6ND is settling In well as BCO, and callbacks each week testify to this.

This is the time of year when many amateurs take off for touring ... and enjoy the security and peace of mind engendered by the Australian Travellers' Net on 14MHz, and Ross' 21MHz net for those unable to call in on 20 metres. For new licensees, the ATN operates on 14.116MHz seven days a week at 0300 Zulu, and the VK6DA net can be found on 21.185 seven days a week at 0100 Zulu

The latter net has been welcomed by many travellers, especially those with novice calls, It fills a long-felt want.

2m group from 1948-1950 using MOPAs and Superment receivers

After shifting to Templestowe, he had problems with the broadcast stations over the river from his location and his amateur radio activities were severely restricted. However, his interest in electronics in general did not diminich

He will be greatly mussed by his daughter Carol and her family as well as other relatives and many friends. Allen Crowther VK3SM

Jack (John Henry) Early VESTER A well known and respected member of

both the post office and amateur radio, tack passed away, aged 90, on Sunday 17 May in Port Macquarie Hospital.

tack, who was born in Helensburgh, south of Sydney, was the son of a coal miner. He attended school in Wollongong, leaving at the age of 15 to take up a job at Clifton Post Office. lack passed his Morse test of 20 words per minute in 1918, worked at many post offices in NSW, and finally became Postmaster at Toronto late in 1941. This office was upgraded by the creation of the RAAF base at Rathmines. Jack was a 'top' morse operator, and right up to the time of his death, was an active ham radio operator.

He had close associations with the Westlakes Amateur Radio Club at Teralba as well as the Newcastle Morsecodians. Frank Mike

Clarice Adams VK3UE

Clarice died on 26 May. She was first licensed in 1947 with the callsion VX3VB, and after her husband Stan died in 1977 took over his callsign VK3UE. Clarice was very active on the VK3UE net and made many friends here. interstate and New Zealand. Her cheery voice and interest in people will be sadly missed. A remarkable lady has left us.

Barry Gauntlett VK3IB

Reg Orr VK4CV

It is with an acute sense of loss that I record the passing of Reg Orr in April 1992.

Reg will be sadly missed by his many friends among the amateur radio fratemity and the Royal Flying Doctor Service. Reg was a radio operator in the merchant navy during WW2. After a short stint with DCA, he joined the Queensland section of the RFDS in 1947 He was in his 43rd year of service as State Radio Supervisor when he retired in 1989. I was fortunate enough to be closely associated with him during the last 10 years of his work-

Reg's amateur radio interests lav mainly in VHF, satellites and packet. A man of firm convictions, he called a spade a space, and was much admired for his traditional values. Vale Reg Orr VK4CV.

Nick Watling VK4YI

Silent Keys

Due to increasing space demands obituaries must be no longer than 200 words.

The WIA regrets to announce the recent passing of

AR (Alan)	McKinnon	VK5AM
DJ (Dave)	Richards	VK4UG
R (Reg)	Orr	VK4CV
C (Clarice)	Adams	VK3UE
LL	Adams	VK3OA
R T (Ray)	Pettigrew	VK3DO
A T (Allan)	Bosher	VK2TU
L (Len)	Pollack	VK2NM
J H (Jack)	Early	VK2KQ

mond Thomas Pettigrew VK3DO (ex VK3PE) Ray passed away suddenly on 10 May 1992.

He had been an amateur since 1947 and worked for many years as an industrial electrician, and later at Preston Technical College as a lab assistant in the electrical and communications section until he retired. He was very active as an amateur in the

earlier years, and was a member of the Coburg

Over To You

All letters from members will be considered for publication but must be less than 300 words. The WIA accepts no responsibility for opinions expressed by correspondents.

Suggest, but not Direct

Reading through the IARU Administrative Council's Summary Record, Bandung 1991. 1 came across the following: "Concerning the improper use of the amateur bands". In respect to various other reports of non-amateur operation in amateur bands and amateur satellite bands Mr Owen VK3KI reminded the group that the ITU exists because of an agreement between countries in the form of a convention: that is, in so agreeing, the countries have not surrendered their sovereignty and have not given the ITU authority to function as an international spectrum policeman. and that every country reserves the right to act in accordance with its own best interests as each country may define for itself So, if a country wants to operate a transmit-

ter for broadcasting in the amateur bands, or cares little about the proliferation of transmissions on the 10m band, that's it! Short of imposing economic sanctions or sending a gun-boat, we may just have to learn to live with other users' of the amateur bands 73 Neil Penfold VK6NE

2 Moss Crt

Kingsley WA 6026

Titanic Anniversary Station Success Single-handedly over a period of five days, using phone and Morse code on 80, 40, 20 and 15 metres, I answered hundreds of contacts

and have already sent out the special OSL card. to those operators who replied direct. Those who made contact on the novice bands will have worked VK2MGY: "MGY".

the callsign of the Titanic But the card carries both calls, with a tick against the call worked Among the contacts made were many from old radio pioneers and ship's operators, as well as those who had various connections with the Titanic

Contact was also made with KAIRR the USA Titanic station. Some of the interesting callers included the son of an operator at Cape Race, Newfoundland, who was on duty and heard the Titanic's CQD SOS call on 14 April 1912

Two people, one a still-current VK, were taken aboard the ship by their parents prior to its saling: one of these, when observing the gleaming cooper antenna wires leading to the Marconi room, was bitten by the 'radio bug' at the tender age of eight, and has been hooked

The highlight was perhaps contact with VO1CQD, the operator at Cape Race telegraph station. Historians will remember that onerator Phillips was so husy working Cane Race with private messages from passengers, he ignored the final and crucial ace warning from the Californian This station obtained the use of the suffix COD after it crased to be an accepted distress call.

All operators who OSL'ed direct (or via manager VK2DZF) will have received their cards by 25 May. All other cards will be held until 15 July 1992, after which they will be sent via the NSW Bureau

Ian C Griegs VK2WR 88 Excelsior Ave Castle Hill 2154

BARC Pienic

As a member of the Barossa Amateur Radio Club it was with regret that I read in the 5/8 Wave column in the May issue of AR lenny Warrington's 'attack' on the BARC's Radio Picnic Day which was held on the same day as Walk Against Want, Particularly offensive was the bold type telling 'picnic organisers' to note the date for next year's event

Firstly, the red faces must have been on her behalf because they did not contact us to tell us of the problem. Secondly, I do not feel the WIA should be letting us know of the plans for next year through Amateur Radio magazine. At no stage has Jenny or the WIA had the decency to telephone or write to the BARC advising us of the matter at hand

The BARC will be holding the next Mt Pleasant picnic on 28 March 1993, the same date as the Walk Against Want. This was planned before I read of the Walk Against Want date in the May AR

We are committed to this date as it is the only time Mt Pleasant is available, in fact, the date for the Mt Pleasant Picnic Day is set with the Showerounds committee for quite a few years to come (the week after the Mt Pleasant Show) The weeks before the Mt Pleasant Show are permanently booked for cricket and, from April on, are booked for football

I feel our picnic day could not be totally blamed for poor response to the Walk Against Want. We had 450 people (amateurs and CBers) turn up at Mt Pleasant, this still leaves many hundreds more who could have volunteered to help out if they had been so inclined. Maybe not that many people are interested in WICEN activities.

Steve Johnston VK5ZNJ Box 67 Elizabeth 5112 (Jenny who saw this letter prior to publication, has declined to comment, Ed)

OSI Carris

I refer to the SWL OSLs article in the "Over to You" column of April '92 issue of AR In response to that letter, I would like to

offer some of my own figures, I work DX regularly on 20m, 100 per cent CW I OSL 100 per cent by prior arrangement and reply 100 per cent to SWIs etc. but not to those who want me to pay the expenses both ways Working Stations

- 1 Of those to which I OSL, about 18 per cent reply 2. Of that 18 per cent, about 95 per cent of
- them wast until they receive my card 3. Via the Bureau or Direct the results are
 - 4. A very small percentage of those who
- reply direct will put extra cards in the envelope to be redirected to other parts of Australia. Usually these are okay in the International Callbook, too.

Working Other VKs 1. Better than 90 per cent return rate

2. Again the great majority wait to get that cand first While I have reservations about someone

who would send 200 cards and not receive a single reply. I do appreciate that SWIs would probably find it more difficult to get a renly than we do. However, as a WIA member who attends branch meetings regularly. I can assure you we do see cards that are SWL related going through our OSL bureau on a regular basis

While I do accept there is a problem with OSLs. I don't accept that Australia is the only trouble-spot, and will never accept that we are as bad as that letter made us out to be

Clarrie Hilder VK7HC 5 Speed St

Coope 7320

De-regulation of Licence Conditions

1 am not one who knocks back things which are the result of change, and am happy to go with progress, but what makes me angry is that full-call licence holders again did not get any more privileges

I do not object to an increase of output power for povice and combined licence holders. But, how about an increase of power for full-call licence holders?

We also have the right to align with commonly available 'commercial equipment' Lots of countries have output power from 750 watts to 1 5kW for full-call holders. Only Australia and some other conservative countries are still behind

I worked very hard to get my full call, probably like many others, and I think now is the time for full-call holders to also get something for nothing

Thomas Knopp VK3GTK PO Box 454 Noble Park 3174

A New Name for the WIA

The Wireless Institute of Australia, as a name, has the virtue of simplicity, but the disadvantage of antiquity. It fails to convey to newcomers and the public just what we're about.

Wireless' has fallen so far from any sort of currency in everyday language as to be meaningless to all but 'the cognoscenti' Among young people, the term is wholly eachewed, if not derided. This reflicts very poorly on our image, particularly on first impressions which as is well recognised, are most important.

In this area, the word wireless is an anachronism - 'something placed or occurring out

of its proper time' (Macquarie Dictionary).

We need a name which conveys what we are and what the organisation is about. But we ought not cast aside bolus-bohus our organisation's proud past and honourable traditions.

for the Institute is, after all, the oldest amateur radio organisation in the world. I believe the answer is a simple one; I

propose the new name be the

Amateur Radio Institute of Australia (ARIA)

Amateur Radio states precisely what the members' interests are, and whom the organsation represents. The term 'amateur radio' could, should and would enjoy a wider currency, and with more positive connotations than does the term 'wireless'.

Retaining 'Institute of Australia' retains a link with our current name and its heritage. I note current moves by the ARRL to change its name to 'The American Amateur Radio

League'.

Ladies and gentlemen of the Institute, what do you think?

Roger Harrison VK2ZTB 3/3 Rosemont Ave Woollahra 2025

Stolen Equipment

Stolen from Peter Corkeron VK2AGB on 28 May, one Yaesu FT-2700RH dual-band transceiver, serial number 5L121354. Contact Peter 018 412 629 or Sutherland Polica.

Stolen from Dick Smith Electronics at Parramatta on 13 May, one Yaesu FT-757GX II serial number IL590102. Notify DSE or police.

Stolen from R Clark VK2KSN, 'Walnut Grove', Morga Rd, Canowindra 2804 on 24 April, one Sawtron 999 UHF CB transceiver, serial number 203026.

Baloon Launch QSLs

A reminder is given to all those hoping to acquire "OSL Cards" and certificates for the recent balloon launch to send contact details and \$5.00 to the EMDRC, PO Box 87 Mitcham Vic. Certificates and cards are prepared and await verification of contacts.

Jeff Daiy VK3MFR

Morseword No 64 Solution Page 56 10 Across: 5 1 Lawn 2 Young Stephen 3 Regretted 2 III Jisten 5 Remain 3 Aden's country 7 Roused 4 8 Young Harold 9 Latvia's capital 10 Dreas Down: 1 Bottom 7 2 Don 3 Underwater craft 8 Sheen ■ Snuggeries 6 Mist 10 7 Oath II Touch ■ Mouth 10 Part of a blind © Audrey Ryan 1992

A Support for the Rotary Beam

J A Gazard VK5J 2 Corbin F

(with apologies to the author for the unconventional placement of his article, caused by a last-minute hitch – Ed)

The simplest and cheapest structure for supporting a rotary beam is a guyed pole but, although the guyed pole is structurally sound, this type is seldom used. The reasons for this are

 that to install the beam the structure has to be climbed, and this cannot easily be done with a guved pole, and

(2) the beam, assembled on the ground, has to be hauled up to the pole top, and the guys prevent this.

In discussion with a friend, it was considered that these difficulties could be overered that these difficulties could be overcome if the pole was telescoped into a borchlo in the ground so the top was about two metres above ground in the low position. The beam army could then be mistalled at ground level, and the pole could did not be winched up into its elevated position. The davantages of this scheme would be (1)

The much greater cost and difficulty of erecting a tower or similar support would be avoided.

All installation, adjustment and repair of the beam would be done on the ground, and no climbing would be necessary


This idea seemed feasible to me and I decided as an experimental check to set up a pole support for a 28MHz quad in this way. The pole chosen was a steel tube 50 8mm od, 16mm wall thickness C2* and 176*) which comes in lengths of six me-

tres. It was passed through and supported vertically by a 450mm long sleeve which was held two metres above the boerhole by an angle iron tripod (see fig. 1). A 2° G I water pipe has exactly the right dimension (50,0mm) for the sleeve, and the tripod was formed from available 38 x 38 x 5mm angle iron.

With this arrangement the top wire of the quad was 10 metres above ground, and the borehole depth needed was four metres. The hole was bored with a 6 posthole borer with extensions, and the bore was cased with a 6 plastic dramping it is essenual, the sleeve should be exactly in line with the borehole, and this was achieved as spiral of 1/2" rope and fitted into the free casting which was then lowered into the borehole and set vertically with a spiral level

The borehole was back-filled around the casing by pounng dry sand. The tripod was then lowered onto the pole so the tripod feet, with holding down bolts fitted, came just over pre-drilled foundation bores. These bores were then filled with concrete to the level of the tripod feet.


A thrust bearing for the pole was fitted to the bottom of the slever. This swing away from the centire line so the pole could be raised or lowered and was swung back under the fully raised pole. A fixed collar was fixed to the top of the pole with a loose collar set just above to take the guys. The pole with the quadattached was rotated by hand. A simple home-brew winch was used to raise the pole. This could be done in less than half a minute



The work was carried out single-handed and, except for the bore, was not difficult. I had not expected any difficulty in boring to four metres, as friends in other suburbs had out down drainage bores to 10 metres, but this bore was very difficult. Although it was done at the end of summer, ground water entered the hole below two metres, which made it difficult to bring up the spoil, and then, at about three metres, the clay, which had been compressed by the weight of the overburden for a million years or more. became very hard, and resembled soft rock. It did not soften when wet, and four hours of boring was needed to complete the last metre. A different type of borer might have been more successful

The mast has metall expectations in use to carried the quote at full height for two years and showed no signs of strain in strong winds. It now supports a 2m 'Slim Jini' and the centre of a down-sloping dipole at 10 metres with a drop-in extension, and in this use needs no guys 'The cost of the pole istelf was \$25.50 and the total cost of materials, including guys, was about \$65 of materials, including guys, was about \$65.

This mast was experimental, and its height was suitable only for a 28MHz quad. For general use it would have to be about two metres higher, and a larger steeltube would be preferred. There is a tube made by Tubernakers Ausst which meets these requirements It is styled 'Gall Tube Plus'. It is galvanseed and has and of 60 Jamm, and a wall thackness of 2. Jmm. It comes in lengths of 65 metres, costs 56 per metre and is calculated to be twice as strong as the \$58 mm tube. A length of 2.5 metres joined



to the 6.5 metres, either by a steel insert or by welding would result in a pole with height of 10.5 metres, or about 35 feet, which is ideal for supporting a rotary beam. The bore depth in this case would be 7.5

There is no ready-made sleeve available to fit this larger tube, but one can be made by setting up four angle irons as shown in fig 2. As this sleeve is four-sided, the tripod could be replaced by a four-legged structure, possibly using 3/4° jupe for the legs A beam rotator could be fixed to the bottom of the thrust bearing if the support legs were designed to fit this in.

I estimate the project using the stronger and taller mast could be carried out for a materials cost of about \$100 - a fraction of the cost of a tower. I would suggest that anyone proposing to carry out a similar project should complete the borehole before acquiring any material You may strike rock!

The above is only a general description of the project I would be happy to supply any further information such as sketches of the thrust bearing or winch that I used to anyone proposing to erect a pole

AMERITRON ALB11 600W PEP HF Linear amplifier



- 600W PEP output
- All bands 160-10
 Three 811A tubes
- Quiet fan cooling
- Quiet fan cooling
 Rugged construction
- 50Hz rated transformer
 Easy to use
- Vernier anode tuning
 Large twin meters
- Safety interlock

Amentons choice of the \$11.8 is no accident, nor is it a purely economical one. The \$81A has developed an enviable reputation for robustness and enablishy over many many years of operations nanature and commercial service. Its directly beased the fornated traggering limitent is autumate to said of stripping which can run an expensive undirectly beated tube in a few millinecrosts of the amplifier is mutured.

Amention have downs a simple yet extensionely effective input circuit, a single its reactions with a slagt sender cold for each position of the band switch. The

Amendment coolers a simple yet extention yet in a plan circuit, a single it section while a single in the collection and it is shown to the collection of the collection and it is shown to the collection of the collection and it is shown to the collection of the co

AL-811 \$1449 plus freight

Stewart Electronic Components Pty, Ltd.
ADMINISTRAL ADMINISTRAL 44 Stafford Street Huntingdale: PO Box 281 Oakleigh 3166

Phone (03)543-7238

(34)543-7238

HAMADS

TRADE ADII

 WEATHER FAX programs for IBMXT/ATs, RADFAX \$35, is a high resolution shortwave weatherfax, morse & RTTY receiving program. Needs CGA, SSB hf radio & RADFAX decoder, Also RF2HERC, RF2EGA and RG2VGA, same as RADFAX2 but suitable for Hercules, EGA and VGA cards respectively SATFAX \$45, is a NOAA, Meleor and GMS weather satellite picture-receiving program. Uses EGA or VGA modes. Needs EGA or VGA colour monitor and card + WEATHER FAX PC card, + 137MHz receiver All programs are on 5.25° or 3.5° disks (state which) & ocumentation, add \$3 postage. ONLY from M Delahunty, 42 Villiers St. New Farm Old 4005, Ph (07) 358 2785

♠ AMIDON FERROMAGNETIC CORES: For LF/HF/ VHF/UHF applications. Send DL size SASE for data/ price to RJ & US Imports, Box 431, Kiama NSW 2533 (no enquiries at office, please ... 14 Boanyo Ave. Klama), Agencies at: Geoff Wood Electronics, Sydney, Webb Electronics, Albury; Assoc TV Service, Hobert: Electronic Components, ACT; Truscott Electronics, Melbourne.

IRM-PC CLONES, AMTOR/RTTY/CW/FAX/SSTV. Your selection of modes supplied in one comprehsive program, Details from VK4ASB, 23 Darwin St, Aspley Old 4034, Tel AH; (07) 263 8669.

FOR SALE - NSW

- ALL transistorised com RX band coverage 500kHz to 30MHz for AM, FM, CW, Brand new, Also one pair new headphones with individual vol controls. VK2AXR Al (02) 477 5275.
- RANK 1085 toner, suitable laser printers, refit your cartridge \$5 ono. Varian Aerograph 1200 gas chromatograph (not working) (two) Any offers? Yeesu FT207R 2M handheld with bettery, PA2 charged adepter and speaker/mike. Noel VK2YXM (02) 871
- ◆ YAESU FRG7700 gen cov RX with FRA7700 and amp in original carton with handbooks etc. \$500, S/N 220909. Ray VK2FW OTHR (063) 65 3410.
- TRANSFORMERS HTX 3KV at 350mA primary taps to provide 1.5-2.0-2.5-3kV on sec, \$110. Heater trans 2.5-0-2.5 at 15 amps \$70. 4kV bridge rect to suit above \$30. Ray VK2FW CITHR (063) 65 3410.
- SPECTRUM analyser Siemens model K2001 200Hz-4000Hz near new, \$250. Also impedance bridge Sigmens model R277 30Hz-1 6MHz resistance complex Jay-Gee-C+L, \$200. Peter VK2CPK QTHR (02) 411 1227
- ICOM IC730 with IC HM7 & IC HM10 mics, \$750. ICOM 251A, \$500. ICOM IC2A with speaker-mic, \$275. Azden PCS400, \$350. Manual for above equip ment evalights if required VK2KAN PO Box 1787 Tamworth 2340.
- TOWER tilt-over 70ft freestanding fully galvanised.

\$1000, Kerwood TS820S av/VFO handbook, \$500. Healthkit monitor, \$150. Audio generator, \$80. Various mobile whips from \$50. All illoms open for offers. DAVID VERSE STATES

- TET HBSSC 5-element beam, complete with filtings, GC, owner moved interstate, \$300. VK2AHJ Geome (02) 878 2278.
- ATTENTION radio clubs! Thinking of setting up a 70cm repeater? I have just what you need. A NEC base station with separate transmitter, receiver, 8cavity duplexer. Xtal ovens, 10 watts output, \$400. VK2ATU (02) 792 2275.

FOR SALE UVUI

- MALDOL HS:260 Pws/SWR meter 3.5-150MHz range, VGC, \$40, Paul VK3EPD (059) 83 1771,
- SPEAKER Kernwood SP120 ser no 0050062, as new cond, best offer. VK3GI (054) 27 2576.
- YAESU FT901D \$825, Also FT101B, \$400, Ham 3. rotator, fully recond, \$425. Chas VK3BRZ (052) 82 3167 AH only.
- ATN 9-ele log period entenna 13-30MHz, all stainless hardware. Cost \$1145 sell \$750. Create RC5A-2 worm drive heavy duty rotator, cost \$965 sell \$550. Both less than 12 months old, VK3BCY Morrison QTHR (058) 89 1205.

FOR SALE - OLD

- CHEAP gued enlenges and components 2el 15m spider quad, 4el 15m and 6el 10m spider quad, both all alloy and fibraglass. 16 fibraglass blanks, alloy quad spiders (6). Prices negotiable. 5-band vertical antenna, \$90, VK4CMY (076) 61 7494.
- ♦ YAESU FT206R 2m rig with manual, rubber whice antenna 10 memories GC, ideal for packet, \$200. VK4ARB QTHR (07) 269 8848.

FOR SALE , SA

- YAESU FT400 tranx, spare new finals splir, mike, menual, s/n SO53915, \$250, (08) 381 5676.
- @ 70-FOOT Southern Cross antenna tower in dismantled state, \$1000, VKSBTA QTHR (08) 332 1381.

KLM KT34XA six element tribander, \$200 or offer. VK5RN (08) 339 1210.

FOR SALE - TAS

♠ KENWOOD TSS20S fitted with CW filter, complete with 2xGE 6146B spare finals, MC50 desk mic, handbook, service manual, all perf cond. Has been on low power all its life, \$450. David VK7ZIXJ (004) 25 2030.

WANTED - NSW

 ICOM model UX14 C1-IV/C1-V converter, Art VK2AS OTHR (02) 416 7784.

WANTED - VIC

TONO 9000E RTTY terminal. Will pay top price. Roc VK3AKN QTHR (03) 336 7992. YAESU FT301 tuner. Hawthorn EAST VK3EB

OTHR ■MC50base mic Oskerblock SWR200 Paul VK3EPD

(059) 83 1771

WANTED - OLD

- KW2000 manual or info circuits for KW Electronics 2000 blow. Will pay costs for copies, postage. (07)
- RECEIVER Eddystone EALZ amateur band only; Vibroplex or other 'oup' key, any cond, pair 8950 valves, EC: old tribender TA33 or similar for experiments; Heathkit HD610 coax switch; old ARRL handbooks, Contact Doc (076) 61 7494 AH, (076) 61 6200
- FOR cassette player used or new drive motor. Sankyo VFA2L73 00701-A or similar. Help all costs met. VK4UA (075) 46 7041

WANTED - SA

■ TWO-METRE Breaz Dalwa LA2080H VK5XT OTHR (085) 58 5881

WANTED - WA

PAIR of \$146Bs, new or good used cond. Also VK6BEB QTHR (098) 41 7773

WANTED - TAS

 FT301 ATU, must be in good cond, with manual and circuit. Required to complete 301 station. Contact. David VK7ZDJ (004) 25 2030.

Sign up a new WIA member today we need the numbers to protect our frequencies.

The Eavesdroppers

Signals Intelligence in the South-West Pacific Area - World War II - Jack Bleakley

ISBN 0 644 22303 0

Australian Government Publishing Service, Canberra ACT

The Eavesdroppers is an excellent exposition of the part signals intelligence played in the defeat of the Japanese in the southwest Pacific area (SWPA) by the Allied Porces.

It is of particular interest to the amateur fratemity as many radio hams played an important part in these activities.

The author, lack Bleakley, who served as an intercept operator in the New Guinea and Philippines campaigns, gives a finely balanced account of the experiences of the operators together with the strategy of the American and Australian forces.

The operators used equipment well known to operators of the 1939-40 era. namely SX28s, HROs and AR7s, which performed very reliably in the rigourous tropical conditions

The Japanese Kana code used for the transmission of messages by W/T comprised 71 Kana Morse symbols as against the International Code of 26 alphabet characters. An operating speed of 40-50wpm was commonplace. Furthermore, you couldn't ask for repeats when you were intercepting a message. Maybe our novice and AOCP Morse speeds


are not so unattainable after all! The book is well written in easy-to-read

chapters. Each chapter has a single map before it showing the main locations discussed. and the text starts with a summary of the strategy of the Allied Forces at that particular part of the campaign.

Thus the reader is carried along with the astounding impetus of the island-hopping campaign in the SWPA right through to the Philippines and thence to the surrender of Japan, without having to backtrack to previous chapters and maps to find out what the author is discussing

General Willoughby, who was Macarthur's Chief G2 (Intelligence) said soon after the defeat of Japan that Signal Intelligence chopped two years off the war in the Pacific.

The book is a paperback of handy size -23mm x 14mm - comprises 261 pages and is available from the AGPS Mail Order Sales GPO Box 84 Canberra ACT 2601, Commonwealth Government bookshops in our capital cities and major bookstores at a RRP of \$12.95



(postage included)

A bargain read Reviewed by Quintin Foster L30720 (who is too modest to admit that he bimself was in the "thick of it"! - Ed).

Н	ŀ	a	ľ	ì	1	

ease Note: If you are advertising items For Sale and Wanted please use a separate form
r each. Include all details; og Name, Address, Telephone Number (and STD code), on
ith forms. Please print copy for your Hamad as clearly as possible.
Deter Know ner lakus from to all Wife mambers, night line for name and address.

mercial rates apply for non-members. Please enclose a mailing latel from this sased Estates: The full Harnad will accept in AR, even if the ad its not fully radio

*Copy typed or in block letters to PO Box 300

-												
moo	enclose	0 20f a	ddressed :	stamped	emelo	pe If p	n ackno	wiedge	ement i	s requi	ired	
of the	Harried I	tan Deep	n received.									

sale distributive trades should be certified as referring only to private ws: \$25.00 for four lines, plus \$2.25 p

n charge — \$25.00 pre pays

QTHR means address is con	erts.		

Not for publication:

.

.

ā

i

☐ Miscellaneous

☐ For Sale

☐ Wanted

Address:

Amateur Radio, July 1992

Solution to Morseword No 64 Page 51



Solution for Morseword No 64

Across: 1 green: 2 Steve: 3 rued: 4 hear: 5 stay: 6 Yemen: 7 woke: 8 Hal: 9 Riga: 10 silt.

Down: 1 base: 2 cur: 3 sub: 4 rams: 5 nests: 6 foo: 7 yow: 8 feel: 9 gob: 10 slat.

TRADE PRACTICES ACT

TRADE PRACTICES ACT It is impossible for us to ensure the adver-tisements submitted for publication comply with the Trade Practices Act 1974. There-fore advertisers and advertising agents will appreciate the absolute need for them to ensure that, the provisions of the / compiled with strictly.

VICTORIAN CONSUMER AFFAIRS ACT All advertisers are advised that advertise-ments containing only a PO Box number as the address cannot be accepted without the addition of the business address of the box-holder or selier of the goods.

TYPESETTING: Magazine Graphics PO Box 72

Caulield Sth, 3162 Ph; 528 1033

равлия-Industrial Printing

MAIL DISTRIBUTION: R L Polk & Co Pty Ltd PO Box 140 Tel:(03) 417 5181

VK1

ADVERTISERS INDEX JULY 1992

Amateur Radio Action ... ATM Anto-

ATIV ATILETITIAS20
Dick Smith Electronics31-33
Electronics Assembly Co 18
Electronics World Disposals 13
ICOMOBC
Jenlex Filters11
Kenwood ElectronicsIFC
Stewart Electronics52
WIA BookshopsIBC
WIA NSW Division34

Trade HAMADS	
M. Delahunty5	4
D Ralph5	4
RJ & US Imports5	4

HOW TO JOIN THE WIA

Fill out the following form and send to:

The Membership Secretary Wireless Institute of Australia PO Box 300 Caulfield South, Vic 3162

I wish to obtain further information

about the WIA.

Mr. Mrs. Miss. Ms:

Call Sign (if applicable):

Address:

State and Postcode: ...

VK QSL Bureaux

The official list of VK QSL Bureaux. All are Inwards and Outwards unless otherwise stated.

GPO Box 600 Canberra ACT 2601

VK2 PO Box 73 Teralba NSW 2284

VK3 40G Victory Blvd, Ashburton Vic 3147 VK4

GPO Box 638 Brisbane Old 4001

VK5 PO Box 10092 Gouger St Adelaide SA 5000

VKG GPO Box F319 Perth WA 6001

VK7 GPO Box 371D Hobart Tas 7001

VKR C/o H G Anderson VK8HA Box 619 Humpty Doo NT 0836

VK9/VK0 C/o Neil Penfold VK6NE

2 Moss Court Kingsley WA 6026

WIA Divisional Bookshops

The following items are available from your Division's Bookshop (see the WIA Division Directory on page 3 for the address of your Division)

ANTENNA BOOKS	Ref	Price is Members		Rei	Price to Members
Art. Compendium Vol 2 Software only	BX293	\$18.00	MORSE CODE (Cont.)		
Aniasra Compendium Vol 1 ARRIL	BX163	\$15.80	Monto Code Tapes Set 1: 5-10 WPM - ARRI.	BX331	\$16.70
Antenna Compendium Voi 2 & Soltware ARRIL	ID294	\$32.40	Morse Code Tapes Set 2: 10-15 WPM - ARRI,	BX332	\$16.70
Antenna Compendium Vol 2 ARRE.	80/292	\$21.60	Morse Code Tapes Set 3: 15-22 WPM - ARRL	BX333	\$15.70
Antenna Impedance Matching - ARRL - 1989 Astenna Note Book W1FB - ARRL - 1987	BX257 BX179	\$27.00	Morse Code Tapes Set 4: 13-14 WPM - ARRI, Morse Tutor 5.25 sech (EM Dea)	BX334 BX187	\$16.70
Adminia Mode Book W1FB - ARPIL - 1987 Avvance Pallert Worksheets Pki of 10 - ARRIL	BX1/9	\$5.40	Morse Tutor 5.25 arch IBM Disa	EX187	\$18.00
Artennas 2nd ed John Kraus - 1968	BX259	\$83.60	(PERATING		
Beam Antenna Handbook - New ED, 1990 Orr	80215	\$23.00	Arrustour Radio Awards Book - RSS8	BX297	\$27.00
Easy Up Antennas	ME/DS	\$35.30	DICC Companion FCC Rule Book A Guide to the FCC Regulations	BX345	\$10.80
HF Antennas - Moxen RSGB - 1968	(CX 188	\$27.00	FCC Rule Book A Guide to the FCC Regulations	BX379	\$16.20
Novice Antenna Rolebook Delitaw - ARRS,	BX162	\$14.40	Low Band Cixing - John Devoldere	BX195	\$18.00
Practical Wire Antennas - RSGB	BX296	\$25.20	Maidenhaad Locator-Grid Allas - ARRIL Operating Manual - ARRIL - 1990 3rd Edition	BX197 BX192	\$9.00
Reflections - Software Sin disk Reflections - Transmission lines The Book - ARRE - 1990	8X358 8X348	\$18.00		BX192	\$27,00 \$25,20
Simple Low Cost Wire Antennas	80218	\$23.00	Passport to World Band Radio 1991	80048	\$30.60
Smith Chart Expanded Scale PK of 10	BXSC3	\$5.90	Prefix Map of North America	BX235	37.20
Smith Charts S/Scale 1 Set co-ord Imp/Admir Pack of 10	BX900	\$5.90	Short Wave Propagation Handbook	BX268	\$15.70
Smith Charts Stand Scale 1 SET Co-or. PK of 10	BX900-	\$5.90	The Complete OXer - Bob Locher - 1989	BX194	\$18.00
The Antenna Hundbook - ARRIL1991, 16th edition	BX370	\$36.00	Transmitter Hunting - TAB - 1967	BX222	\$32.30
The Truth About CB Antennas - Orr	BX219	\$23.00	PACKET BADIO BOOKS		
Transmission Line Transformers - ARRL 2nd odition	BX329 BX284	\$36.00	AX 25 Link Laver Protocol - ARRIL	BX178	\$14.40
Vertical Antenna Handbook - Lee - 1990	BX284	\$16.70	Computer Networking Con (Packet) No 5 1985 - ARRI.	BX167	\$15.00
Yagi Antenna Design - ARRL - 1986	BX 104	327.00	Computer Networking Con (Packet) No 6 1967 - ARPS	8X168	\$18.00
ATV BOOKS			Computer Networking Con (Packet) No 7 1988 - ARRI,	8X184	\$22.50
The ATV Compendium - BATC	BX270	\$15.80	Computer Networking Con (Packet) No 8 1989 - ARRE	BX295	\$21.60
			Computer Networking Con (Packet) No 9 1990 - ARRIL	BX360	\$21.60
CALL BOOKS			Computer Networking Con (Packet) No 10 1991 - ARRU	8X387	\$22.50
Radio Call Book international	80339	\$57.50	Computer Retworking Conf (Packet) 1-4 1982/5	8X165	\$32.40
Radio Call Book North America	BX338	\$57.50	Galtrusy to Packet Radio 2nd edition - ARRL Packet Radio Made Easy - Rosers	BX169 MFJ32	\$18.50
FICTION			Facility made casy - nogets	BCF332	\$10.00
CO Brings Danger - ARRI,	B00206	\$2.40	SATELLITE BOOKS		
CO Ghost Ship - ARRE.	8x204	\$9.40	Oscar Satelite Review - Ingram	64FJ31	\$15.30
Death Valley QTH - ARRIL	800205	\$9.40	Salelite AMSAT-HA Str. Symposium 1987 - ARRI,	BX185	\$15.80
Grand Carryon GSO - ARRIL	8x207	\$9.49	Satellite AMSAT-NA 6th Sympotium - ARRL	BX199	\$15.80
Morder By ORM - ARRI.	BX208	\$9.40	Satelite Anthology - ARRI.	8X180	\$14.40
SOS At Midnight - ARRL	8x209	\$9.40	Saletille Experimenters Handbook 1990 edition Space Alimanuc - ARRI, - 1990	BX177 BX299	\$36.00 \$36.00
HANDEGOOKS			Weather Saletite Handbook - ARRIL	BX324	\$36.00
ARRI, Handbook - 1992	80069	\$47.60	Weather Satellite Handbook Software only - ARFIL	BX326	\$18.00
Electronics Data Book - ARRIL - 1988	80(201	\$21.60		D. III.	4.0.00
Mobile Radio Handbook	MF,J33	\$22.50	THE/DHE/MICROWAVE		
Motorola RF Device Data - 2 Volumes	83347	\$23.00	All About VYF Anutewo Radio - Ciri - 1988	BX216	\$23.00
Radin Communication Handblook - RSSB Radio Handbook 23rd edition - Bill Orr	8X256 BX224	\$50.40 \$53.90	Microwave Handbook Vol 1 - RSGB - 1985 Microwave Handbook Vol 2 - RSGB - 1992	800318 800437	\$63.00
Radio Theory For Ameteur Doerstors - Swakeston - 1991	BX255	\$38.75	Microwave Update Con. 1987 - ARRI,	BX174	\$15.80
Hadro Trecky For America Optrosors - Sweetston - 1991	80,000	238.70	Microwave Update Con. 1969 - ARRI,	BX1/4	\$15.80
HISTORY			Microwave Opdate Con. 1989 - ARRIL	800321	121.50
200 Meters and Down 1936 - ARRIL	8X198	\$7.20	Mid Atlantic VHF Con. October 1987 - ARRL	BX175	\$15.40
50 Years of the ARRL - 1981	8X196	\$7.20	Sorend Spectrum Source Book - ARRI, - 1991	BX355	\$38.00
Big Ear - Aufobiography Df John Kraus WEJK - 1975	800363	\$11.30	UHF Compendium Part 1 & 2 Vol 1	B00250	\$67.50
Golden Classics of Yesterday - Ingram	MEJ30	\$19.40	UHF Compendium Part 3 & 4 Vol 2	BX251	\$67.50
Spark to Space - ARRL 75th Anniversary - 1999	82310	\$36.00	UHF Compendium Part 5 German Only	83354	\$50.20
INTERPENDICE SCORES			URF Microwave Experimenters Manual - ARRI, - 1990 URF Microwave Experimenters Software 5 Inch Disk - ARRI,	8X325	\$36.00 \$18.00
Interference Handbook - Neison - 1989	8X181	\$23.00	VMF 21st Central States Con. 1987 - ARRE.	BX177	\$15.80
Radio Frequency Interlerence - ARRE,	BX186	\$27.00	VHF 22nd Central States Con. 1987 - ARRI.	BX172	\$15.80
			VHF 23rd Central States Con. 1989 - ARRI,	8X236	\$15.80
MISCELLANEOUS			VHF 29th Central States Con. 1990 - ARFL	BX322	\$21.60
Arridon Ferrite Complete Data Book Design Notebook W1FR - ARRL	8004 80057	\$9.00	VALLUE Names - RSGB	BX287	\$43.20
Ham Radio Communications Circuit Files	8A357 MF.337	\$12.50			
Helo For New Harns Celiforn - ARRL	53300	\$18.00	WIA MEMBERS SUNDRIES		
Hints and Kinks 12th edition - ARRL	80730	314.40	Log Book Covers		\$18.00
Movice Notes, The Book - ARRL OST	80298	\$10.50	WA Badge - Diamond		\$4.00 \$4.00
DRP Classics - ARRI, OST	60023	321.50	WA Budge - Diamond With Call Sign Space WA Budge - Traditional Blue		\$4.00
DRP Note Book - New 2nd edition ARRIL	8X170	\$15.00	WIA Bodge - Traditional Red		\$4.00
Radio Astronomy 2nd edition - John () Kraus	80252	\$71.98			50 50
Fadin Aurosas RSUE New 1921	80/381	\$27.00	WA Tape - Sounds of Amsteyr Redio		\$7.00
Racko Buyers Source Book - APRL - 1991	80377	\$27.00			
Shortwave Receivers Past and Present	BX253 BX171	\$19.88	WIA PUBLICATIONS Autoritian Radio America Call Book - 1952		\$10.00
Solid State Design - DeMaw ARRs.	BX171	321.69	Band Plans Booklet		\$2.50
MORSE CODE			WIA Log Book - Horizontal or Vertical Format		\$5.00
Advanced Morsa Tutor - 3.5 inch Disk	80028	\$36.00	WITA REVIEW South Guide		\$1.50
Advanced Morse Tutor - 5.25 inch Disk Morse Code 6 Tapes Novice Code Course - Gordon West	EXTRE	\$36.00			
	BX229	\$63.90			

Not all fittens above are available from all Divisions (and none; is available from the Executive Office).

If the ten its carried by your Divisional Bloobleshe, but it not its stack, your order will be taken and filled as soon as practicable.

All prices are for WIA members only - postage and packing, if applicable, is extraall orders must be accompanied by a resultance.





IC-765

Our Base Units Have So Many Features, These Pictures Speak Louder Than Words.



IC-781

ur features speak volumes.

Rather than write hundreds of words to introduce our range of base units, we'd like you to phone us free on (008) 338 915.

We'll provide you with detailed brochures

and the name of your nearest authorised Icom dealer.

Alternatively, you can write to Reply Paid 1009 Icom Anstralia Pty Ltd P.O. Box 1162 Windsor Victoria 3181. Telephone (03) 529 7582 A.C.N. 006 092 575

L.L. Brown Advertising 3909